


AIR TREATMENT AND GAS GENERATION

Product Catalogue 2021



Pneumatech Air Treatment



Contents

Refrigeration Dryers..... 7

Cool 12 - 272 - Non-cycling refrigeration dryers.....	8
AD15 - 3000 - Non-cycling refrigeration dryers	10
Anti-corrosion treatment	13
AC 15 - 200 - Cycling refrigeration dryers	14
AC 200 - 630 VSD - Refrigeration dryers	16
AC 650 - 2100 - Large cycling refrigeration dryers	18
AC 2650 - 8500 - Large cycling refrigeration dryers.....	20

Adsorption Dryers 23

PH 2 - 45 HE - Extruded profile heatless adsorption dryers	24
PH 55 - 550 HE - Extruded profile heatless adsorption dryers	26
PH 760-3390 HE - Welded vessel heatless adsorption dryers	28
PH 55 - 550 S - The cost-efficient alternative to PH 55-550 HE.....	30
PE 760 - 3390 S - Heated purge adsorption dryers.....	32
PB 210 - 635 HE (P/ZP) - Blower purge/ zero purge adsorption dryers	34
PB 700 - 6350 HE (P/ZP) - Blower purge/ zero purge adsorption dryers	36
PB 760 - 3390 S - The cost efficient alternative to PB 700-2950 HE.....	38

Membrane Dryers 41

M POU 2 - 16 - Point-of-use membrane dryers.....	42
PMD 1 - 7 - Membrane dryers	44

Gas Generators..... 49

PPNG 6 - 68 HE - Nitrogen generator with pressure swing adsorption technology	50
PPNG 6 - 68 S - Nitrogen generator with pressure swing adsorption technology	52
PPNG SKID - High-pressure nitrogen skid.....	54
PPNG 150 - 800 HE - Nitrogen generators with pressure swing adsorption technology.....	56
PMNG 1 - 3 Nitrogen generator with membrane technology	58
PMNG 5 - 75 S - Nitrogen generator with membrane technology.....	60
PPOG 1 - 120 - Oxygen generator with pressure swing adsorption technology	62
Oxygen solutions	64

Breathing Air Solutions 67

BA 25 - 300 HE - Breathing air purifiers	68
BA 25 - 300 S - Breathing air purifiers.....	70

Filter Solutions 73

Ultimate water separators.....	74
Ultimate filters - Threaded filters.....	76
Ultimate filters - Elements.....	78
Ultimate filters - Industries.....	80
FF 1 - 12 - Flanged filters	82
VT - Activated carbon towers + vessels.....	84
HP - High pressure filters	86
SLF - Silicone free filters	88
FP & FP HP - Process filters	90
FS - Sterile filters.....	92
TF DC - Filters with desiccant cartridges	94
TF CC & TF HC - Filters with activated carbon & hopcalite cartridges.....	95
Competitor spare parts - Alternative line filter cartridges	96
Competitor spare parts - Alternative desiccants.....	98

Condensate Management 101

WD - Water detector	102
LD 100 - 204 - Zero loss drains	104
TD - Timer drain.....	106
MD - Mechanical zero-loss float drain	107
ECOBX 2 - 4 - Oil water separators.....	108
OWS 25 - 5300 - Oil water separators.....	110
CA - Air cooled aftercoolers.....	112
CW 1 - 17 - Water cooled aftercoolers	114

Piping Systems..... 117

AIRnet - Aluminium range	118
AIRnet - Stainless steel range	120

For compressed air measurement equipment please
email us on support-eu@pneumatech.com for separate
catalogue or visit our website www.pneumatech.com



Compressed Air Treatment

Untreated compressed air always contains contaminants because of the nature of the gas and how it is produced. The need for air treatment basically results from 3 characteristics of compressed air.


Compressed air is always wet

Contaminants

- Liquid water - water aerosols - water vapor

How are the contaminants formed?

As water is incompressible, the amount of moisture per m^3 increases when air is compressed. The maximum amount of moisture per m^3 air¹ is however limited for a certain temperature. Condensation will thus be formed when air is compressed.



What problems can the contaminants cause?

- Corrosion of pipe lines
- Bad quality of the end product
- Malfunctioning of controls
- Build-up of ice
- Cultivation of micro-organisms

The Pneumatech solution

- Water separators
- Drains
- Refrigeration dryers
- Adsorption dryers

¹The so-called holding capacity of moisture in air.

Compressed air is always contaminated


Contaminants

- Liquid oil - oil aerosols - oil vapor
- Dirt - microorganisms - pipescale
- Trace gases: carbon monoxide, sulfur dioxide, nitrous oxide

How are the contaminants formed?

Added by the compressor installation through oil lubricated compressors (oil), adsorption dryers and activated carbon filters (dirt), piping network and vessels (pipescale).

Trash in, trash out: oil vapors from car exhausts and industrial processes, atmospheric dirt and microorganisms get sucked in by the compressor. As with water, their concentration – and thus importance – increases significantly after compression.



What problems can the contaminants cause?

- Damaged production equipment, leading to inefficiencies and increased costs
- Air pollution, creating unhealthy work environments
- Pollution of the condensate

The Pneumatech solution

- Coalescing filters for oil aerosols/particles
- Oil vapor filters
- Dust filters
- Oil-water separators
- Breathing air units


Compressed air composes of other gases

Contaminants

- Oxygen: contaminant if oxidation is unwanted
- Nitrogen: contaminant if oxidation is wanted

How are the contaminants formed?

Dry air is mainly composed of nitrogen (78%) and oxygen (21%). Air will keep the same nitrogen/oxygen ratio after compression, so additional treatment is needed to change this gas mix.



What problems can the contaminants cause?

- Oxygen causes oxidation, leading to explosions or fire of flammables (fast oxidation) or to rotting processes and corrosion of metals (slow oxidation).
- Nitrogen is an inert gas that can prevent oxidation to happen.

The Pneumatech solution

- PSA nitrogen generators
- Membrane nitrogen generators
- PSA oxygen generators

In-house design & manufacturing

Within Pneumatech we design and produce all our core drying, filtration and gas generator products in-house. We invest 3% of our total revenues in R&D. This results in an expert know-how of drying & filtration mechanisms, state-of-the-art test facilities and breakthrough innovations. From operations side, we distinct ourselves with our high level of automation and quality control in triple certified manufacturing production plants.





Refrigeration dryers

With our refrigeration dryers too, we let you choose between investment cost and lifecycle cost.

Pneumatech's COOL range is our robust, no-frills drying solution, meant for basic condensate removal in your compressed air system. With the AD dryers we guarantee dry air through real-time PDP monitoring, while also reducing power consumption and compressed air losses. Our premium AC dryers optimize the energy consumption based on the actual compressed air demand, through energy saving algorithms or variable speed technology.

Cool 12 - 272 - Non-cycling refrigeration dryers

Features & Benefits

- ▶ Solid performance & strong reliability
 - Stable pressure dew point as low as 5°C/41°F ensuring ISO 8573-1 class 5 quality
- ▶ Compact & easy to install
 - Simple vertical design
 - Plug- and play mechanical & electrical connections
- ▶ Super cost saver
 - Low initial investment
 - Efficient cooling system ensures low energy costs
 - Increased lifetime of tools and equipment
- ▶ Easy maintenance at low cost
 - Long service intervals
 - Easy access to key components

General Specifications

- ▶ Non-cycling refrigeration dryers
- ▶ Operating pressure: 4-16 barg/58-232 psig (4-13 barg/58-189 psig from COOL 145 onwards)
- ▶ Max. ambient temperature: 50°C/122°F
- ▶ Flow rate: 21 to 462 m³/hr (12-272 cfm)⁽¹⁾
- ▶ Pressure dew point: 5°C/41°F (ISO 8573-1:2010 class 5)
- ▶ Power supply: 230VAC 50 Hz (60Hz version on request)
- ▶ Refrigerant: R134a (COOL 12-145) or R410A (COOL 184-272)



Applications



Pneumatic tools and equipment



Pneumatic control systems



Painting



Injection moulding



Car shops



Tire inflations

¹ Flow is measured at reference conditions: ambient pressure of 1 bara and 25°C at operating pressure of 7 barg, inlet temperature 35°C .



The compressed air coming out of the compressor is always saturated. Pneumatech's reliable and robust COOL refrigeration dryers are an efficient solution to lower the presence of moisture and the resultant corrosion in your compressed air system. COOL dryers can act as a second line of defence after water separators and aftercoolers giving you a stable dew point as low as 5°C/41°F, maintaining the ISO 8573-1 class 5 air quality.

Designed to work up to 16 barg/232 psig, COOL dryers deliver stable performance thanks to the efficient refrigerant gas and carefully selected components. The simple vertical design and small foot print make COOL dryers the easy-to-use drying solution in various industrial applications such as car shops, spray painting, injection moulding, tire inflation and many more.

Technical specifications for COOL 12-272 50 Hz													
Pneumatech Variants →	Units	COOL 12	COOL 21	COOL 30	COOL 42	COOL 64	COOL 76	COOL 106	COOL 127	COOL 145	COOL 184	COOL 230	COOL 272
Specifications ↓													
Flow ⁽¹⁾	l/s	5.8	10.0	14.2	20.0	30.4	35.8	50.0	60.0	68.3	86.7	108.3	128.3
	m³/hr	21	36	51	72	110	129	180	216	246	312	390	462
Nominal electric power	kW	0.13	0.13	0.16	0.28	0.32	0.30	0.42	0.68	0.74	0.70	0.75	0.95
Power Supply Voltage/Phase		230/50/1	230/50/1	230/50/1	230/50/1	230/50/1	230/50/1	230/50/1	230/50/1	230/50/1	230/50/1	230/50/1	230/50/1
Max Operating Pressure	barg	16	16	16	16	16	16	16	16	13	13	13	13
	psig	232	232	232	232	232	232	232	232	188	188	188	188
Refrigerant Gas		R134a	R134a	R134a	R134a	R134a	R134a	R134a	R134a	R134a	R410A	R410A	R410A
Inlet and Outlet Connections	G Threads	1/2" F	1/2" F	1/2" F	1/2" F	1/2" F	3/4" F	1" F	1" F	1 1/2" F	1 1/2" F	1 1/2" F	1 1/2" F
Dimensions	L (mm)	233	233	233	233	233	233	233	310	310	310	310	310
	L (inch)	8.8	8.8	8.8	8.8	8.8	8.8	8.8	12.2	12.2	12.2	12.2	12.2
	W (mm)	550	550	550	550	550	550	559	706	706	706	706	706
	W (inch)	22	22	22	22	22	22	22	27.8	27.8	27.8	27.8	27.8
	H (mm)	561	561	561	561	561	561	561	994	994	994	994	994
	H (inch)	22.1	22.1	22.1	22.1	22.1	22.1	22.1	39.1	39.1	39.1	39.1	39.1
Weight	kg	19	19	19	20	25	27	30	52	57	59	80	80
	lbs	42	42	42	44	55	59	66	114	125	130	176	176

1.Flow is measured at reference conditions: ambient pressure of 1 bara and 25°C at operating pressure of 7 barg, inlet temperature 35°C.

Correction factors for ambient temperature					
Ambient temperature	°C	25	30	35	40
	°F	77	86	95	104
Temperature correction factor	Kt (amb)	1	0.92	0.84	0.8

Correction factors for compressed air inlet temperature						
Inlet temperature	°C	30	35	40	45	50
	°F	86	95	104	113	122
Temperature correction factor	Kt	1.24	1	0.8	0.69	0.54

Correction factors for compressed air inlet pressure													
Operating pressure	barg	5	6	7	8	9	10	11	12	13	14	15	16
	psig	73	87	101	116	131	145	159	174	188	203	218	232
Pressure correction factor	Kp	0.9	0.96	1	1.03	1.06	1.08	1.1	1.12	1.13	1.15	1.16	1.17

AD 15 - 3000 - Non-cycling refrigeration dryers

General specifications

- ▶ Non-cycling refrigeration dryers
- ▶ Operating Pressure:
 - AD 15 - 50: 4-16 barg/60-232 psig
 - AD 85 - 3000: 4-14 barg/60-203 psig
- ▶ Max. inlet temperature: 55°C/113°F
- ▶ Flow rate: 21 - 5040 m³/hr/
22 - 2966 cfm⁽¹⁾
- ▶ Pressure dew point: up to +3°C/37°F
- ▶ Power supply:
 - AD 15 - 270: 230V AC 50/60 Hz
 - AD 355 - 3000: 400V/50Hz; 380V/60Hz; 460V/60Hz
- ▶ Refrigerant: R513A (AD 15 - 105);
R410A (AD 125 - 1250);
R452A (AD 1600 - 3000)

Refrigeration Dryers: AD Series (15-3000) Non cycling

AD 15-65	AD 85-105
	
Features & Benefits	Features & Benefits
<ul style="list-style-type: none"> Stable performance and guaranteed dew point up to 3°C/37°F Ingeniously designed components to ensure maximum performance <ul style="list-style-type: none"> Hot gas bypass valve to prevent freezing at lower loads Zero-loss electronic drain to prevent loss of valuable compressed air Brazed plate heat exchanger with integrated water separator and air-to-air heat exchange R513A refrigerant gas: low global warming impact, zero ozone depletion Digital display with real-time PDP monitoring Easy plug-and-play installation 	<ul style="list-style-type: none"> Stable performance and guaranteed dew point up to 3°C/37°F Ingeniously designed components to ensure maximum performance <ul style="list-style-type: none"> Hot gas bypass valve to prevent freezing at lower loads Zero-loss electronic drain to prevent loss of valuable compressed air Aluminium block heat exchanger with integrated water separator and air-to-air heat exchange Environmental safe refrigerant gases R513A Digital display with real-time PDP monitoring Easy plug-and-play installation

Options



Filter support



Bypass valve

Pneumatech's AD 15-3000 non-cycling refrigeration dryers are designed to protect your compressed air system by lowering the presence of moisture in the compressed air. Thanks to the new controller with digital display, real time PDP monitoring is possible. The zero-loss electronic drains avoid compressed air losses. The well-designed heat exchangers ensure maximum cooling efficiency, making the AD dryers a genuine air drying solution in industrial applications. The AD15-105 is introducing the efficient and environmental friendly R513A refrigerant, reducing the global warming potential largely.

The AD125-1250 range is equipped with the winning combination: rotary compressors and R410A refrigerant. This combination is up to 30% more energy efficient, requires 19% less refrigerant gas and is 100% compliant with European regulation EU No 517/2014, hereby significantly reducing the ecological footprint of these dryers. Rotary compressors are moreover very reliable thanks to the low vibration levels and limited mechanical load. R410A guarantees stable evaporation, which makes the pressure dew point of up to 3°C/37°F achievable.

AD 125-270	AD 355-1250	AD 1600 - 3000
		
Features & Benefits	Features & Benefits	Features & Benefits
<ul style="list-style-type: none"> Stable performance and guaranteed dew point up to 3°C/37°F Rotary compressors and R410A refrigerant: the winning combination <ul style="list-style-type: none"> 30% more energy efficient Requires 19% less refrigerant gas Extremely reliable: low vibration levels and limited mechanical load Ingeniously designed components to ensure maximum performance <ul style="list-style-type: none"> Hot gas bypass valve to prevent freezing at lower loads Zero-loss electronic drain to prevent loss of valuable compressed air Aluminium block heat exchanger with integrated water separator and air-to-air heat exchange Digital display with real-time PDP monitoring and voltage-free contact for remote alarm Easy plug-and-play installation 	<ul style="list-style-type: none"> Stable performance and guaranteed dew point up to 3°C/37°F Rotary compressors and R410A refrigerant: the winning combination <ul style="list-style-type: none"> 30% more energy efficient Requires 19% less refrigerant gas Extremely reliable: low vibration levels and limited mechanical load Ingeniously designed components to ensure maximum performance <ul style="list-style-type: none"> Hot gas bypass valve to prevent freezing at lower loads Zero-loss electronic drain to prevent loss of valuable compressed air Aluminium block heat exchanger with integrated water separator and air-to-air heat exchange Advanced controlling and monitoring thanks to the controller installed <ul style="list-style-type: none"> Digital PDP display Remote start/stop Voltage-free contact for general alarm Easy plug-and-play installation 	<ul style="list-style-type: none"> Stable performance and guaranteed dew point of 3°C/37°F. Ingeniously designed components to ensure maximum performance <ul style="list-style-type: none"> Hot gas bypass valve to prevent freezing at lower loads Zero-loss electronic drain to prevent loss of valuable compressed air Aluminium block heat exchanger with integrated water separator and air-to-air heat exchange Environmental safe refrigerant gases R452A Advanced controlling and monitoring <ul style="list-style-type: none"> Digital PDP display Remote start/stop Voltage-free contact for general alarm Easy plug-and-play installation

¹ Flow is measured at reference conditions: ambient pressure of 1 bara and 25°C at operating pressure of 7 barg, inlet temperature 35°C .

AD 15 - 3000 - Non-cycling refrigeration dryers

Technical specifications for AD 10-3000 50Hz

Pneumatech Variants →	Units	AD 15	AD 20	AD 30	AD 40	AD 65	AD 85	AD 105	AD 125	AD 145	AD 185	AD 230	AD 270	AD 355	AD 425	AD 530	AD 635	AD 750	AD 1000	AD 1250	AD 1600	AD 1800	AD 2500	AD 3000
Specifications ↓																								
Flow ⁽¹⁾	l/s	6	10	14	20	30	39	50	60	68	87	108	128	167	200	250	300	400	500	583.3	750	833.3	1166.7	1400
	m³/hr	22	36	50	72	108	140	180	216	245	313	389	461	601	720	900	1080	1440	1800	2100	2700	3000	4200	5040
Nominal electric power	kW	0.13	0.164	0.19	0.266	0.284	0.674	0.716	0.613	0.705	0.905	0.969	1.124	1.54	1.98	2.01	2.77	3.26	3.89	4.75	6.715	6.8	10.2	12.3
Power Supply/ Voltage/Phase	V/Hz/ Ph	230 50 1	230 50 1	230 50 1	230 50 1	230 50 1	230 50 1	230 50 1	230 50 1	230 50 1	230 50 1	230 50 1	230 50 1	400 50 3	400 50 3	400 50 3	400 50 3	400 50 3	400 50 3	400 50 3	400 50 3	400 50 3	400 50 3	
Max Operating Pressure	bar	16	16	16	16	16	14	14	14	14	14	14	14	14	14	14	14	14	14	14	14	14	14	14
	psi	232	232	232	232	232	203	203	203	203	203	203	203	203	203	203	203	203	203	203	203	203	203	203
Refrigerant Gas		R513AR513AR513AR513AR513AR513AR513AR410AR410AR410AR410AR410AR410AR410AR410AR410AR410AR410AR410AR410AR410AR452AR452AR452AR452A																						
Inlet and Outlet Connections	inch/ DIN	3/4"M	3/4"M	3/4"M	3/4"M	3/4"M	1"F	1"F	1" 1/2F	1" 1/2F	1" 1/2F	1" 1/2F	1" 1/2F	2"F	2"F	2" 1/2F	2" 1/2F	3"M	3"M	3"M	DN 125	DN 125	DN 125	DN 125
Dimensions	L (mm)	350	350	350	350	350	370	370	460	460	460	580	580	805	805	805	805	1020	1020	1020	1020	1020	1020	1020
	L (inch)	13.8	13.8	13.8	13.8	13.8	14.6	14.6	18.1	18.1	18.1	22.8	22.8	31.7	31.7	31.7	31.7	40.2	40.2	40.2	40.2	40.2	40.2	40.2
	W (mm)	493	493	493	493	493	497	497	557	557	557	587	587	1070	1070	1070	1070	1083	1083	1083	1121	2099	2099	2099
	W (inch)	19.4	19.4	19.4	19.4	19.4	19.6	19.6	21.9	21.9	21.9	23.1	23.1	42.1	42.1	42.1	42.1	42.6	42.6	42.6	44.1	82.6	82.6	82.6
	H (mm)	450	450	450	450	450	764	764	789	789	789	899	899	962	962	962	962	1526	1526	1526	1526	1535	1535	1535
	H (inch)	17.7	17.7	17.7	17.7	17.7	30.1	30.1	31.1	31.1	31.1	35.4	35.4	37.9	37.9	37.9	37.9	60.1	60.1	60.1	60.1	60.4	60.4	60.4
Weight	kg	19	19	20	25	27	44	44	53	60	65	80	80	128	146	158	165	325	335	350	380	550	600	650
	lbs	42	42	44	55	60	97	97	117	132	143	176	176	282	322	348	364	717	739	772	838	1213	1323	1433

(1) Flow is measured at reference conditions: ambient pressure of 1 Bar(a) and 25°C at operating pressure of 7 bar (g), inlet temperature 35°C.

Correction factors for ambient temperature

Room temperature	°C		25	30	35	40	43	46
	A	AD 15-270	1	0.92	0.84	0.8	0.79	-
		AD 355-3000	1	0.91	0.81	0.72	-	0.62

Operating temperature	°C					50	55	60	
	B	AD 15-270	1.24	1	0.82	0.69	0.58	0.45	-
		AD 355-3000	1	1	0.82	0.69	0.58	0.49	0.42

Operating temperature	bar		5	6	7	8	9	10	11	12	13	14	15	16
	C	AD 15-270	0.9	0.96	1	1.03	1.06	1.08	1.1	1.12	1.13	1.15	1.16	1.17
		AD 355-3000	0.9	0.97	1	1.03	1.05	1.07	1.09	1.11	1.12	1.15	-	-

Anti-corrosion treatment (available for all refrigerant dryers)

Technical specifications

Coating type	Aluminum pigmented polyurethane
Color	Champagne
Pretreatment	Degreasing
Temperature Range (dry)	-20 to 150°C (-4° to 302°F)
Substrates	Aluminum and Copper
ASTM B117	4000+ hours(neutral-salt spray test)
Kesternich (2.0 ltr SO ₂)	80 cycles
Layer Thickness	25-30 µm (1 mil)
UV Resistance	Excellent
Adhesion (cross hatch)	0 (European) 5b (USA)
Chemical Resistance	Excellent

Coating resistance of some typical corrosive gas vapors (based on exposure temperature of 20°C/68°F) – maximum concentrations

Chlorine	64 ppm	Ethanol	320 ppm
Ammonia	160 ppm	Sulphuric acid	320 ppm
Phosphoric acid	320 ppm	Seawater	640 ppm



Problem

Refrigerant dryers can be subjected to severe corrosion when placed in environments rich of e.g ammonia and sulfurs, or close to the seaside. In these cases incompatible metals like copper will be affected since the condenser-fan is blowing a high volume of polluted air through the dryer. Corrosion and pollution of condensers will directly impact the dryer performance. Corrosion can even lead to leaks in the condenser and refrigeration piping.



Solution

Pneumatech offers a long-lasting corrosion protection to the condenser and the refrigerant piping without affecting heat transfer and pressure drop. The heat conductive pigmentation in the coating is oriented in such a way that it creates a very high chemical resistance at a low layer thickness. Therefore it is considered the best available option to prevent refrigeration dryer failure and unnecessary energy consumption.

AC 15 - 200 - Cycling refrigeration dryers

Features & Benefits

- ▶ Premium energy efficiency
 - Energy-saving & flow control: adapt energy consumption to the real load
 - Lowest pressure drop over heat exchanger and air piping
 - Zero-loss drains
- ▶ Strong performance & reliability
 - Stable pressure dew point as low as 3°C
 - Guaranteed drying performance in wide range of ambient temperatures
- ▶ Optimal control and monitoring
 - Energy-saving control
 - Voltage-free contact for remote alarm
 - Auto-restart after voltage-failure
 - Communication via industrial protocols like Modbus, Profibus or Ethernet/IP (for AC250-600 only)
- ▶ Easy installation and maintenance at low cost
 - Pipe connections on top
 - Long service intervals
 - Easy access to key components

General Specifications

- ▶ AC refrigeration dryers: cycling type
- ▶ Operating pressure: 4-16 barg/58-232 psig (4-14 barg/58-189 psig from AC 125 onwards)
- ▶ Max. inlet temperature: 60°C/140°F
- ▶ Flow rate : 22-1026 m³/hr (13-604 cfm)⁽¹⁾
- ▶ Pressure dew point: 3°C/37°F (ISO 8573-1:2010 class 4)
- ▶ Power supply: 115/230VAC 50/60 Hz
- ▶ Refrigerant: R134a (AC 15-100), R410a (AC 125-600)



Options



Integrated high efficiency line filters



Electric panel protection IP 54

¹Flow is measured at reference conditions: ambient pressure of 1 bara and 25°C at operating pressure of 7 barg, inlet temperature 35°C .



Pneumatech's AC range offers premium refrigeration drying technology at the lowest operational costs. All AC dryers are equipped with our proprietary energy saving algorithm, which adapts the energy consumption to the real load by continuously monitoring the ambient temperature and the pressure dewpoint. In this way, the risk of downstream corrosion is reduced to zero at all times. When there is less cooling needed, the refrigerant compressor stops and power consumption is significantly reduced, with savings up to 50%.

Premium energy efficiency is also guaranteed thanks to low pressure drops over the heat exchangers, zero-loss drains and our winning combination: rotary compressors and R410A refrigerant on AC125-200. This combination is up to 30% more energy efficient, requires 19% less refrigerant gas and is 100% compliant with European regulation EU No 517 / 2014.

Technical specifications for AC 15-600 50Hz Aircooled

Pneumatech Variant Specifications	Units	AC 15	AC 20	AC 30	AC 40	AC 50	AC 65	AC 85	AC 100	AC 125	AC 150	AC 200
Flow ⁽¹⁾	l/s	6	10	15	20	25	30	40	50	60	70	95
	m3/hr	22	36	54	72	90	108	144	180	216	252	342
Power consumption	kW	0.2	0.2	0.33	0.41	0.41	0.41	0.6	0.5	0.7	0.7	0.89
	hp	0.27	0.27	0.44	0.55	0.55	0.55	0.80	0.67	0.94	0.94	1.19
Pressure drop over dryer	barg	0.07	0.11	0.12	0.12	0.17	0.25	0.2	0.2	0.21	0.28	0.25
	psig	1.02	1.60	1.74	1.74	2.47	3.63	2.90	2.90	3.05	4.06	3.63
Refrigerant type		R134a	R134a	R134a	R134a	R134a	R134a	R134a	R134a	R410A	R410A	R410A
Dimensions	L (mm)	496	496	496	496	496	496	716	716	792	792	792
	L (inch)	19.5	19.5	19.5	19.5	19.5	19.5	28.2	28.2	31.2	31.2	31.2
	W (mm)	377	377	377	377	377	377	380	380	500	500	500
	W (inch)	14.8	14.8	14.8	14.8	14.8	14.8	15.0	15.0	19.7	19.7	19.7
	H (mm)	461	461	461	461	461	461	676	676	680	680	680
	H (inch)	18.1	18.1	18.1	18.1	18.1	18.1	26.6	26.6	26.8	26.8	26.8
Inlet and Outlet Connections		ISO7-R3/4"(m)	ISO7-R3/4"(m)	ISO7-R3/4"(m)	ISO7-R3/4"(m)	ISO7-R3/4"(m)	ISO7-R3/4"(m)	ISO7-R1"(m)	ISO7-R1"(m)	ISO7-R1"(m)	ISO7-R1"(m)	ISO7-R1"(m)
Weight	kg	27	27	32	34	34	34	56	57	82.4	82.4	109.4
	lbs	60	60	71	75	75	75	123	126	182	182	241

1. Flow is measured at reference conditions: ambient pressure of 1 bara and 25°C at operating pressure of 7 barg, inlet temperature 35°C.

K1 Flow correction factors due to compressed air inlet temperature and/or pressure dewpoint (PDP) - 50Hz units

Temperature		°C	25	30	35	40	45	50	55	60
		°F	77	86	95	104	113	122	131	140
PDP	3°C	37°F	1,2	1,1	1	0,85	0,72	0,6	0,49	0,37
	5°C	41°F	1,35	1,23	1,11	0,94	0,8	0,67	0,55	0,42
	7°C	45°F	1,5	1,35	1,22	1,02	0,88	0,75	0,61	0,47
	10°C	50°F	1,72	1,54	1,38	1,15	1	0,86	0,7	0,54
	15°C	59°F	2,11	1,89	1,68	1,43	1,23	1,03	0,83	0,62

K1 Flow correction factors due to compressed air inlet temperature and/or pressure dewpoint (PDP) - 60Hz units

		Pressure dew point (p 51) - 50 Hz table								
Temperature		°C	25	30	35	38	45	50	55	60
		°F	77	86	95	100	113	122	131	140
PDP	4°C	39°F	1,14	1,09	1,03	1	0,8	0,67	0,53	0,4
	7°C	45°F	1,27	1,22	1,14	1,09	0,88	0,74	0,59	0,44
	10°C	50°F	1,4	1,35	1,24	1,18	0,96	0,8	0,65	0,49
	15°C	59°F	1,63	1,55	1,41	1,32	1,08	0,91	0,74	0,56

K2 Flow correction factors due to compressed air inlet pressure (g)

Air inlet pressure	barg	4	5	6	7	8	10	12	14	16
	psig	58	72	87	101	116	145	174	203	232
		0,74	0,84	0,92	1	1,05	1,15	1,25	1,31	1,35

Flow correction factor due to ambient temperature - 50Hz units

Temperature	°C	25	30	35	40	45	50
	°F	77	86	95	104	113	122
		1,00	0,95	0,88	0,81	0,74	0,67

Flow correction factor due to ambient temperature - 60Hz units

Temperature	°C	25	30	35	38	45	50
	°F	77	86	95	100	113	122
		1,10	1,06	1,02	1,00	0,93	0,88

AC 200 - 630 VSD - Refrigeration dryers

Features & Benefits


- ▶ Variable frequency drive providing variable frequency drive providing unmatched energy savings
 - Up to 60% in energy savings
 - Patented heat exchangers on air to air side allow very low internal pressure drops 100 - 180 mbar (1.5 - 2.6 PSI) depending on the size resulting in less energy consumption of the compressor at or below 0.18 bar / 2.6 PSI
 - Faster payback as low as 1.5 years as compared to non-cycling or thermal mass dryers
- ▶ Increased uptime, powered by ICONS and new PureLogicT™ for advanced control and monitoring
 - PureLogicT™ controller
 - » Touch based advance controller
 - » Modbus, Profibus or Ethernet/IP, no extra interfaces required
 - Intelligent connectivity system (ICONS)
 - » Insights from PureLogicT™ controller delivered to your device
 - » On-time maintenance to control costs and ensure a longer machine life.
 - » Recognize potential problems before they affect your uptime

General Specifications

- ▶ Stable and guaranteed performance at all operating conditions - PDP of 3°C – ISO 8573- 1:2010 air purity class 4 guaranteed
- ▶ Reduced power consumptions at all conditions – performance is guaranteed even at ambient conditions as high as 46°C (115°F)
- ▶ 100% of the compressed air nominal flow at all operational temperatures up to the maximum
- ▶ No oversizing necessary for operation at maximum temperature with 100% of the nominal flow
- ▶ Reduced energy consumption of the dryer compared to oversized solution
- ▶ Fully hermetically sealed refrigerant compressor with VSD inverter
- ▶ Patented energy efficient HEAT EXCHANGER
- ▶ PurelogicT™ controller
- ▶ Zero loss drains
- ▶ Single electric connection for easy and smooth installation



Reduced total cost of ownership and faster payback – as low as 1.5 years thanks to reduced power consumption:



- Energy consumption by the dryer
- Energy consumption by the compressor due to pressure drop
- Investment
- Installation and maintenance
- **Savings - 60%** - A unique combination of high-efficiency components, smart unit design and an advanced control system enables you to achieve average energy savings of 60%



The AC VSD from Pneumatech raises the bar in refrigerant dryer performance. Using variable speed drive technology, it significantly reduces energy consumption while consistently supplying top-quality air. And, thanks to a carbon footprint that is smaller than that of its competitors, it even benefits the environment.

AC 200-630 VSD is Pneumatech's premium refrigeration dryer range at smaller flows: from 360 to 1080 Nm³/hr (210 CFM to 635 CFM)

The new AC VSD refrigerant dryer from Pneumatech was engineered to make a difference, delivering energy savings of up to 60%. At the same time, the AC VSD supports production quality and reliability and offers a small carbon footprint.

The use of variable speed drive (VSD) technology ensures that the AC VSD only uses the energy it needs at any point. The result is a much lower electric bill that greatly reduces the total cost of dryer ownership.

At the same time, Pneumatech's new dryer produces a stable supply of Class 4 purity air, which helps protect production reliability and quality. The AC VSD maintains its low dew point even in ambient temperatures of up to 46°C.

In spite of its sophisticated technology, the dryer is easy to operate thanks to its intuitive PureLogic™ controller. Users can even analyze and optimize their dryer's performance from anywhere by taking advantage of the advanced connectivity and remote monitoring option.

But the AC VSD's benefits extend beyond its outstanding performance. Due to its low energy consumption, it features a smaller carbon footprint than its competitors. Combined with an excellent TEWI-score, it helps companies meet their climate goals.

Lastly, the new AC VSD from Pneumatech is more compact than conventional dryers and can fit even in tight spaces.

Technical specifications for AC 200-630 VSD

Specifications ↓	Units	AC200 VSD	AC300 VSD	AC400 VSD	AC450 VSD	AC550 VSD	AC630 VSD
Maximum conditions at full flow ambient (Inlet) temp	°C	46 (60)	46 (60)	46 (60)	46 (60)	46 (60)	46 (60)
Inlet flow for pressure dew point (PDP) of 3°C / 37.4°F	l/s	100	140	180	220	260	300
	cfm	212	297	381	466	551	636
	m ³ /hr	360	500	650	790	940	1080
Pressure drop at full flow	bar	0.16	0.11	0.18	0.14	0.1	0.18
	psi	2.3	1.6	2.6	2	1.5	2.6
Power consumption	kW	0.66	1.04	1.54	1.77	1.9	2.64
	hp	0.90	1.41	2.09	2.41	2.58	3.59
Max. working pressure	bar	14.5	14.5	14.5	14.5	14.5	14.5
	psi	210	210	210	210	210	210
Compressed air connections (NPT for UL version)		G 1 1/2" F	G 2" F	G 2" F	G 2 1/2" F	G 2 1/2" F	G 2 1/2" F
Dimensions	L (mm)	805	805	805	805	805	805
	L (inch)	31.69	31.69	31.69	31.69	31.69	31.69
	H (mm)	962	962	962	962	962	962
	H (inch)	37.87	37.87	37.87	37.87	37.87	37.87
	W (mm)	1040	1040	1040	1040	1040	1040
	W (inch)	41	41	41	41	41	41
Weight	kg	130	134	134	143	150	165
	lbs	287	295	295	315	331	364

Correction factors for ambient temperature

Ambient temperature	°C	25	30	35	40	46
	°F	77	86	95	104	114
Temperature correction factor	Kt (amb)	1	0.91	0.81	0.72	0.62

Correction factors for compressed air inlet pressure

Operating pressure	barg	6	7	8	10	13
	psig	87	100	116	145	188
Pressure correction factor	Kp	0.97	1	1.03	1.07	1.12

Correction factors for compressed air inlet temperature

Inlet temperature	°C	25	30	35	40	46	50	55	60
	°F	77	86	95	104	114	122	131	140
Temperature correction factor	Kt	1.1	1.05	1	0.82	0.69	0.58	0.49	0.42

AC 650 - 2100 - Large cycling refrigeration dryers (including VSD solutions)

Features & Benefits

- ▶ Premium energy efficiency
 - Energy-saving & flow control: adapt energy consumption to the real load
 - Variable speed range: exact match between energy consumption and actual demand (available for AC 1600-2100)
 - Lowest pressure drop over heat exchanger and air piping
 - Zero-loss drains
- ▶ Strong performance & reliability
 - Stable pressure dew point as low as 3°C
 - Rotary refrigerant compressors: limited mechanical load & low vibrations
 - Guaranteed drying performance in wide range of ambient temperatures
 - Refrigeration cycle optimized in all conditions thanks to automatic expansion valve & electronic hot gas bypass valve
- ▶ Air-cooled as well as water-cooled versions available
- ▶ Optimal control and monitoring thanks to the Purelogic™ controller
 - Communication via industrial protocols like Modbus, Profibus or Ethernet/IP
 - Internet-based visualization
- ▶ Easy maintenance at low cost
 - Pipe connections on top
 - Long service intervals
 - Easy access to key components

General Specifications

- ▶ AC refrigeration dryers: cycling type including VSD option (only for AC 1600-2100)
- ▶ Operating Pressure: 4-14 barg/58-189 psig
- ▶ Max. temperature: 50°C/122°F
- ▶ Flow rate: 1116-3636 m³/hr (657-2141 cfm)⁽¹⁾
- ▶ Pressure dew point: 3°C/37°F
- ▶ Power supply: 400V/50Hz; 380V/60Hz; 400-460V/60Hz
- ▶ Refrigerant: R410a
- ▶ Cooling type: Air-cooled and water-cooled



Options



IP 54 protection
(only for 650-1050;
standard on AC1250-2100)

K1 Flow correction factors due to compressed air inlet temperature and/or pressure dewpoint (PDP) - 50Hz units

Temperature	°C	25	30	35	40	45	50	55	60
	°F	77	86	95	104	113	122	131	140
PDP	3°C	37°F	1,2	1,1	1	0,85	0,72	0,6	0,49
	5°C	41°F	1,35	1,23	1,11	0,94	0,8	0,67	0,55
	7°C	45°F	1,5	1,35	1,22	1,02	0,88	0,75	0,61
	10°C	50°F	1,72	1,54	1,38	1,15	1	0,86	0,7
	15°C	59°F	2,11	1,89	1,68	1,43	1,23	1,03	0,83

1 Flow is measured at reference conditions: ambient pressure of 1 bara and 25°C at operating pressure of 7 barg, inlet temperature 35°C.

K1 Flow correction factors due to compressed air inlet temperature and/or pressure dewpoint (PDP) - 60Hz units

Temperature	°C	25	30	35	38	45	50	55	60
	°F	77	86	95	100	113	122	131	140
PDP	4°C	39°F	1,14	1,09	1,03	1	0,8	0,67	0,53
	7°C	45°F	1,27	1,22	1,14	1,09	0,88	0,74	0,59
	10°C	50°F	1,4	1,35	1,24	1,18	0,96	0,8	0,65
	15°C	59°F	1,63	1,55	1,41	1,32	1,08	0,91	0,74

K2 Flow correction factor due to compressed air inlet pressure (g)

Air inlet pressure	barg	4	5	6	7	8	10	12	14
	psig	58	72	87	101	116	145	174	203
		0,74	0,84	0,92	1	1,05	1,15	1,25	1,31

Flow correction factor due to ambient temperature or cooling water temperature - 50Hz units

Temperature	°C	25	30	35	40	45	50
	°F	77	86	95	104	113	122
		1,00	0,95	0,88	0,81	0,74	0,67

Flow correction factor due to ambient temperature or cooling water temperature - 60Hz units

Temperature	°C	25	30	35	38	45	50
	°F	77	86	95	100	113	122
		1,10	1,06	1,02	1,00	0,93	0,88



AC 650-2100 is Pneumatech's premium refrigeration dryer range at higher flows: from 1120 up to 3636 m³/hr (657-2141 cfm).

As in the small AC range, operating costs are significantly reduced thanks to the energy saving and flow switch algorithms, the zero-loss drains, the low pressure drop over the heat exchangers and the combination of rotary compressors and R410A refrigerant. The refrigeration cycle is further optimized in all working conditions by making use of the automatic expansion valve & electronic hot gas bypass valve.

From AC 650 onwards, dedicated variable speed (VSD) variants have been added to the range. The VSD controller incorporated

in these dryers matches the energy consumption to the actual compressed air demand. This reduces energy used by as much as 70%, compared to conventional dryers. It works by varying the speed of the compressor, hereby ensuring a stable dew point.

The Purelogic™ is installed as standard on all dryers: it ensures maximum reliability by monitoring the most important parameters of the dryer and offers impressive control and monitoring capabilities, like internet-based visualization.

The entire range is available in both air-cooled and water-cooled versions.

Technical specifications AC 650 - 2100 fixed speed															
		Air Cooled							Water Cooled						
Pneumatech Variant Specifications	Units	AC 650	AC850	AC 1050	AC 1250	AC 1600	AC 1800	AC 2100	AC 650	AC 850	AC 1050	AC 1250	AC 1600	AC1800	AC2100
Flow ⁽¹⁾	l/s	310	410	510	610	760	870	1010	310	410	510	610	760	870	1010
	m ³ /hr	1116	1476	1836	2196	2736	3132	3636	1116	1476	1836	2196	2736	3132	3636
Power consumption	kW	2.80	3	4.5	4.8	5.3	6.6	7.4	2.00	2.4	4.1	3.1	3.6	4.5	5.1
	hp	3.75	4.02	6.03	6.44	7.11	8.85	9.92	2.68	3.22	5.50	4.16	4.83	6.03	6.84
Pressure drop over dryer	mbar	230	210	200	170	170	140	170	230	210	200	170	170	140	170
	psi	3.3	3.0	2.9	2.5	2.5	2.0	2.5	3.3	3.0	2.9	2.5	2.5	2.0	2.5
Refrigerant type		R410A	R410A	R410A	R410A	R410A	R410A	R410A	R410A	R410A	R410A	R410A	R410A	R410A	R410A
Dimensions	L (mm)	1263	1263	1525	1040	1245	1245	1580	1263	1263	1263	1245	1580	1245	1245
	L (inch)	49.7	49.7	60.0	40.9	49.0	49.0	62.2	49.7	49.7	49.7	49.0	62.2	49.0	49.0
	W (mm)	850	850	850	1060	1060	1060	1060	850	850	850	1060	1060	1060	1060
	W (inch)	33.5	33.5	33.5	41.7	41.7	41.7	41.7	33.5	33.5	33.5	41.7	41.7	41.7	41.7
	H (mm)	1190	1375	1580	1580	1580	1580	1580	1190	1375	1375	1580	1580	1580	1580
	H (inch)	46.9	54.1	62.2	62.2	62.2	62.2	62.2	46.9	54.1	54.1	62.2	62.2	62.2	62.2
Inlet and Outlet Connections		G3"	G3"	G3"	DN100	DN100	DN150	DN150	G3"	G3"	G3"	DN100	DN150	DN150	DN150
Weight	kg	200	245	310	320	380	400	460	180	245	265	350	360	370	380
	lbs	441	540	683	705	838	882	1014	397	540	584	772	794	816	838

Technical specifications AC 650 - 2100 VSD															
		Air Cooled						Water Cooled							
Pneumatech Variant Specifications	Units	AC 650 VSD	AC 850 VSD	AC 1050 VSD	AC 1600 VSD	AC 1800 VSD	AC 2100 VSD	AC 650 VSD	AC 850 VSD	AC 1050 VSD	AC 1600 VSD	AC 1800 VSD	AC 2100 VSD		
Flow ⁽¹⁾	l/s	310	410	510	760	870	1010	310	410	510	760	870	1010		
	m ³ /hr	1116	1476	1836	2736	3132	3636	1116	1476	1836	2736	3132	3636		
Power consumption	kW	2.28	3.02	3.38	5.3	5.8	6.6	1.48	2.2	2.78	3.3	4.2	5.6		
	hp	3.06	4.05	4.53	7.11	7.78	8.85	1.98	2.95	3.73	4.43	5.63	7.51		
Pressure drop over dryer	mbar	230	210	200	170	140	170	230	210	200	90	120	170		
	psi	3.3	3.0	2.9	2.5	2.0	2.5	3.3	3.0	2.9	1.3	1.7	2.5		
Refrigerant type		R410A	R410A	R410A	R410A	R410A	R410A	R410A	R410A	R410A	R410A	R410A	R410A		
Dimensions	L (mm)	1263	1263	1263	1245	1245	1580	1263	1263	1263	1580	1580	1580		
	L (inch)	49.7	49.7	49.7	49.0	49.0	62.2	49.7	49.7	49.7	62.2	62.2	62.2		
	W (mm)	850	850	850	1060	1060	1060	850	850	850	1060	1060	1060		
	W (inch)	33.5	33.5	33.5	41.7	41.7	41.7	33.5	33.5	33.5	41.7	41.7	41.7		
	H (mm)	1190	1375	1375	1580	1580	1580	1190	1375	1375	1580	1580	1580		
	H (inch)	46.9	54.1	54.1	62.2	62.2	62.2	46.9	54.1	54.1	62.2	62.2	62.2		
Inlet and Outlet Connections		ISO7-R3*	ISO7-R3*	ISO7-R3*	DN100	DN150	DN150	ISO7-R3*	ISO7-R3*	ISO7-R3*	DN150	DN150	DN150		
Weight	kg	218	245	265	380	400	460	200	245	265	410	410	410		
	lbs	481	540	584	838	882	1014	441	540	584	904	904	904		

*3 control modes i.e Economy, lowest dewpoint and maximum saving control offer different power consumptions.

AC 2650 - 8500 - Large cycling refrigeration dryers (including VSD solutions)

Features & Benefits


- ▶ Stable and guaranteed Performance at all operating conditions - PDP of 3°C thanks to direct expansion technology
- ▶ Lowest pressure drop
- ▶ Advanced control algorithm with three different control modes for variable speed versions:
 - Regulation of the refrigerant compressor based on actual load
 - Economy: PDP = ambient temperature minus 20°C (68°F)
 - Lowest Dew-point: best possible PDP
 - Max. saving: PDP = ambient temperature minus 15°C (59°F)
 - Much better turndown efficiency is achieved when the unit runs in a partial load condition
- ▶ Zero glide refrigerant – R410a: No-temperature-glide effect resulting in stable guaranteed PDP
- ▶ Comprehensive scope of supply:
 - Energy efficient heat exchanger
 - Fully hermetically sealed refrigerant compressor with phase sequence relay
 - Refrigerant filter/dryer (standard on all AC 2650-8500 fixed speed and VSD dryers)
 - Electronic hot gas bypass valve (EHGPV)
 - Purelogic™ for advanced control and monitoring

General Specifications


- AC refrigeration dryers: cycling type including VSD
- Operating Pressure: 4-14 barg/ 58-189 psig
- Max. Ambient temperature: 40°C/104°F (46°C/115°F as an option)
- Flow rate: 450-14400 m³/hr (2650-8475 cfm)
- Pressure dew point: 3°C/37°F
- Power supply: 400V/50Hz; 380V/60Hz; 400-460V/60Hz
- Refrigerant: R410a
- Cooling type: Air-cooled and water-cooled




Reduced lifecycle costs and faster payback thanks to reduced power consumption



Options



46°C/115°F ambient temperature version



Cooling air pre-filter



Anchor pads



Customized solutions (contact your Pneumatech representative for further information)



AC 2650-8500 FS/VSD is Pneumatech's premium refrigeration dryer range at higher flows: from 4500 up to 14400 m³/hr (2650-8475 cfm). AC 2650-8500 (VSD) refrigerant dryers are engineered in house and tested using the most stringent methods (at ambient temperatures up to 46°C/115°F). They exceed the international standards for compressed air purity and are tested according to ISO 7183:2007.

New AC Range is the most efficient dryer for continuous and varying air demand applications. A combination of new innovative technologies integrated in the new AC 2650-8500 (VSD) dryers'

design makes them a perfect match for customers looking for reliable equipment with a low cost of ownership. The unique combination of high efficiency components, a smart unit design and an advanced unit control system gives an opportunity to save on average 50% of the consumed energy.

Significantly reduced power consumption and low quantities of refrigerant make sure the AC 2650-8500 (VSD) dryers operate at the lowest possible carbon footprint

Technical specifications AC 2650 - 4200 fixed speed									
Pneumatech Variants Specifications	Units	Air Cooled				Water Cooled			
		AC 2650	AC 3200	AC 3700	AC 4200	AC 2650	AC 3200	AC 3700	AC 4200
Flow ⁽¹⁾	l/s	1250	1500	1750	2000	1250	1500	1750	2000
	m ³ /hr	4500	5400	6300	7200	4500	5400	6300	7200
Power consumption	kW	6.80	8.9	10.5	12.2	5.3	5.8	6.4	8.70
	hp	9.12	11.94	14.08	16.36	7.11	7.78	8.58	11.67
Pressure drop over dryer	mBar	180	180	150	190	180	160	150	190
	psi	2.6	2.6	2.2	2.8	2.6	2.3	2.2	2.8
Refrigerant type	kg	R410A	R410A	R410A	R410A	R410A	R410A	R410A	R410A
Dimensions	L (mm)	1474	1474	1474	1474	1474	1474	1474	1474
	L (inch)	58.0	58.0	58.0	58.0	58.0	58.0	58.0	58.0
	W (mm)	1579	1579	1579	1579	1579	1579	1579	1579
	W (inch)	62.2	62.2	62.2	62.2	62.2	62.2	62.2	62.2
	H (mm)	2295	2295	2295	2295	1725	1725	1725	1725
	H (inch)	90.4	90.4	90.4	90.4	67.9	67.9	67.9	67.9
Inlet and Outlet Connections		DN150	DN150	DN150	DN150	DN150	DN150	DN150	DN150
Weight	kg	835	865	910	950	775	800	845	850
	lbs	1841	1907	2006	2094	1709	1764	1863	1874

Technical specifications AC 2650 - 8500 VSD															
Pneumatech Variants Specifications	Units	Air Cooled							Water Cooled						
		AC 2650 VSD	AC 3200 VSD	AC 3700 VSD	AC 4200 VSD	AC 5100 VSD	AC 6400 VSD	AC 8500 VSD	AC 2650 VSD	AC 3200 VSD	AC 3700 VSD	AC 4200 VSD	AC 5100 VSD	AC 6400 VSD	AC 8500 VSD
Flow ⁽¹⁾	l/s	1250	1500	1750	2000	2400	3000	4000	1250	1500	1750	2000	2400	3000	4000
	m ³ /hr	4500	5400	6300	7200	8640	10800	14400	4500	5400	6300	7200	8640	10800	14400
Power consumption	kW	5.50	7.4	8.4	8.8	6.4	12.8	18.7	4.4	5.1	6.1	6.7	5.5	10.6	14.5
	hp	7.38	9.92	11.26	11.80	8.58	17.17	25.08	5.90	6.84	8.18	8.98	7.38	14.21	19.44
Pressure drop over dryer	mBar	180	180	150	190	270	190	190	180	180	150	190	270	190	190
	psi	2.6	2.6	2.2	2.8	3.9	2.8	2.8	2.6	2.6	2.2	2.8	3.9	2.8	2.8
Refrigerant type		R410A	R410A	R410A	R410A	R410A	R410A	R410A	R410A	R410A	R410A	R410A	R410A	R410A	R410A
Dimensions	L (mm)	1474	1474	1474	1474	1474	2502	2502	1474	1474	1474	1474	1474	2502	2502
	L (inch)	58.0	58.0	58.0	58.0	58.0	98.5	98.5	58.0	58.0	58.0	58.0	58.0	98.5	98.5
	W (mm)	1579	1579	1579	1579	1579	1579	1579	1579	1579	1579	1579	1579	1579	1579
	W (inch)	62.2	62.2	62.2	62.2	62.2	62.2	62.2	62.2	62.2	62.2	62.2	62.2	62.2	62.2
	H (mm)	2295	2295	2295	2295	2295	2295	2295	1725	1725	1725	1725	1725	1736	1736
	H (inch)	90.4	90.4	90.4	90.4	90.4	90.4	67.9	67.9	67.9	67.9	67.9	67.9	68.3	68.3
Inlet and Outlet Connections		DN150	DN150	DN150	DN150	DN150	DN200	DN200	DN150	DN150	DN150	DN150	DN150	DN200	DN200
Weight	kg	850	880	920	965	990	1690	1820	800	815	855	865	870	1410	1540
	lbs	1874	1940	2028	2127	2183	3726	4012	1764	1797	1885	1907	1918	3109	3395

1. Flow is measured at reference conditions: 1 bara and 20°C at operating pressure of 7 barg, inlet temperature 35°C & std PDP of 3°C at the outlet.

For accurate sizing for your operating conditions consult Pneumatech

Optimal control & monitoring thanks to Pneumatech's Purelogic™ controller

The Purelogic™ Central Controller is the ideal complement to your dryers and gas generators. This state-of-the-art control solution will provide optimal control and monitoring of your machines, increased reliability and reduced energy use.

The built-in web server allows direct read-out of all important parameters, settings and service counters of your dryer, by a simple connection via a local area network. Machine status information can also be received and dryers remotely start/stopped through voltage-free contacts. Communication with industrial protocols such as Modbus and Profibus is also possible.



Adsorption Dryers

Pneumatech offers four different adsorption dryer technologies. Heatless dryers (PH) have the lowest initial investment cost, while zero-purge adsorption dryers (PB ZP) the lowest lifecycle cost. Heated purge (PE) and blower purge (PB) dryers balance between both.

No matter what your preference is, Pneumatech guarantees stable, dry air at the lowest operating costs and with excellent control and monitoring capabilities for each dryer you select.

PH 2 - 45 HE - Extruded profile heatless adsorption dryers

Features & Benefits

- ▶ Advanced energy management for lowest operating costs
 - Compressor synchronization
 - Purge nozzle optimization (optional)
 - PDP control (optional)
- ▶ High-quality, high-efficient desiccant, selected for the right application – molecular sieves
- ▶ Spring-loaded cartridges, hence minimizing the risk of crushed desiccant
- ▶ Counter-current regeneration for optimal energy efficiency and guaranteed dry air
- ▶ Designed for transportability & mountability
 - Dryer can be installed vertically or horizontally
 - Wall-mounting kit (optional)
- ▶ In & outlet can be reversed
- ▶ Low noise levels while purging
- ▶ High reliability and robust design

General Specifications

- ▶ Heatless adsorption dryers: extruded profile design
- ▶ Dew points achievable: -40°C/-40°F & -70°C/-94°F
- ▶ Pressure range: 4-16 barg/58-232 psig
- ▶ Ambient temperature range: 1-50°C/34-122°F
- ▶ Inlet temperature range: 1-60°C/34-140°F
- ▶ Power supply: 230VAC 50/60Hz



Options



Purge nozzle optimization



Wall mounting kit



PDP control

Incorporating high-quality components, PH heatless adsorption dryers provide you with clean, dry air to extend the life of your equipment and products. Heatless adsorption dryers use dry, expanded purge air to remove moisture from the desiccant material.

PH 2-45 HE adsorption dryers are capable of drying air to a PDP of -70°C/-94°F, simply by reducing the flow, thanks to the use of carefully selected molecular sieves. The desiccant is housed in a robust extruded aluminum body, which can operate until 16 barg/232 psig (fatigue load). The dryers are equipped with a mounted pre-filter and an integrated after-filter as standard,

can be installed vertically and can also be wall-mounted with a specially designed wall-mounting kit (optional).

The controller ensures the lowest operational costs thanks to compressor synchronization and the optional PDP control. LED's on the controller indicate whether power supply is connected, towers are pressurized and solenoids are functioning properly. It also provides with preventive maintenance information. Alarms can also be triggered remote thanks to the available voltage-free contact.

Technical specifications for PH 2 HE up to PH 45 HE (standard version, PDP -40 °C)

Specifications	Unit	PH 2 HE	PH 4 HE	PH 6 HE	PH 11 HE	PH 15 HE	PH 20 HE	PH 25 HE	PH 35 HE	PH 45 HE
Nominal volume flow at dryer inlet ⁽¹⁾	l/s	1	2	3	5	7	10	12	17	22
	m³/hr	4	7	11	18	25	36	43	61	79
Average purge air consumption	%	18	18	18	18	18	18	18	18	18
Inlet and outlet connections	G	1/4"	1/4"	1/4"	1/2"	1/2"	1/2"	1/2"	1/2"	1/2"
	NPT	1/4"	1/4"	1/4"	1/2"	1/2"	1/2"	1/2"	1/2"	1/2"
Pressure drop at max. flow	barg	0.012	0.075	0.185	0.01	0.04	0.075	0.125	0.21	0.34
	psig	0.17	1.09	2.68	0.15	0.58	1.09	1.81	3.05	4.93
Included pre-filter size	Super fine filter	Mini 3 C HE	Mini 3 C HE	Mini 3 C HE	TF 1 C HE	TF 1 C HE	TF 1 C HE	PH 2 C HE	PH 2 C HE	PH 2 C HE
Mass	kg	7	9	11	19	22	25	29	35	44
	lbs	15.5	19.8	24.2	41.9	48.5	55.1	63.9	77.1	97
Height	mm	540	720	855	640	725	875	1015	1270	1505
	inch	21.2	28.3	33.6	25.1	28.5	34.4	39.9	50	59.2
Width	mm	197	197	197	320	320	320	320	320	320
	inch	7.7	7.7	7.7	12.5	12.5	12.5	12.5	12.5	12.5
Length	mm	106	106	106	149	149	149	149	149	149
	inch	4.1	4.1	4.1	5.8	5.8	5.8	5.8	5.8	5.8

1. Flow is measured at reference conditions: 1 bara and 20°C at operating pressure of 7 barg, inlet temperature 35°C & std PDP of -40°C at the outlet.

Flow correction factors due to air inlet pressure Kp

Operating pressure	barg	4	5	6	7	8	9	10	11	12	13	14	15	16
	psig	58	72	87	100	116	130	145	160	174	189	203	218	232
Pressure correction factor	Kp	0.62	0.75	0.87	1	1.12	1.25	1.37	1.5	1.62	1.75	1.87	2	2.12

Flow correction factors due to air inlet temperature Kt

Temperature	°C	20	25	30	35	40	45	50
	°F	68	77	86	95	104	113	122
Temperature correction factor	Kt	1.07	1.06	1.04	1	0.88	0.67	0.55

Flow correction factors due to pressure dew point Kdp

Dew point	°C	-40	-70
	°F	-40	-94
Dew point correction factor	Kdp	1	0.7

PH 55 - 550 HE - Extruded profile heatless adsorption dryers

Features & Benefits


- ▶ Advanced energy management for lowest operating costs
 - Compressor synchronization
 - Purge nozzle optimization
 - PDP control (optional)
- ▶ Best-in-class performance thanks to unique valve and exhaust design (patent pending)
 - Lowest pressure drop during drying
 - Lowest purge loss by ensuring maximum purge air expansion during regeneration
- ▶ Low noise levels during purge and blow-off
- ▶ High-quality, high-efficient desiccant, selected for the right application
 - PDP -20°C/-3°F & PDP -40°C/-40°F: activated alumina
 - PDP -70°C/-94°F: molecular sieves
- ▶ Spring-loaded desiccant, minimizing the risk of crushing
- ▶ Counter-current regeneration for optimal energy efficiency and guaranteed dry air
- ▶ Designed for transportability & mountability
 - Wall-mounting kit for PH 55-190 HE (optional)
- ▶ Optimal control and monitoring thanks to the Purelogic™ controller (optional)
- ▶ Desiccant bags for easy service from the top

General Specifications


- ▶ Heatless adsorption dryers: extruded profile design
- ▶ Dew points achievable: -20°C/-3°F; -40°C/-40°F & -70°C/-94°F
- ▶ Pressure range: 4-14 barg/58-203 psig
- ▶ Ambient temperature range: 1-45°C/34-113°F
- ▶ Inlet temperature range: 1-50°C/34-122°F (For temperatures up to 60°C/140°F: see HIT option)
- ▶ Power supply: 230VAC 50/60Hz & 115VAC 50/60Hz




Options



High inlet temperature



PDP -20°C



PDP -70°C



Wall mounting kit



PDP control



Purelogic controller



IP65 protection



Incorporating high-quality components, PH heatless adsorption dryers provide you with clean, dry air to extend the life of your equipment and products. Heatless adsorption dryers use dry, expanded purge air to remove moisture from the desiccant material.

PH 55-550 HE adsorption dryers are available in 3 PDP variants: -20°C/-4°F, -40°C/-40°F and -70°C/-94°F, each optimized to provide the lowest purge loss. The unique manifold (patent pending) includes pilot air controlled 3/2-way valves, which switch fast and reliably. The pressure drop over the valves is reduced to a minimum. This does not only result in a low pressure drop over the dryer, but also ensures maximum purge air expansion during regeneration. The latter makes that the purge consumption of the dryers has been reduced significantly.

The desiccant is spring-loaded and housed in a robust extruded aluminum body, which can operate up to 14 barg/203 psig (fatigue load). The dryers are equipped with a mounted pre-filter and after-filter as standard and can also be wall-mounted with a specially designed wall-mounting kit (optional).

Operating costs are optimized at all times thanks to the availability of compressor synchronization and purge nozzle optimization as standard and PDP control as option. The full machine status can be checked on the display of the controller and the vessel pressure gauges on the unit.

The controller indicates whether power supply is connected, towers are pressurized, valves are functioning properly or preventive maintenance needs to be done. In case the optional PDP control is connected, the PDP value can be monitored from the display. Alarms and warnings can also be triggered remote with the available voltage-free contacts.

Optionally the Purelogic™ can be used as central brain of the adsorption dryer.

The Purelogic™ offers impressive control and monitoring capabilities, and can communicate with industrial protocols as Modbus, Profibus or Ethernet/IP.

Technical specifications for PH 55 HE up to PH 550 HE (standard version, PDP -40 °C)

Specification	Unit	PH 55 HE	PH 75 HE	PH 95 HE	PH 120 HE	PH 140 HE	PH 190 HE	PH 230 HE	PH 275 HE	PH 350 HE	PH 420 HE	PH 550 HE
Nominal volume flow at dryer inlet ⁽¹⁾	l/s	25	35	45	55	65	90	110	130	165	195	260
	m³/hr	90	126	162	198	234	324	396	468	594	702	936
Regeneration air consumption average at max. flow	%	16.5	16.5	16.5	16	16	16.5	16.5	16.5	16.5	17	17
Connection inlet/outlet	G	1/2"	1"	1"	1"	1 1/2"	1 1/2"	1 1/2"	1 1/2"	1 1/2"	1 1/2"	2"
	NPT	1/2"	1"	1"	1"	1 1/2"	1 1/2"	1 1/2"	1 1/2"	1 1/2"	1 1/2"	2"
Pressure drop at max. flow	barg	0.031	0.065	0.114	0.18	0.278	0.114	0.18	0.278	0.18	0.278	0.278
	psig	0.45	0.94	1.65	2.61	4.03	1.65	2.61	4.03	2.61	4.03	4.03
Included pre & after filter size	Super fine filter	TF 3 C HE	TF 4 C HE	TF 5 C HE	TF 5 C HE	TF 6 C HE	TF 6 C HE	TF 6 C HE	TF 7 C HE	TF 8 C HE	TF 8 C HE	TF 9 C HE
	Dust filter	TF 3 S HE	TF 4 S HE	TF 5 S HE	TF 5 S HE	TF 6 S HE	TF 6 S HE	TF 6 S HE	TF 7 S HE	TF 8 S HE	TF 8 S HE	TF 9 S HE
Height	mm	1205	1205	1495	1495	1835	1495	1495	1835	1495	1835	1835
	inch	47.4	47.4	58.9	58.9	72.2	58.9	58.9	72.2	58.9	72.2	72.2
Width	mm	807	827	847	847	877	907	906	907	907	907	985
	inch	31.8	32.6	33.3	33.3	34.5	35.7	35.7	35.7	35.7	35.7	38.8
Length	mm	394	394	394	394	394	564	564	564	734	734	929
	inch	15.5	15.5	15.5	15.5	15.5	22.2	22.2	22.2	28.9	28.9	36.6
Mass	kg	100	109	128	140	165	217	234	276	331	389	500
	lb	220.5	240.3	282.2	308.6	363.8	478.4	515.9	608.5	729.7	857.6	1102.3

*1. Flow is measured at Reference Conditions: 1 bara and 20°C at operating pressure of 7 barg, inlet temperature 35°C & std PDP of -40°C at the outlet

Flow correction factors due to air inlet pressure												
Operating pressure	barg	4	5	6	7	8	9	10	11	12	13	14
	psig	58	72	87	100	116	130	145	160	174	189	203
Pressure correction factor	Kp	0.62	0.75	0.87	1	1.12	1.25	1.37	1.5	1.62	1.75	1.87

Flow correction factors due to air inlet temperature												
Temperature	°C	20	25	30	35	40	45	50				
	°F	68	77	86	95	104	113	122				
Temperature correction factor	Kt	1	1	1	1	0.84	0.67	0.55				

PH 760 - 3390 HE - Welded vessel heatless adsorption dryers

Features & Benefits


- ▶ Available in three standard variants
 - With Standard DC1 Controller (PDP Control optional)
 - With Purelogic™ (PDP control std available)
 - With Pneumatic Controller (no need of electricity for the installation and no PDP control possible)
- ▶ Lowest possible pressure drop thanks to innovative open silencer design
- ▶ Improved performance with reduced purge rate to 16% across the complete range
- ▶ Advanced energy management for lowest operating costs
 - PDP control - (std with Purelogic™ and optional with DC1 Controller)
 - Compressor synchronization
 - Purge nozzle optimization (optional)
- ▶ High-quality, high-efficient desiccant, selected for the right application
 - PDP -40°C/-40°F (std): activated alumina
 - PDP -70°C/-94°F and high inlet temp. (option): molecular sieves
- ▶ Minimal risk of crushed desiccant thanks to the large vessel diameter and the sonic nozzle (std available)
- ▶ Counter-current regeneration for optimal energy efficiency and guaranteed dry air
- ▶ High reliability and robust design
- ▶ Low noise levels while purging
- ▶ Designed for transportability
- ▶ Optimal control and monitoring thanks to the Purelogic™ controller

General Specifications


- ▶ Heatless adsorption dryers: welded vessel design
- ▶ Dew points achievable: -40°C/-40°F & -70°C/-94°F
- ▶ Pressure range: 4-9 barg/58-130 psig (14 barg/203 psig variant available as separate variant)
- ▶ Ambient temperature range: 1-50°C/34-122°F
- ▶ Inlet temperature range: 1-55°C/34-131°F
- ▶ Power supply: 230VAC 50 Hz; 115VAC 60 Hz 3 ph



Variants




PDP -70°C



14.5 Bar(g)



DC1 controller



Purelogic™



Pneumatic controlled

Options



Purge nozzle optimization



PDP Control for DC1 controller variants (std with Purelogic™ Controller)




In and outlet filters



Vessel Safety valves



Wooden Packaging



High inlet temperature

Pneumatech presents the newly designed and significantly improved heatless adsorption dryer range – PH 760-3390 HE. Incorporating high-quality components, PH heatless adsorption dryers provide you with clean, dry air to extend the life of your equipment and products. Heatless adsorption dryers use dry, expanded purge air to remove moisture from the desiccant material.

PH 760-3390 HE adsorption dryers are capable of drying air to a PDP of -40°C/-40°F as standard and -70°C/-94°F as option for higher flows up to 5760 m³/hr/3390 cfm. The desiccant is housed in welded vessels, which are coated and can operate up to 9 barg/130 psig (fatigue load) with std variant and up to 14,5 barg/203 psi with high pressure variant (fatigue load). All dryers can be equipped with 2 coalescing pre-filters before and 1 particulate filter after the dryer (optional).

Thanks to ingeniously designed mechanical components i.e open type of silencers and large vessels, PH 760-3390 HE range offers highest performance with lowest pressure drop and improved purge loss of 16%.

Considering different needs of the customers, the PH 760-3390 HE range offers 3 different controller for different requirements. DC 1 Controller version has a basic controller with required controls and monitoring such as Service Alarm, General alarm relay, synchronization control and optional dew point control whereas Purelogic™ controller version will have the Purelogic™ as central brain of the adsorption dryer. The Purelogic™ optimizes operating costs; ensures maximum reliability by monitoring the most important parameters; and offers impressive control and monitoring capabilities. For special applications where Pneumatic control is preferred and no electricity is possible, PH 760-3390 HE also operates with Pneumatically enabled controller.

Technical specifications for PH 760 HE up to PH 3390 HE (standard version, -40 PDP °C)

Specification	Unit	PH760 HE	PH1020 HE	PH1330 HE	PH2060 HE	PH2670 HE	PH3390 HE
Max volume Flow at Dryer Inlet ⁽¹⁾	l/s	360	480	630	970	1260	1600
	m³/hr	1296	1728	2268	3492	4536	5760
Regeneration Air Consumption average at max. flow	%	16	16	16	16	16	16
Pressure Drop over Dryer excluding Filters	bar	0.15	0.15	0.15	0.15	0.15	0.18
	psi	2.18	2.18	2.18	2.18	2.18	2.61
Inlet and outlet connections	DIN PN16	DN80	DN80	DN80	DN100	DN100	DN150
Optional Pre & After Filter Sizes ⁽²⁾	General purpose coalescing filter	PMH G 1529	PMH G 1529	G 1F	G 2F	G 3F	G 4F
	High efficiency coalescing filter	PMH C 1529	PMH C 1529	C 1F	C 2F	C 3F	C 4F
	Particulate filter	PMH S 1529	PMH S 1529	S 1F	S 2F	S 3F	S 4F
Length	mm	1776	1776	1884	2359	2472	2788
	inch	69.9	69.9	74.1	92.8	97.3	109.7
Width	mm	822	822	822	1000	1026	1417
	inch	32.3	32.3	32.3	39.3	40.3	55.7
Height	mm	2549	2549	2604	2671	2653	2576.5
	inch	100.3	100.3	102.5	105.1	104.4	101.4
Length	inch	69.9	69.9	74.2	92.9	97.3	109.8
Width	inch	32.4	32.4	32.4	39.4	40.4	55.8
Height	inch	100.4	100.4	102.5	105.2	104.4	101.4
Mass	kg	1220	1300	1620	2651	3100	4600
	lbs	2690	2866	3571	5844	6834	10141

*1. Flow is measured at Reference Conditions: 1 Bar(a) and 25°C at operating pressure of 7 bar (g), inlet temperature 35°C & std PDP of -40°C at the outlet

*2. Filters are sized at reference conditions. Consult the AML of the filters for sizing outside the reference conditions.

For accurate sizing for your operating conditions consult Pneumatech

PH 55 - 550 S - The cost-efficient alternative to PH 55-550 HE

Features & Benefits

- ▶ Advanced energy management for lowest operating costs
 - Compressor synchronization
 - Purge nozzle optimization (2 nozzles)
 - PDP control (optional)
- ▶ High reliability and low maintenance costs thanks to unique valve design (patent pending)
- ▶ High-quality desiccant, resulting in a consistent PDP of -20°C/-3°F or -40°C/-40°F
- ▶ Spring-loaded desiccant, minimizing the risk of crushing
- ▶ Counter-current regeneration for optimal energy efficiency and guaranteed dry air
- ▶ Designed for transportability & mountability
 - Wall-mounting kit for PH 55-140 S (optional)
- ▶ Advanced controller to monitor machine status at all times
- ▶ Desiccant bags for easy service from the top

General Specifications

- ▶ Heatless adsorption dryers: extruded profile design
- ▶ Dew points achievable:
-20°C/-3°F & -40°C/-40°F
- ▶ Pressure range:
4-14 barg/58-203 psig
- ▶ Ambient temperature range:
1-45°C/34-113°F
- ▶ Inlet temperature range:
1-50°C/34-122°F
- ▶ Power supply:
230VAC 50/60Hz & 115VAC 50/60Hz



Options



Wall mounting kit



PDP control

Incorporating high-quality components, PH heatless adsorption dryers provide you with clean, dry air to extend the life of your equipment and products. Heatless adsorption dryers use dry, expanded purge air to remove moisture from the desiccant material.

PH 55-550 S adsorption dryers are available in 2 PDP variants: -20°C/-4°F and -40°C/-40°F. The unique manifold (patent pending) includes pilot air controlled 3/2-way valves, which switch fast and reliably.

The desiccant is spring-loaded and housed in a robust extruded aluminum body, which can operate up to 14 barg/203 psig (fatigue load). Pre- and afterfilters are delivered as standard with every dryer.

Operating costs are optimized at all times thanks to the availability of compressor synchronization and purge nozzle optimization as standard and PDP control as option. The full machine status can be checked on the display of the controller and the vessel pressure gauges on the unit. The controller indicates whether power supply is connected, towers are pressurized, valves are functioning properly or preventive maintenance needs to be done. In case the optional PDP control is connected, the PDP value can be monitored from the display. Alarms and warnings can also be triggered remote with the available voltage-free contacts.

Technical specifications for PH 55 S up to PH 550 S (standard version, PDP -40 °C)

Specification	Unit	PH 55 S	PH 75 S	PH 95 S	PH 120 S	PH 140 S	PH 190 S	PH 230 S	PH 275 S	PH 350 S	PH 420 S	PH 550 S
Nominal volume flow at dryer inlet	l/s	25	35	45	55	65	90	110	130	165	195	260
	m³/hr	90	126	162	198	234	324	396	468	594	702	936
Regeneration air consumption average at max. flow ^{(1) (2)}	%	18.5	18.5	18.5	18.5	18.5	18.5	18.5	18.5	18.5	18.5	18.5
Pressure drop at max. flow	barg	0.03	0.059	0.107	0.171	0.251	0.107	0.171	0.251	0.447	0.251	0.494
	psig	0.44	0.86	1.55	2.48	3.64	1.55	2.48	3.64	6.48	3.64	7.16
Connection inlet/outlet	G	1"	1"	1"	1"	1"	1 1/2"	1 1/2"	1 1/2"	1 1/2"	1 1/2"	1 1/2"
	NPT	1"	1"	1"	1"	1"	1 1/2"	1 1/2"	1 1/2"	1 1/2"	1 1/2"	1 1/2"
Integrated filter model	Super fine filter	TF 2 C S	TF 3 C S	TF 4 C S	TF 5 C S	TF 5 C S	TF 6 C S	TF 6 C S	TF 6 C S	TF 7 C S	TF 8 C S	TF 8 C S
	Dust filter	TF 2 S S	TF 3 S S	TF 4 S S	TF 5 S S	TF 5 S S	TF 6 S S	TF 6 S S	TF 6 S S	TF 7 S S	TF 8 S S	TF 8 S S
Height	mm	1070	1115	1285	1465	1615	1285	1465	1615	1695	1615	1915
	inch	42.1	43.9	50.6	57.7	63.6	50.6	57.7	63.6	66.7	63.6	75.4
Width	mm	620	620	620	620	620	620	620	620	620	620	620
	inch	24.4	24.4	24.4	24.4	24.4	24.4	24.4	24.4	24.4	24.4	24.4
Length	mm	401	401	401	401	401	571	571	571	571	738	738
	inch	15.8	15.8	15.8	15.8	15.8	22.5	22.5	22.5	22.5	29.1	29.1
Mass	kg	87	88	99	114	124	165	197	211	245	298	328
	lbs	191.8	194.0	218.3	251.3	273.4	363.8	434.3	465.2	540.1	657.0	723.1

*1. Flow is measured at reference conditions: 1 bara and 25°C at operating pressure of 7 barg, inlet temperature 35°C & std PDP of -40°C at the outlet.

Flow correction factors due to air inlet pressure Kp

Operating pressure	barg	4	5	6	7	8	9	10	11	12	13	14
Pressure correction factor	Kp	0.62	0.75	0.87	1	1.12	1.25	1.37	1.5	1.62	1.75	1.87

Flow correction factors due to air inlet temperature Kt

Temperature	°C	20	25	30	35	40	45	50
Temperature correction factor	Kt	1	1	1	1	0.84	0.67	0.55

PE 760 - 3390 S - Heated purge adsorption dryers

Features & Benefits


- ▶ Advanced energy management for lowest operating costs
 - Compressor synchronization
 - PDP control (optional)
 - Regeneration & cooling temperature control
- ▶ High-quality, high-efficient desiccant, selected for the right application
 - PDP -40°C/-40°F (std): Activated Alumina⁽¹⁾
 - PDP -70°C/-94°F (option): Molecular sieves and Activated alumina
- ▶ Minimal risk of crushed desiccant thanks to the sonic nozzle and the large vessel diameter
- ▶ Counter-current regeneration for optimal energy efficiency and guaranteed dry air
- ▶ High reliability and robust design
- ▶ Low noise levels while purging
- ▶ Designed for transportability
- ▶ High efficient heaters, designed for maximum lifetime and minimal risk
- ▶ Optimal control and monitoring thanks to the Purelogic™ controller

General Specifications

- ▶ Heated purge adsorption dryers: welded vessel design
- ▶ Dew points achievable: -40°C/-40°F & -70°C/-94°F
- ▶ Pressure range: 4-10 barg/58-145 psig
- ▶ Ambient temperature range: 1-40°C/34-104°F
- ▶ Inlet temperature range: 1-45°C/34-113°F
- ▶ Power supply: 400VAC 50Hz; 440-460VAC 60Hz



Options



PDP -70°C
(Except PE760)

PDP -70°C
(Except PE760)



In and outlet filters



Wooden packaging
(Std on PE760)



PDP control



Vessel insulation
(required for
PDP-70°C option)



Vessel safety
valves
(Std on PE760)

¹For PE760S (-40°C PDP) Desiccant used is silica gel WR & NWR.



With distinctive, patented technology, PE adsorption dryers provide you with a dry air solution; at a lower initial investment cost than PB blower purge dryers and a lower lifecycle cost than PH heatless dryers. PE dryers use heated purge air to remove moisture from the desiccant material.

PE 760S-3390S adsorption dryers are capable of drying air to a PDP of -40°C/-40°F as standard and -70°C/-94°F as option. The desiccant is housed in welded vessels, which are coated and can

operate up to 10 barg/145 psig (fatigue load). Mounted pre- and after- filters can be ordered as an option.

The Purelogic™ is the central brain of the adsorption dryer. It optimizes operating costs thanks to the availability of regeneration temperature control, PDP control (optional) and compressor synchronization; ensures maximum reliability by monitoring the most important parameters of the dryer; and offers impressive control and monitoring capabilities.

Technical specifications for PE 760S up to PE 3390S (standard version, PDP -40 °C)

Specification	Unit	PE 760 S	PE 1020 S	PE 1330 S	PE 2060 S	PE 2670 S	PE 3390 S
Nominal volume flow at dryer inlet ^{(1) (2)}	l/s	360	480	630	970	1260	1600
	m³/hr	1296	1728	2268	3492	4536	5760
Average purge air consumption	%	10	10	10	10	10	10
Pressure drop at max. flow	barg	0.27	0.17	0.17	0.17	0.17	0.11
	psig	3.92	2.47	2.47	2.47	2.47	1.60
Inlet and outlet connections	PN16	DN 50	DN 80	DN 80	DN 100	DN 100	DN 150
Optional pre & after filter sizes ⁽³⁾	Fine filter	PMH G 1189	PMH G 1529	PMH G 2125	FF 2 G HE	FF 3 G HE	FF 4 G HE
	Super fine filter	PMH C 1189	PMH C 1529	PMH C 2125	FF 2 C HE	FF 3 C HE	FF 4 C HE
	Dust filter	PMH S 1189	PMH S 1529	PMH S 2125	FF 2 S HE	FF 3 S HE	FF 4 S HE
Mass	kg	820	1130	1410	2280	2750	3560
	lbs	1808	2491	3109	5027	6063	7848
Height	mm	1829	2558	2612	2702	2684	2603
	inch	72	101	103	106	106	102
Width	mm	1075	930	930	1085	1085	1342
	inch	42	37	37	43	43	53
Length	mm	1100	1764	1884	2359	2472	2708
	inch	43	69	74	93	97	107

1. Flow is measured at reference conditions: 1 bara and 20°C at operating pressure of 7 barg, inlet temperature 35°C & std PDP of -40°C at the outlet.

2. Dryer designed for mentioned volume flow, based on average duty of 80%.

3. Filters are sized at reference conditions. Consult the AML of the filters for sizing outside the reference conditions.

Correction factor Kp x Kt for -40°C PDP

T inlet	Working pressure barg (psig)						
°C (°F)	4.5 (65)	5 (73)	6 (87)	7 (102)	8 (116)	9 (131)	10 (145)
<=20 (68)	"1,00"						
25 (77)							
30 (86)							
35 (95)							
40 (104)							
45 (113)	0.89	0.87	0.88	0.71	0.8	0.89	0.98
	0.42	0.5	0.62	0.49	0.55	0.61	0.67

Notes for PDP-40 variants

1) Correction factors are for 100% saturated compressed air

Correction factor Kp x Kt for -70°C PDP

T inlet	Working pressure barg (psig)						
°C (°F)	4.5 (65)	5 (73)	6 (87)	7 (102)	8 (116)	9 (113)	10 (145)
<=20 (68)	"1,00"						
25 (77)							
30 (86)							
35 (95)							
40 (104)							
45 (113)	0.89	0.87	0.88	0.76	0.86	0.95	0.80
	0.45	0.53	0.67	0.58	0.65	0.73	0.80

Notes for PDP-70 variants

1) Correction factors are for 80% saturated compressed air

PB 210 - 635 HE (P/ZP) - Blower purge/zero purge adsorption dryers

Features & Benefits


- ▶ Advanced energy management for lowest operating costs
 - Compressor synchronization
 - PDP control
 - Regeneration & cooling temperature control
 - Purge nozzle optimization (optional)
- ▶ Zero-purge variants for lowest life-cycle costs
 - Purge back-up mode for ambient conditions outside of limitations
- ▶ High-quality, high-efficient desiccant, selected for the right application
 - PDP -40°C/-40°F (std): silica gel WR & NWR
 - PDP -70°C/-94°F (optional): molecular sieves
- ▶ Minimal risk of crushed desiccant thanks to the sonic nozzle and the large vessel diameter
- ▶ Counter-current regeneration for optimal energy efficiency and guaranteed dry air
- ▶ High reliability and robust design
- ▶ Low noise levels while purging
- ▶ Designed for transportability
- ▶ High efficient heaters, designed for maximum lifetime and minimal risk
- ▶ Compact, efficient and reliable side-channel centrifugal blower
- ▶ Optimal control and monitoring thanks to the Purelogic™ controller

General Specifications

- ▶ Blower purge & zero purge adsorption dryers: welded vessel design
- ▶ Dew points achievable:
-40°C/-40°F & -70°C/-94°F
(-70°C/-94°F only with Purge Cooled option)
- ▶ Pressure range: 4-14 barg/58-203 psig
- ▶ Ambient temperature range: 1-45°C/34-113°F
- ▶ Inlet temperature range: 1-50°C/34-122°F
- ▶ Power supply: 400VAC 50Hz;
440-460VAC 60Hz



Options



**-70°C PDP
variant available**
(only available on
blower purge variants)



**Reverse in
and outlet pipe**



**NEMA 4
electrical enclosure**



**Insulated
vessels**



**Inlet blower
filters**



**Purge nozzle
optimization**



PB dryers are for customers who focus on energy efficiency and low lifecycle costs, while maintaining the highest standards in air purity. PB dryers use heated blower purge air to remove moisture from the desiccant material and have therefore no purge loss during regeneration. The Zero Purge variants reduce life cycle cost even further by also eliminating purge loss during cooling.

PB 210-635 HE adsorption dryers are capable of drying air to a PDP of -40°C/-40°F as standard and -70°C/-94°F as option for purge units. The desiccant is housed in welded vessels, which are coated and can operate up to 14.5 barg/210 psig (fatigue load). All dryers are standard equipped with 2 coalescing pre-filters before and 1 particulate filter after the dryer.

Operating costs are reduced to the absolute minimum thanks to PDP control, regeneration & cooling temperature control and compressor synchronization; which are all integrated in the Purelogic™ controller. Zero Purge variants are equipped with a purge back-up mode which switches the dryer to purge cooling mode in case PDP could not be met at ambient conditions outside of limitations. The Purelogic™ also ensures maximum reliability by monitoring the most important parameters of the dryer and offers impressive control and monitoring capabilities.

Technical specifications for PB 210 HE up to PB 635 HE (ZP) (standard version, PDP -40°C)

Specification	Unit	PB 210HE	PB 320 HE	PB 390 HE	PB 530 HE	PB 635 HE	PB 210 HE ZP	PB 320 HE ZP	PB 390 HE ZP	PB 530 HE ZP	PB 635 HE ZP
Cooling Mode	-	Purge	Purge	Purge	Purge	Purge	Zero Purge	Zero Purge	Zero Purge	Zero Purge	Zero Purge
Nominal volume flow at dryer inlet ⁽¹⁾	l/s	100	150	185	250	300	100	150	185	250	300
	m³/hr	360	540	666	900	1080	360	540	666	900	1080
Purge air consumption average	%	2	2	2	2	2	0	0	0	0	0
Pressure Drop Over Dryer	barg	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
	psig	2.90	2.90	2.90	2.90	2.90	2.90	2.90	2.90	2.90	2.90
Inlet and outlet connections	G	1 ½"	1 ½"	1 ½"	2"	2"	1 ½"	1 ½"	1 ½"	2"	2"
	NPT	1 ½"	1 ½"	1 ½"	2"	2"	1 ½"	1 ½"	1 ½"	2"	2"
Included pre and after filters	Fine filter	TF 6 G HE	TF 7 G HE	TF 8 G HE	TF 9 G HE	TF 9 G HE	TF 6 G HE	TF 7 G HE	TF 8 G HE	TF 9 G HE	TF 9 G HE
	Super fine filter	TF 6 C HE	TF 7 C HE	TF 8 C HE	TF 9 C HE	TF 9 C HE	TF 6 C HE	TF 7 C HE	TF 8 C HE	TF 9 C HE	TF 9 C HE
	Dust filter	TF 6 S HE	TF 7 S HE	TF 8 S HE	TF 9 S HE	TF 9 S HE	TF 6 S HE	TF 7 S HE	TF 8 S HE	TF 9 S HE	TF 9 S HE
Height	mm	1720	1770	1770	1816	1853	1855	1891	1891	1969	2006
	inch	67.7	69.7	69.7	71.5	73.0	73.0	74.4	74.4	77.5	79.0
Width	mm	770	870	870	955	1010	840	966	966	1098	1123
	inch	30.3	34.3	34.3	37.6	39.8	33.1	38.0	38.0	43.2	44.2
Length	mm	1250	1300	1300	1345	1425	1174	1360	1360	1580	1507
	inch	49.2	51.2	51.2	53.0	56.1	46.2	53.5	53.5	62.2	59.3
Mass	kg	640	680	710	775	820	400	498	537	663	765
	lbs	1411	1499	1565	1709	1808	882	1098	1184	1462	1687

1. Flow is measured at reference conditions: 1 barg and 20°C at operating pressure of 7 barg, inlet temperature 35°C & std PDP of -40°C at the outlet. (For ZP versions inlet temperature is 33°C)

Flow correction factors due to air inlet pressure

Operating pressure	barg	4.5	5	6	7	8	9	10	11	12	13	14
	psig	65	72	87	100	116	130	145	160	174	189	203
Pressure correction factor	Kp	0.687	0.75	0.88	1	1.13	1.25	1.38	1.5	1.62	1.74	1.86

Flow correction factors due to air inlet temperature (For -40°C PDP Units with Silica Gel)

Temperature	°C	20	25	30	35	40	45
	°F	68	77	86	95	104	113
Temperature correction factor	Kt	1	1	1	1	0.75	0.55

Flow correction factors due to air inlet temperature (For -70°C PDP Units with Molecular Sieves)

Temperature	°C	20	25	30	35	40	45	50	55
	°F	68	77	86	95	104	113	122	131
Temperature Correction Factor	Kt	1	1	1	1	1	0.78	0.61	0.49

Flow correction factors due to Pressure Dew Point (For 11 barg Units)

Dew point	°C	0	-40	-70
	°F	32	-40	-94
Dew point correction factor	Kdp	1	1	0.8

For accurate sizing for your operating conditions consult Pneumatech

PB 700 - 6350 HE (P/ZP) - Blower purge/zero purge adsorption dryers

Features & Benefits


- ▶ Advanced energy management for lowest operating costs
 - Compressor synchronization
 - PDP control
 - Regeneration & cooling temperature control
 - Purge nozzle optimization (optional)
- ▶ Zero-purge variants with cooling in closed loop
 - Lowest life-cycle costs
 - Excellent performance at high ambient temperatures
 - Frequency controlled blower to guarantee optimal cooler performance
- ▶ High-quality, high-efficient desiccant, selected for the right application
 - PDP -40°C/-40°F (std): silica gel + activated alumina
 - PDP -70°C/-94°F and HIT (optional): activated alumina & molecular sieves
- ▶ Minimal risk of crushed desiccant thanks to the sonic nozzle and the large vessel diameter
- ▶ Counter-current regeneration for optimal energy efficiency and guaranteed dry air
- ▶ High reliability and robust design
- ▶ Low noise levels while purging
- ▶ Designed for transportability
- ▶ Optimal control and monitoring thanks to the Purelogic™ controller

General Specifications

- ▶ Blower purge & zero purge adsorption dryers: welded vessel design
- ▶ Dew points achievable:
-40°C/-40°F & -70°C/-94°F
(-70°C/-94°F only with Zero Purge variants)
- ▶ Pressure range: 4-10 barg/58-145 psig
(14 barg/ 203 psig available on request)
- ▶ Ambient temperature range:
1-45°C/34-113°F (For temperatures above 40°C and up to 55°C see High Ambient Temp. option)
- ▶ Inlet temperature range: 1-45°C/34-113°F
(For temperatures above 45°C see HIT option)
- ▶ Power supply: 400VAC 50Hz;
440-460VAC 60Hz



Options



PDP -70°C

**-70°C PDP
variant available
(only for ZP variants)**



**Insulated vessels
(std on -70°C PDP Variant)**



**Inlet blower
filters**




**2nd PDP
read out**



**Purge nozzle
optimization**




**External pilot air
connection for low
pressure inlet**



High inlet
temperature

**High inlet
temperature variant
(not applicable on -70°C PDP)**



High ambient
temperature

**High ambient
temperature variant**



**In and outlet
filters**



**Vessel safety
valves**



**Wooden
packaging**



PB dryers are for customers who focus on energy efficiency and low lifecycle costs, while maintaining the highest standards in air purity. Pneumatech extends its PB dryer range to flows up to 10800 m³/hr with both blower purge and Zero Purge variants.

PB dryers use heated blower purge air to remove moisture from the desiccant material and have therefore no purge loss during regeneration. The Zero Purge variants reduce life cycle costs even further by also eliminating purge loss during cooling. The cooling phase happens in a closed loop, hereby minimizing the performance impact at high ambient temperature and relative humidity.

PB 700-6350 HE ZP dryers are capable of drying air to a PDP of -40°C/-40°F as standard and -70°C/-94°F as option. The desiccant is housed in welded vessels, which are coated and can operate up to 10 barg/145 psig (fatigue load). All dryers can be equipped with 2 coalescing pre-filters before and 1 particulate filter after the dryer.

Operating costs are reduced to the absolute minimum thanks to PDP control, regeneration & cooling temperature control and compressor synchronization; which are all integrated in the Purelogic™ controller. The Purelogic™ also ensures maximum reliability by monitoring the most important parameters of the dryer and offers impressive control and monitoring capabilities.

Technical specifications for PB 700 HE up to PB 6350 HE (standard version, PDP -40 °C)

Specification	Unit	PB 700 HE	PB 850 HE	PB 1150 HE	PB 1800 HE	PB 2350 HE	PB 2950 HE	PB 3800 HE	PB 4650 HE	PB 6350 HE	PB 700 HE ZP	PB 850 HE ZP	PB 1150 HE ZP	PB 1800 HE ZP	PB 2350 HE ZP	PB 2950 HE ZP	PB 3800 HE ZP	PB 4650 HE ZP	PB 6350 HE ZP
Cooling Mode	-	Purge	Purge	Purge	Purge	Purge	Purge	Purge	Purge	Purge	Zero Purge Air Cooled	Zero Purge Air Cooled	Zero Purge Air Cooled	Zero Purge Air Cooled	Zero Purge Air Cooled	Zero Purge Water Cooled	Zero Purge Water Cooled	Zero Purge Water Cooled	Zero Purge Water Cooled
Nominal volume flow at dryer inlet ⁽¹⁾	l/s	330	400	550	850	1100	1400	1800	2200	3000	330	400	550	850	1100	1400	1800	2200	3000
	m³/hr	1188	1440	1980	3060	3960	5040	6480	7920	10800	1188	1440	1980	3060	3960	5040	6480	7920	10800
Avg. purge air consumption	%	2%	2%	2%	2%	2%	2%	2%	2%	2%	0	0	0	0	0	0	0	0	0
Pressure drop over dryer	barg	0.12	0.12	0.12	0.12	0.12	0.1	0.16	0.22	0.18	0.12	0.12	0.12	0.12	0.12	0.1	0.16	0.22	0.18
	psig	1.74	1.74	1.74	1.74	1.74	1.45	2.32	3.19	2.61	1.74	1.74	1.74	1.74	1.74	1.45	2.32	3.19	2.61
Inlet and outlet connections	DN, acc to DIN2633 PN16	80	80	80	100	100	150	150	150	200	80	80	80	100	100	150	150	150	200
Optional pre & after filter sizes ⁽²⁾	Fine filter	PMH G 1529	PMH G 1529	FF 1 G HE	FF 2 G HE	FF 3 G HE	FF 4 G HE	FF 5 G HE	FF 6 G HE	FF 7 G HE	TF 10 G HE	TF 10 G HE	FF 1 G HE	FF 2 G HE	FF 3 G HE	FF 4 G HE	FF 5 G HE	FF 6 G HE	FF 7 G HE
	Super fine filter	PMH C 1529	PMH C 1529	FF 1 C HE	FF 2 C HE	FF 3 C HE	FF 4 C HE	FF 5 C HE	FF 6 C HE	FF 7 C HE	TF 10 C HE	TF 10 C HE	FF 1 C HE	FF 2 C HE	FF 3 C HE	FF 4 C HE	FF 5 C HE	FF 6 C HE	FF 7 C HE
	Dust filter	PMH S 1529	PMH S 1529	FF 1 S HE	FF 2 S HE	FF 3 S HE	FF 4 S HE	FF 5 S HE	FF 6 S HE	FF 7 S HE	TF 10 S HE	TF 10 S HE	FF 1 S HE	FF 2 S HE	FF 3 S HE	FF 4 S HE	FF 5 S HE	FF 6 S HE	FF 7 S HE
Mass	kg	1190	1300	1620	2600	3040	4200	4800	5750	7800	1370	1490	1830	2840	3340	4550	5150	6100	8150
	lb	2624	2866	3571	5732	6702	9259	10582	12677	17196	3020	3285	4034	6261	7363	10031	11354	13448	17968
Height	mm	2558	2558	2612	2702	2681	2488	2548	2548	2793	2558	2558	2612	2702	2681	2548	2548	2548	2893
	inch	100.7	100.7	102.8	106.4	105.6	98.0	100.3	100.3	110.0	100.7	100.7	102.8	106.4	105.6	100.3	100.3	100.3	113.9
Width	mm	1024	1024	1024	1175	1175	2373	2400	2792	2834	1351	1351	1428	1530	1530	2779	2825	3009	3053
	inch	40.3	40.3	40.3	46.3	46.3	93.4	94.5	109.9	111.6	53.2	53.2	56.2	60.2	60.2	109.4	111.2	118.5	120.2
Length	mm	1764	1764	1884	2359	2472	2809	2830	2993	3385	1764	1764	1884	2359	2472	3122	3197	3197	3792
	inch	69.4	69.4	74.2	92.9	97.3	110.6	111.4	117.8	133.3	69.4	69.4	74.2	92.9	97.3	122.9	125.9	125.9	149.3

- Flow is measured at reference conditions: 1 bara and 20°C at operating pressure of 7 barg, inlet temperature 35°C & std PDP of -40°C at the outlet.
- Filters are sized at reference conditions. Consult the AML of the filters for sizing outside the reference conditions.

Correction factor Kp x Kt for PDP-40

T inlet	Working pressure barg (psig)						
°C (°F)	4.5 (65)	5 (73)	6 (87)	7 (102)	8 (116)	9 (131)	10 (145)
<=20 (68)	"1,00"						
25 (77)							
30 (86)							
35 (95)							
40 (104)							
45 (113)	0.89	0.87	0.88	0.71	0.8	0.89	0.98
	0.42	0.5	0.62				
	0.29	0.34	0.43	0.49	0.55	0.61	0.67

Notes for PDP-40 variants

- Correction factor are for 100% saturated compressed air
- For temperatures above 45 deg C see HIT-variant

For accurate sizing for your operating conditions consult Pneumatech

PB 760 - 3390 S - The cost efficient alternative to PB 700-2950 HE

Features & Benefits


- ▶ Advanced energy management for lowest operating costs
 - Compressor synchronization
 - PDP control (optional)
 - Regeneration & cooling temperature control
- ▶ High-quality, high-efficient desiccant, selected for the right application activated alumina
- ▶ Minimal risk of crushed desiccant thanks to the sonic nozzle and the large vessel diameter
- ▶ Counter-current regeneration for optimal energy efficiency and guaranteed dry air
- ▶ High reliability and robust design
- ▶ Low noise levels while purging
- ▶ Designed for transportability
- ▶ High efficient heaters, designed for maximum lifetime and minimal risk
- ▶ Compact, efficient and reliable side-channel centrifugal blower
- ▶ Optimal control and monitoring thanks to the Purelogic™ controller

General Specifications

- ▶ Blower purge adsorption dryers: welded vessel design
- ▶ Dew points achievable: -40°C/-40°F
- ▶ Pressure range: 4-10 barg/58-145 psig
- ▶ Ambient temperature range: 1-40°C/34-104°F
For ambient temperatures above 40 deg C see High Ambient Temperature variant
- ▶ Inlet temperature range: 1-45°C/34-113°F
For temperatures above 45 deg C see HIT-variant
- ▶ Power supply: 400VAC 50Hz;
440-460VAC 60Hz



Options



Blower inlet filter



In and outlet filters



Vessel safety valves



External pilot air connection




PDP control




Wooden packaging



Vessel insulation



High inlet temperature



High ambient temperature
(not on PB760S)



PB dryers are for customers who focus on energy efficiency and low lifecycle costs, while maintaining the highest standards in air purity. PB dryers use heated blower purge air to remove moisture from the desiccant material and have therefore no purge loss during regeneration.

PB 760-3390 S adsorption dryers are capable of drying air to a PDP of -40°C/-40°F. The desiccant is housed in welded vessels, which are coated and can operate up to

10 barg/145 psig (fatigue load). Mounted pre- and after-filters can be ordered as an option.

The Purelogic™ is the central brain of the adsorption dryer. It optimizes operating costs thanks to the availability of regeneration & cooling temperature control, PDP control (optional) and compressor synchronization; ensures maximum reliability by monitoring the most important parameters of the dryer; and offers impressive control and monitoring capabilities.

Technical specifications for PB 760S up to PB 3390S (standard version, PDP -40 °C)

Specification	Unit	PB 760 S	PB 1020 S	PB 1330 S	PB 2060 S	PB 2670 S	PB 3390 S
Maximum volume flow at dryer inlet ^{(1) (2)}	l/s	360	480	630	970	1260	1600
	m ³ /hr	1296	1728	2268	3492	4536	5760
Average purge air consumption ⁽³⁾	%	2%	2%	2%	2%	2%	2%
Pressure drop over dryer	barg	0.2	0.16	0.16	0.16	0.16	0.11
	psig	2.9	2.32	2.32	2.32	2.32	1.60
Inlet and outlet connections	G Thread/DN, acc to DIN2633 PN16	ISO 7-R2" ⁽²⁾	DN80	DN80	DN100	DN100	DN150
Optional pre & after filter sizes ⁽⁴⁾	Fine filter	TF 9 G S	TF 10 G S	TF 11 G S	FF 2 G HE	FF 3 G HE	FF 4 G HE
	Super fine filter	TF 9 C S	TF 10 C S	TF 11 C S	FF 2 C HE	FF 3 C HE	FF 4 C HE
	Dust filter	TF 9 S S	TF 10 S S	TF 11 S S	FF 2 S HE	FF 3 S HE	FF 4 S HE
Mass	kg	1160	1355	1700	2720	3185	4470
	lbs	2557	2987	3748	5997	7022	9855
Height	mm	1829	2558	2612	2702	2681	2488
	inch	72.0	100.7	102.8	106.4	105.6	98.0
Width	mm	1028	1024	1024	1175	1175	2373
	inch	40.5	40.3	40.3	46.3	46.3	93.4
Length	mm	1100	1764	1884	2359	2472	2809
	inch	43.3	69.4	74.2	92.9	97.3	110.6

1. Flow is measured at reference conditions: 1 bara and 20°C at operating pressure of 7 barg, inlet temperature 35°C & std PDP of -40°C at the outlet.

2. Dryer designed for mentioned volume flow, based on average duty of 80%.

3. Specially designed adapters are to be used when no filter is ordered.

4. Filters are sized at reference conditions. Consult the AML of the filters for sizing outside the reference conditions.

Correction factor Kp x Kt for PDP-40

T inlet	Working pressure barg (psig)						
°C (°F)	4.5 (65)	5 (73)	6 (87)	7 (102)	8 (116)	9 (131)	10 (145)
<=20 (68)	"1,00"						
25 (77)							
30 (86)							
35(95)							
40(104)	0.42	0.5	0.62	0.71	0.8	0.89	0.98
45(113)	0.29	0.34	0.43	0.49	0.55	0.61	0.67

Notes for PDP-40°C variants

1) Correction factor are for 100% saturated compressed air.

Do not ‘over-dry’ your entire compressed air network

Dry air comes with a cost, both in terms of initial investment as well as running costs. The required dryness should be chosen based on the largest compressed air consumers, while more critical applications can be covered with a low PDP dryer at point-of-use.

So before you install a centralized adsorption dryer, verify whether such high degree of dryness is required for your entire system. It could be sufficient to install a centralized refrigeration dryer, and to place a small adsorption or membrane dryer at point-of-use for critical applications.



Membrane Dryers

Because they are not powered by electricity, membrane dryers function safely in environments that must be explosion proof such as laboratories. Thanks to their quiet operation, membrane dryers can be used close to the workplace.

Pneumatech offers a range of 5 models for low flow applications.

M POU 2 - 16 - Point-of-use membrane dryers

Features and Benefits

- ▶ No power source needed
- ▶ Simple yet eco-friendly technology
 - No desiccants or refrigerants used for drying
 - No condensate drains
- ▶ Guaranteed performance
 - High water vapor selectivity thanks to non-porous membrane
 - No penetration of gases other than moisture
- ▶ Maintenance free
 - No wear and tear of any mechanical or electrical part
 - No need of replacement of any component
- ▶ Easy to transport and install
 - Built-in purging circuits
 - Easy and simple dew point adjustments thanks to the purge low control

General Specifications

- ▶ Dew points achievable: up to $-40^{\circ}\text{C}/-40^{\circ}\text{F}$
 - Note: only energy-efficient up to pressure dew point reductions of $30^{\circ}\text{C}/86^{\circ}\text{F}$
- ▶ Operating pressure range:
0 - 8.5 barg/0-120 psig
- ▶ Operating temperature range:
 $-20^{\circ} - 55^{\circ}\text{C} / -4^{\circ} - 131^{\circ}\text{F}$
- ▶ Ambient temperature range:
 $-20^{\circ} - 55^{\circ}\text{C} / -4^{\circ} - 131^{\circ}\text{F}$



Applications



Dehumidified
sampling gases for
gas analysers



Laser
machining tool



Paper industry



EDM tools



Food and
beverages



Gas
generators

Pneumatech offers an easy-to-use and simple drying solution for small compressed air needs. Pneumatech's point-of-use membrane dryer does not require any power source, is compact and easy to install. This makes the dryer suitable for various smaller compressed air applications where a higher degree of dehumidification is required, such as laser machining tools, precision measuring equipment, gas analyzers and small gas generators.

can go down to -40°C/-40°F. This is achieved by a hollow-fiber membrane, where moisture can diffuse through the fine pores of the fiber bundles. When differences in moisture concentration arise between the inside and outside of a fiber membrane, moisture is transferred through the membrane surface to equalize the moisture concentration on both sides of the membrane. Part of the dry air is used as purge air in order to remove the moisture from the incoming wet air.

The pressure dew point achieved by membrane dryers is dependent on the inlet temperature of the compressed air; but

Technical specifications for M POU 2-16							
Product → Specification ↓	Unit		M POU 2	M POU 3	M POU 5	M POU 11	M POU 16
Nominal volume flow at dryer inlet ⁽¹⁾	l/s		0,83	1,33	2,50	5,00	7,50
	m³/hr		3	4,8	9	18	27
Supply Gas Inlet and outlet connections	Inlet (G/NPT)		1/8"	1/8"	1/4"	3/8"	3/8"
	Outlet (G/NPT)		1/4"	1/4"	1/4"	1/4"	1/4"
Weight	kg		0,27	0,27	0,34	0,68	0,72
	lbs		0,59	0,6	0,76	1,5	1,59
Dimensions	Width	mm	61	61	70	100	100
		inch	2,4	2,4	2,8	3,9	3,9
	Height	mm	112	112	153	200	200
		inch	4,4	4,4	6,0	7,9	7,9
	Length	mm	31	31	40	50	50
		inch	1,2	1,2	1,6	2,0	2,0

1. Flow is measured at Reference Conditions: 1 bara and 20°C at operating pressure of 7 barg, inlet temperature 35°C & 30°C dew point reduction on inlet temperature..

PMD 1 - 7 - Membrane dryers

Features and Benefits


- ▶ Lowest total cost of ownership ensuring the highest air quality
- ▶ Compact size and flexible design allows different orientation per application
- ▶ Pneumatech's unique PMD dryer range ensures the lowest pressure drop and the lowest purge air use – providing real energy savings without compromise in production reliability and efficiency. Simple yet eco-friendly technology.
- ▶ Dry air in environments with strict safety or environmental requirements:
 - Low flow environments
 - Areas without electrical supply
 - Areas with explosion proof requirements
 - Noise sensitive areas
 - Corrosion sensitive areas
 - Pneumatech's membrane dryers perform where others won't:
 - Small spaces
 - Areas where flexible mounting is required
 - High vibration areas
 - Widely fluctuating temperatures
- ▶ State of the art fiber technology offering maximum efficiency
 - An engineers unique coating helps the PMD membrane dryers increase the separation efficiency between water vapour, oxygen and nitrogen
 - Extremely low air leakages and lowest purge loss in comparison with other standard membrane dryers
- ▶ Lowest pressure drop thanks to minimal air resistance
 - Simple and longitudinal design ensures steady compressed air flow eliminating unwanted twists and turns inside the housing resulting into minimal pressure drop and utmost efficiency
- ▶ Variants to suit your performance needs
- ▶ Equipped with our Ultimate filters for optimal performance
- ▶ Pneumatech's dryer range includes the P and N model range, each in 7 different sizes
- ▶ P range: Ensures a suppression of 32° C (55° F), giving at the reference conditions an outlet air pressure dew point of 3° C (40° F)
- ▶ N range: Lowers the inlet dew point with 55°C (100° F), giving a pressure dew point of -20°C (-5° F) at the reference conditions



Variants



Version with
purge control



Version without
purge control

Options



Electronic drain



Wall brackets



With its pre-filters, Pneumatech PMD dryers remove oil particles and moisture from compressed air in the most demanding conditions, at the lowest energy cost. Thanks to their special fiber technology, PMD dryers ensure the lowest pressure drop and purge air loss for the highest possible efficiency, saving you time and money.

From small spaces to environments with fluctuating ambient temperatures, PMD dryers can perform in a wide variety of harsh and critical conditions. PMD dryers also come with different types of membranes, allowing you to choose the exact air treatment you need and the dew point your operation requires. With an innovative design, PMD dryers provide the quality of air that will increase the reliability and energy efficiency of your production.

Technical specifications for PMD P																						
Product → Specification ↓	Unit	PMD 1P			PMD 2P			PMD 3P			PMD 4P			PMD 5P			PMD 6P			PMD 7P		
Pressure	bar	7	10	13	7	10	13	7	10	13	7	10	13	7	10	13	7	10	13	7	10	13
	psi	102	145	190	102	145	190	102	145	190	102	145	190	102	145	190	102	145	190	102	145	190
Max. inlet flow	m³/h	4.0	14.4	8.5	18.0	25.2	30.6	32.4	43.2	50.4	50.4	68.4	79.2	68.4	90.0	115.2	90.0	122.4	151.2	126.0	158.4	198.0
	cfm	5.0	18.0	10.6	10.6	14.8	18.0	19.1	25.4	29.7	29.7	40.3	46.6	40.3	53.0	67.8	53.0	72.1	89.0	74.2	93.3	116.6
Purge	%	14	10	8	15	11	9	15	11	9	15	14	11	14	11	8	14	10	8	14	11	9
Pressure drop	mBar	100	100	100	170	170	170	170	170	170	270	270	270	170	175	180	240	240	250	180	200	190
	psi	1.5	1.5	1.5	2.5	2.5	2.5	2.5	2.5	2.5	3.9	3.9	3.9	2.5	2.5	2.6	3.5	3.5	3.6	2.6	2.9	2.8
Filter model		PMH G 54, PMH C 54	PMH G 54, PMH C 54	PMH G 54, PMH C 54	PMH G 54, PMH C 54	PMH G 54, PMH C 54	PMH G 54, PMH C 54	PMH G 54, PMH C 54	PMH G 54, PMH C 54	PMH G 54, PMH C 54	PMH G 85, PMH C 85	PMH G 85, PMH C 85	PMH G 85, PMH C 85	PMH G 85, PMH C 85	PMH G 85, PMH C 85	PMH G 119, PMH C 119	PMH G 119, PMH C 119	PMH G 119, PMH C 119	PMH G 119, PMH C 119	PMH G 119, PMH C 119	PMH G 119, PMH C 119	
Connection	G	3/8"	3/8"	3/8"	3/8"	3/8"	3/8"	1/2"	1/2"	1/2"	1/2"	1/2"	1/2"	1/2"	1/2"	1/2"	1/2"	1/2"	1/2"	1/2"	1/2"	3/4"
Weight excl. filters	kg	0.6	0.6	0.6	0.6	0.6	0.6	1.7	1.7	1.7	1.7	1.7	1.7	2.8	2.8	2.8	2.8	2.8	2.8	5.0	5.0	5.0
	lbs	1.3	1.3	1.3	1.3	1.3	1.3	3.7	3.7	3.7	3.7	3.7	3.7	6.2	6.2	6.2	6.2	6.2	6.2	11.0	11.0	11.0
Weight incl. filters	kg	2.9	2.9	2.9	2.9	2.9	2.9	4.0	4.0	4.0	4.2	4.2	4.2	5.3	5.3	5.7	5.7	5.7	5.7	7.9	7.9	8.9
	lbs	6.4	6.4	6.4	6.4	6.4	6.4	8.8	8.8	8.8	9.2	9.2	9.2	11.7	11.7	12.5	12.5	12.5	12.5	17.4	17.4	20
Dimensions	mm	99			99			122			122			145			145			170		
	inch	A			3.9			4.8			4.8			5.7			5.7			6.7		
	mm	B			532			532			733			733			79			709		
	inch	20.9			20.9			28.9			28.9			27.9			27.9			28.8		
	mm	C			757			757			959			959			934			934		
	inch	29.8			29.8			37.8			37.8			36.8			36.8			37.7		
	mm	D			264			264			277			277			287			342		
	inch	10.4			10.4			10.9			10.9			11.3			13.5			14.0		
	mm	E			716			716			906			906			881			936		
	inch	28.2			28.2			35.7			35.7			34.7			36.9			37.5		
	mm	F			291			291			313			313			334			334		
	inch	11.5			11.5			12.3			12.3			13.1			13.1			14.2		

Notes:
Add 100mm free space below the filters for easy cartridge exchange
The purge stop option adds 50mm to diameter A and height D

Kp Flow correction factor due to compressed air inlet pressure (e) 7bar							
Operating pressure	bar	4	5	6	7	8	9
Pressure correction factor	Kp	0.61	0.74	0.87	1.00	1.12	1.25

Kp Flow correction factor due to compressed air inlet pressure (e) 10bar						
Operating pressure	bar	8	9	10	11	12
Pressure correction factor	Kp	0.79	0.88	1.00	1.06	1.14



Kp Flow correction factor due to compressed air inlet pressure (e) 13bar					
Operating pressure	bar	11	12	13	14
Pressure correction factor	Kp	0.89	0.97	1.00	1.12

Please contact Pneumatech team for conditions other than specified.

PMD 1 - 7 - Membrane dryers

General Specifications

- ▶ Standard equipment, complete scope of supply ensuring peace of mind for you
 - Purge block, fitted onto the dryer, controls the purged air
 - Two pre-filters, all interconnection components included, ensure optimal inlet air quality
 - Flexible inlet and outlet caps allow filters and dryer to be mounted in two settings for optimal use of available space
- Optional equipment
 - Purge air stop to save purge when there is no air consumption
 - Wall mounting
 - Electronic condensate drain
- ▶ Membrane Dryers
 - Pressure dew point suppressions of 15°C (27°F) to as much as 95°C (171°F) are possible. Correction factors give the correct flow
 - Compressed air inlet pressure: 4 - 14bar(g), 58 - 203 psi(g)
 - Ambient temperature range: 1-66°C/34-150°F
 - Inlet temperature range: 1-66°C/34-150°F
 - The achievable PDP of the PMD membrane dryer range is dependent on inlet dew point





Technical specifications for PMD N

Product → Specification ↓	Unit	PMD 1N			PMD 2N			PMD 3N			PMD 4N			PMD 5N			PMD 6N			PMD 7N		
Pressure	bar	7	10	13	7	10	13	7	10	13	7	10	13	7	10	13	7	10	13	7	10	13
	psi	102	145	190	102	145	190	102	145	190	102	145	190	102	145	190	102	145	190	102	145	190
Max. inlet flow	m³/h	5.4	7.2	9.0	12.6	16.2	19.8	21.6	28.8	36.0	32.4	43.2	54.0	46.8	64.8	82.8	61.2	79.2	100.8	93.6	126.0	162.0
	cfm	3.2	4.2	5.3	7.4	9.5	11.7	12.7	17.0	21.2	19.1	25.4	31.8	27.6	38.2	48.8	36.0	46.6	59.4	55.1	74.2	95.4
Purge	%	18	13	11	19	13	10	17	12	10	17	14	10	17	12	10	19	14	10	18	13	10
Pressure drop	m bar	80	80	80	250	240	240	160	150	150	250	240	240	180	190	190	250	240	250	250	240	250
	psi	1.2	1.2	1.2	3.6	3.5	3.5	2.3	2.2	2.2	3.6	3.5	3.5	2.6	2.8	2.8	3.6	3.5	3.6	3.6	3.5	3.6
Filter model		DD9, PD9	DD9, PD9	DD9, PD9	DD9, PD9	DD9, PD9	DD9, PD9	DD9, PD9	DD9, PD9	DD9, PD9	DD9, PD9	DD9, PD9	DD9, PD9	DD17, PD17	DD17, PD17	DD17, PD17	DD17, PD17	DD17, PD17	DD17, PD17	DD32, PD32	DD32, PD32	DD32, PD32
Connection	G	3/8"	3/8"	3/8"	3/8"	3/8"	3/8"	1/2"	1/2"	1/2"	1/2"	1/2"	1/2"	1/2"	1/2"	1/2"	1/2"	1/2"	1/2"	1/2"	1/2"	1/2"
Weight excl. filters	kg	0.7	0.7	0.7	0.9	0.9	0.9	2.4	2.4	2.4	2.4	2.4	2.4	3.6	3.6	3.6	3.6	3.6	3.6	6.8	6.8	6.8
	lbs	1.5	1.5	1.5	2.0	2.0	2.0	5.3	5.3	5.3	5.3	5.3	5.3	7.9	7.9	7.9	7.9	7.9	7.9	15.0	15.0	15.0
Weight incl. filters	kg	3.0	3.0	3.0	3.2	3.2	3.2	4.7	4.7	4.7	4.7	4.7	4.7	6.1	6.1	6.1	6.1	6.1	6.1	9.7	9.7	9.7
	lbs	6.6	6.6	6.6	7.0	7.0	7.0	10.3	10.3	10.3	10.3	10.3	10.3	13.4	13.4	13.4	13.4	13.4	13.4	21.3	21.3	21.3
Dimensions	mm	99			99			122			122			145			145			170		
	inch	A			3.9			4.8			4.8			5.7			5.7			6.7		
	mm	715			1020			1076			1076			1074			1074			1113		
	inch	B			28.1			40.2			42.4			42.3			42.3			43.8		
	mm	940			1245			1302			1302			1299			1299			1338		
	inch	C			37.0			49.0			51.3			51.1			51.1			52.7		
	mm	264			264			277			277			287			287			355		
	inch	D			10.4			10.4			10.9			11.3			11.3			14.0		
	mm	899			1204			1249			1249			1246			1246			1334		
	inch	E			35.4			47.4			49.2			49.1			49.1			52.5		
	mm	291			291			313			313			334			334			361		
	inch	F			11.5			11.5			12.3			12.3			13.1			14.2		

Notes: PMD 5P-7: dimensions, filters and weight of PMD 6P
Add 100mm free space below the filters for easy cartridge exchange
The purge stop option adds 50mm to diameter A and height D

Kp Flow correction factor due to compressed air inlet pressure (e) 7bar

Operating pressure	bar	4	5	6	7	8	9
Pressure correction factor	Kp	0.62	0.75	0.88	1.00	1.13	1.26

Kp Flow correction factor due to compressed air inlet pressure (e) 10bar

Operating pressure	bar	8	9	10	11	12
Pressure correction factor	Kp	0.84	0.94	1.00	1.12	1.22

Kp Flow correction factor due to compressed air inlet pressure (e) 13bar

Operating pressure	bar	11	12	13	14
Pressure correction factor	Kp	0.96	1.04	1.00	1.20

Please contact Pneumatech team for conditions other than specified.

The importance of defining the right purity

Purity has a substantial impact on the sizing and the energy efficiency of a gas generator. In order to increase purity, air needs to stay longer in contact with the adsorbent, meaning that the outlet flow needs to be reduced substantially.

It is thus very important to define the right purity for the right application. High purity levels are often recommended by gas companies to make the business case for on-site gas generators look worse and to defend their own business. There are however few applications requiring purity levels above 99,9% nitrogen purity.



Gas Generators

Pneumatech designs and manufactures both standard and engineered on-site gas generator products. Nitrogen and oxygen generators are available with Pressure Swing Adsorption (PSA) technology, resulting in nitrogen purities up to 99,999% and oxygen purities up to 95%. Membrane technology is also offered for nitrogen purity levels up to 99,5%.

Pre-defined high-pressure nitrogen skids have been developed as a plug-and-play solution for various applications like laser-cutting. Our engineering department hence becomes your best partner for all kinds of special requests.

PPNG 6 - 68 HE - Nitrogen generator with pressure swing adsorption technology

Features & Benefits

- ▶ Advanced energy saving control
 - Reduced air consumption at low nitrogen demand
 - Also compensates for altering ambient conditions and purity settings
 - No compressed air use when no nitrogen is consumed
- ▶ Outstanding air factors thanks to back-flow pressurization
- ▶ High-quality, high-efficient Carbon Molecular Sieves selected for the right application
- ▶ Guaranteed purity
 - Automatically regulates to the requested nitrogen pressure and purity
 - Zirconia sensors for reliable purity measurement
- ▶ Designed & tested for cyclic load
- ▶ Optimal control and monitoring thanks to Purelogic™ Controller
 - Self-protective monitoring of the feed air quality
 - Feed-air blow-off in case of contamination
 - Nitrogen flow, purity and pressure measured and controlled
 - Automatic start-up

General Specifications

- ▶ Pressure Swing Adsorption (PSA) nitrogen generators - extruded profile design
- ▶ Nitrogen purity achievable: 95% - 99.9% (PCT Variant) & 99.95%-99.999% (PPM variant)
- ▶ Inlet pressure range: 4-13 barg /60-189 psig
- ▶ Inlet temperature range: 5-60°C/41-140°F
- ▶ Required inlet air quality: 1-4-1 according to ISO 8573-1:2010
- ▶ Power supply: 115-230VAC/50-60Hz



Options



Wooden
packaging

The PPNG6-68HE series is Pneumatech's premium on-site nitrogen solution for low to medium flows, with best-in-class performance and the most complete scope of supply.

The generator has outstanding air factors at full load thanks to the use of highly efficient Carbon Molecular Sieves (CMS) and back-flow pressurization.

The air consumption is also optimized at reduced nitrogen flow or pressure demands, thanks to the advanced energy

saving algorithm, which automatically adjusts the cycle times of the generator.

The control and monitoring capabilities of the PPNG6-68 HE are truly impressive. Purity is guaranteed at all times by opening the consumer valve only at the requested purity level and flushing nitrogen when purity is not reached. Feed air quality is controlled by monitoring temperature, pressure and PDP. The feed air is blown off in case of contamination. All risks of possible CMS damage are eliminated thanks to the automatic start-up feature.

Technical specifications for PPNG 6 - PPNG 68 HE

Specifications	Units	Variant	Product→ Purity ↓	PPNG 6 HE	PPNG 7 HE	PPNG 9 HE	PPNG 12 HE	PPNG 15 HE	PPNG 18 HE	PPNG 22 HE	PPNG 28 HE	PPNG 30 HE	PPNG 37 HE	PPNG 41 HE	PPNG 50 HE	PPNG 63 HE	PPNG 68 HE
Nominal free nitrogen delivery ⁽¹⁾	m³/hr	PCT (%)	95	18.4	23.4	28.8	36.4	46.8	57.2	70.2	86.0	93.6	114.8	128.9	157.7	NA	NA
			99.9	5.8	7.2	9.0	11.5	14.8	18.0	22.0	26.6	29.2	35.6	40.7	49.7	61.9	66.6
		PPM (%)	99.999	1.9	2.5	2.9	4.0	5.0	6.1	7.9	9.7	10.4	13.0	15.8	19.4	22.7	25.9
Nominal air consumption	m³/hr	PCT (%)	95	33.8	43.6	53.3	67.7	87.1	106.6	130.7	159.8	174.2	213.1	243.7	298.1	NA	NA
			99.9	18.0	23.4	28.4	36.4	46.8	56.9	69.8	85.7	93.2	114.1	135.7	166.0	196.9	221.0
		PPM (%)	99.999	12.2	15.5	19.1	24.1	31.3	38.2	44.3	54.0	59.0	72.4	88.6	108.4	124.2	144.4
Air Factor	-	PCT (%)	95	1.86	1.86	1.86	1.86	1.86	1.86	1.86	1.86	1.86	1.86	1.89	2	NA	NA
			99.9	3.19	3.19	3.19	3.19	3.19	3.19	3.19	3.19	3.19	3.19	3.33	3.33	3.18	3.33
		PPM (%)	99.999	6.3	6.3	6.3	6.3	6.3	6.3	5.6	5.6	5.6	5.6	5.6	5.6	5.5	5.6
Pressure dewpoint outlet	°C / °F			-40	-40	-40	-40	-40	-40	-40	-40	-40	-40	-40	-40	-40	-40
Maximum pressure drop		PCT (%)	95	0.4	0.4	0.4	0.5	0.5	0.5	0.6	0.6	0.6	0.6	0.6	0.9	0.9	NA
			99.9	0.3	0.3	0.3	0.3	0.3	0.3	0.3	0.3	0.3	0.3	0.5	0.5	0.6	0.6
		PCT (%)	99.999	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.3	0.3	0.3
Length	mm			775	775	775	775	775	775	1400	1400	1400	1400	1400	1400	1400	1400
	inch			31	31	31	31	31	31	55	55	55	55	55	55	55	55
Width	mm			840	840	840	840	840	840	840	840	840	840	840	840	840	970
	inch			33	33	33	33	33	33	33	33	33	33	33	33	33	38
Height	mm			2015	2015	2015	2015	2015	2015	2015	2015	2015	2015	2015	2015	2015	2015
	inch			79	79	79	79	79	79	79	79	79	79	79	79	79	79
Mass	kg			264	277	290	326	359	380	619	647	683	736	865	1038	1211	1211
	lbs			582	611	639	719	791	838	1365	1426	1506	1623	1907	2288	2670	2670
Inlet and outlet connections	G/NPT			1"	1"	1"	1"	1"	1"	1"	1"	1"	1"	1"	1"	1"	1"

1. Flow is measured at Reference Conditions: 1 bara and 20°C at operating pressure of 7 barg, inlet temperature 20°C & Air Inlet Quality of ISO 8573-1:2010 class 1-4-1

PPNG 6 - 68 S - Nitrogen generator with pressure swing adsorption technology

Features & Benefits

- ▶ Energy saving control
- ▶ Outstanding air factors thanks to back-flow pressurization
- ▶ High-quality, high-efficient Carbon Molecular Sieves selected for the right application
- ▶ Guaranteed purity
 - Zirconia sensors for reliable purity measurement
 - Dedicated high purity variants
 - Purity certificates
- ▶ Designed & tested for cyclic load
- ▶ Reliable, efficient and low-maintenance angle seat valves
- ▶ Carefully designed exhaust silencers resulting in quiet and safe operation of the generator
- ▶ Optimal control and monitoring thanks to Purelogic™ Controller

General Specifications

- ▶ Pressure Swing Adsorption (PSA) nitrogen generators - extruded profile design
- ▶ Nitrogen purity achievable:
95% - 99.9% (PCT Variant) & 99.95%-99.999% (PPM variant)
- ▶ Inlet pressure range: 4-13 barg /60-189 psig
- ▶ Inlet temperature range: 5-60°C/41-140°F
- ▶ Required inlet air quality:
1-4-1 according to ISO 8573-1:2010
- ▶ Power supply: 115-230VAC/50-60Hz



Options



Wooden
packaging



Flow meter



PDP sensor kit



The PPNG 6-68s series provides an efficient source of nitrogen for use in various industries like food and beverage, pharma, electronics and plastics. PPNG nitrogen generators use Pressure Swing Adsorption technology to extract nitrogen molecules from the compressed air; and can reach purities from 95% up to 99,999%. Nitrogen pressures can go up to 12 barg without the need for an additional booster. The air factors of the PPNG6-68s range are outstanding, making the return on investment very attractive compared to traditional gas supply.

With its PPNG 6-68s series, Pneumatech follows the plug and play philosophy. Pressure vessels, valves, exhaust system,

sensors and controls are all integrated within a compact canopy, designed for easy transport, installation and service.

The Purelogic™ is the central brain of the nitrogen generator. It optimizes operating costs thanks to the availability of the energy saving control; ensures maximum reliability by keeping track of the most important parameters of the generator; and offers impressive control and monitoring capabilities.

The optional flow meter and inlet pressure dew point sensor can be added to the scope of supply to further exploit the monitoring capabilities of the Purelogic™ controller.

Technical specifications for PPNG 6-68 S

Specifications	Units	Variant	Product → Purity ↓	PPNG 6S	PPNG 7S	PPNG 9S	PPNG 12S	PPNG 15S	PPNG 18S	PPNG 22S	PPNG 28S	PPNG 30S	PPNG 37S	PPNG 41S	PPNG 50S	PPNG 63S	PPNG 68S
Nominal free nitrogen delivery ⁽¹⁾	m³/hr	PCT (%)	95	22.3	28.8	35.2	44.7	57.5	70.3	86.3	105.5	115.0	140.7	159.7	NA	NA	NA
			99.9	5.9	7.6	9.3	11.8	15.2	18.6	22.8	27.9	30.4	37.2	45.6	55.8	59.1	64.7
		PPM (%)	99.999	1.7	2.2	2.7	3.4	4.4	5.3	7.1	8.7	9.5	11.6	14.3	17.4	20.5	23.3
Nominal air consumption ⁽¹⁾	m³/hr	PCT (%)	95	43.1	55.5	67.9	86.3	111.0	135.8	166.5	203.7	222.0	271.5	308.3	NA	NA	NA
			99.9	23.9	30.8	37.7	47.9	61.6	75.3	92.4	113.0	123.2	150.7	182.5	223.3	226.8	258.6
		PPM (%)	99.999	11.5	14.8	18.1	22.9	29.5	36.1	47.4	58.0	63.2	77.3	93.4	114.2	122.4	152.3
Air Factor	-	PCT (%)	95	1.93	1.93	1.93	1.93	1.93	1.93	1.93	1.93	1.93	1.93	1.93	NA	NA	NA
			99.9	4.05	4.05	4.05	4.05	4.05	4.05	4.05	4.05	4.05	4.05	4.00	4.00	3.84	4.00
		PPM (%)	99.999	6.8	6.8	6.8	6.8	6.8	6.8	6.7	6.7	6.7	6.7	6.6	6.6	6.0	6.6
Pressure dewpoint outlet	°C / °F			-40	-40	-40	-40	-40	-40	-40	-40	-40	-40	-40	-40	-40	-40
Maximum pressure drop	barg	PCT (%)	95	0.8	0.8	0.8	1	1	1.1	1.2	1.2	1.2	1.2	1.4	NA	NA	NA
	barg		99.9	0.5	0.5	0.5	0.6	0.6	0.7	0.7	0.7	0.7	0.7	0.9	0.9	0.9	1
	barg	PCT (%)	99.999	0.3	0.3	0.4	0.4	0.4	0.4	0.4	0.5	0.6	0.6	0.6	0.7	0.7	0.7
Length	mm			798	798	798	798	798	798	1422	1422	1422	1422	1422	1422	1422	1422
	inch			31	31	31	31	31	31	56	56	56	56	56	56	56	56
Width	mm			840	840	840	840	840	840	840	840	840	840	970	970	970	970
	inch			33	33	33	33	33	33	33	33	33	33	38	38	38	38
Height	mm			2022	2022	2022	2022	2022	2022	2022	2022	2022	2022	2022	2022	2022	2022
	inch			80	80	80	80	80	80	80	80	80	80	80	80	80	80
Mass	kg			244	257	270	306	339	360	599	627	663	716	805	1018	1191	1191
	lbs			538	567	595	675	747	794	1321	1382	1462	1579	1775	2244	2626	2626
Inlet and outlet connections	G/NPT			1"	1"	1"	1"	1"	1"	1"	1"	1"	1"	1"	1"	1"	1"

1. Flow is measured at Reference Conditions: 1 bara and 20°C at operating pressure of 7 barg, inlet temperature 20°C & Air Inlet Quality of ISO 8573-1:2010 class 1-4-1

PPNG SKID - High-pressure nitrogen skid

Are you looking for a true plug-and-play solution that delivers on-site nitrogen at the lowest cost?

Pneumatech has developed compact and pre-commissioned skids in two pressure versions.

The 40 barg version offers high-pressure nitrogen for direct use; with the 300 barg version you can fill the skid-mounted cylinders to create your own supply. These bottles can serve as your nitrogen back-up supply, but also allow you to downsize your system in case of fluctuating demand. With its supreme efficiency and reliability, ease of use and small footprint, the high-pressure skid is the ideal solution for laser cutting applications.

Standard solution does not fit for your needs?

Do not worry. We at Pneumatech understand that every case is unique especially with high pressure Nitrogen applications. Therefore Pneumatech offers a tailor made solution just for your application.

Please consult with your local Pneumatech contact for more details.

PPNGs nitrogen generator

- ▶ Guaranteed purity
- ▶ Outstanding air factors
- ▶ Energy saving control
- ▶ Optimal control and monitoring thanks to Purelogic™ controller

4-stage filter train for guaranteed purity and reliability

- ▶ General-purpose and high-efficient oil-coalescing filters, activated carbon tower and high-efficient particle filter
- ▶ Guaranteed air quality of class 1:4:1 (according to ISO8573-1:2010) at the inlet of the nitrogen generator

Variable speed compressor with integrated refrigerant dryer

- ▶ Closely follow the air demand by automatic adjustment of the motor speed
- ▶ Direct driven transmission for outstanding energy efficiency and reliability
- ▶ Very quiet operation due to improved noise insulation
- ▶ Compact design, also thanks to integrated refrigerant dryer



Technical specifications for PPNG skid

Pneumatech variant		PPNG SKID 1	PPNG SKID 2	PPNG SKID 3	PPNG SKID 4	PPNG SKID 5	PPNG SKID 6	PPNG SKID 7	PPNG SKID 8
N ₂ Pressure		40 barg	40 barg	40 barg	40 barg	300 barg	300 barg	300 barg	300 barg
N ₂ Capacity ⁽¹⁾ (m ³ /hr)	99.90%	10.5	21	42	73.1	13.4	21	42	73.1
	99.99%	5.3	10.5	22.1	41.1	6.7	10.5	22.1	41.1
Compressor with Integrated Dryer		8kW	11kW	22kW	36kW	8kW	11kW	22kW	36kW
Filter train		G-C-VT-D	G-C-VT-D	G-C-VT-D	G-C-VT-D	G-C-VT-D	G-C-VT-D	G-C-VT-D	G-C-VT-D
Air receiver		500L 11Bar CE Vessel	500L 11Bar CE Vessel	1000L 11Bar CE Vessel	1500L 11Bar CE Vessel	500L 11Bar CE Vessel	500L 11Bar CE Vessel	1000L 11Bar CE Vessel	1500L 11Bar CE Vessel
N ₂ Generator		PPNG9S PPM IEC	PPNG18S PPM IEC	PPNG37S PPM IEC	PPNG68S PPM IEC	PPNG12S PPM IEC	PPNG18S PPM IEC	PPNG37S PPM IEC	PPNG68S PPM IEC
N ₂ Receiver		500L 11Bar CE Vessel	500L 11Bar CE Vessel	1000L 11Bar CE Vessel	1500L 11Bar CE Vessel	500L 11Bar CE Vessel	500L 11Bar CE Vessel	1000L 11Bar CE Vessel	1500L 11Bar CE Vessel
Particulate Filter		D	D	D	D	D	D	D	D
N ₂ Booster		15 hp 40 barg	15 hp 40 barg	15 hp 40 barg	15 hp 40 barg	10 hp 300 barg	10 hp 300 barg	15 hp 300 barg	2 x 15 hp 300 barg
HP Storage		500L/45 barg	500L/45 barg	1000L/45 barg	1000L/45 barg	2 cylinder 300 barg	12 cylinder rack 300 barg	12 cylinder rack 300 barg	16 cylinder rack 300 barg

1. Flow specified is at the outlet of the PPNGs Generator measured at Reference Conditions: 1 bara and 20°C at operating pressure of 7 barg, inlet temperature 20°C & Air Inlet Quality of ISO 8573-1:2010 class 1-4-1



Nitrogen storage: 40 barg receiver or 300 barg cylinders

- ▶ Bottle rack consisting of up to 16 high-pressure bottles
- ▶ Allows to shave peak demands

Nitrogen booster: 40 barg or 300 barg

- ▶ IE3-standard energy efficient motor
- ▶ Automatic condensate drain, reducing pressure losses by 80%
- ▶ Compressor block made of light alloys with high thermal efficiency, resulting in outstanding reliability
- ▶ Low noise levels thanks to sound insulated panels

PPNG 150 - 800 HE - Nitrogen generators with pressure swing adsorption technology

Features & Benefits

- ▶ Advanced energy saving control
 - Reduced air consumption at low nitrogen demand
 - Also compensates for altering ambient conditions and purity settings
 - No compressed air use when no nitrogen is consumed
- ▶ Outstanding air factors thanks to back-flow pressurization
- ▶ High-quality, high-efficient Carbon Molecular Sieves selected for the right application
- ▶ Guaranteed purity
 - Automatically regulates to the requested nitrogen pressure and purity
 - Zirconia sensors for reliable purity measurement
- ▶ Designed & tested for cyclic load
- ▶ Optimal control and monitoring thanks to Purelogic™ Controller
 - Self-protective monitoring of the feed air quality
 - Feed-air blow-off in case of contamination
 - Nitrogen flow, purity and pressure measured and controlled
 - Automatic start-up

General Specifications

- ▶ Nitrogen purity achievable: 95%-99.9% (PCT Variant) & 99.95%-99.999% (PPM variant)
- ▶ Inlet pressure range: 5-10 barg/72-150 psig
- ▶ Ambient temperature range: 5-50°C/41-122°F
- ▶ Required inlet air quality: 1-4-1 according to ISO 8573-1:2010
- ▶ Power supply: 230VAC/50-60Hz



Options



Wooden packaging



Outlet PDP sensor



The PPNG150-800 HE series is Pneumatech's premium on-site nitrogen solution for high flows, with best-in-class performance and the most complete scope of supply.

The generator has outstanding air factors at full load thanks to the use of highly efficient Carbon Molecular Sieves (CMS) and back-flow pressurization.

The air consumption is also optimized at reduced nitrogen flow or pressure demands, thanks to the advanced energy saving algorithm, which automatically adjusts the cycle times of the generator.

The control and monitoring capabilities of the PPNG150-800 HE are truly impressive. Purity is guaranteed at all times by opening the consumer valve only at the requested purity level and flushing nitrogen when purity is not reached. Feed air quality is controlled by monitoring temperature, pressure and PDP. The feed air is blown off in case of contamination. All risks of possible CMS damage are eliminated thanks to the automatic start-up feature.

Technical specifications for PPNG150 - 800 HE

Specifications	Units	Variant	Product Purity → ↓	PPNG 150 HE	PPNG 200 HE	PPNG 250 HE	PPNG 300 HE	PPNG 350 HE	PPNG 400 HE	PPNG 500 HE	PPNG 650 HE	PPNG 800 HE
Nominal free Nitrogen delivery ⁽¹⁾	m³/hr	PCT(%)	95%	469	604	734	865	1063	1244	1607	2038	2592
			99.9%	169	218	265	312	384	449	580	735	935
		PPM	99.999%	75	96	117	138	169	198	253	321	408
Nominal air consumption ⁽¹⁾	m³/hr	PCT(%)	95%	886	1142	1387	1635	2010	2351	3036	3852	4898
			99.9%	549	708	859	1013	1245	1456	1881	2386	3034
		PPM	99.999%	377	486	590	695	854	999	1303	1653	2102
Air factor		PCT(%)	95%	1.9	1.9	1.9	1.9	1.9	1.9	1.9	1.9	1.9
			99.9%	3.2	3.2	3.2	3.2	3.2	3.2	3.2	3.2	3.2
		PPM	99.999%	5.1	5.1	5.1	5.1	5.1	5.1	5.2	5.2	5.2
Pressure dewpoint outlet (°C)		°C/°F		-40	-40	-40	-40	-40	-40	-40	-40	-40
Maximum pressure drop (barg)		PCT(%)	95-99.9%	1,5 - 1	1,5 - 1	1,5 - 1	1,5 - 1	1,5 - 1	1,5 - 1	1,5 - 1	1,5 - 1	1,5 - 1
		PPM	99.95% - 99.999%	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5
Length	mm			1800	1800	1800	2300	2300	2300	3120	3120	3120
	inch			70.9	70.9	70.9	90.6	90.6	90.6	122.8	122.8	122.8
Width	mm			2230	2570	2650	2720	2850	2900	3660	3760	3860
	inch			87.8	101.2	104.3	107.1	112.2	114.2	144.1	148.0	152.0
Height	mm			2610	2640	2625	3020	3050	3040	3970	4175	4405
	inch			102.8	103.9	103.3	118.9	120.1	119.7	156.3	164.4	173.4
Mass	kg			3200	3800	4800	6400	7000	7700	10300	12000	14200
	lbs			7054.8	8377.6	10582.2	14109.6	15432.3	16975.6	22707.6	26455.4	31305.6
N ₂ & Air Receiver size	liters			3000	4000	5000	6000	8000	8000	12000	16000	20000
Nitrogen to buffer connection	DN			80	80	80	80	80	80	100	100	100
Nitrogen from buffer connection	DN	PCT(%)	95-99.9%	50	50	50	80	80	80	100	100	100
	DN	PPM	99.95% - 99.999%	40	40	40	40	40	40	50	50	50
Nitrogen outlet connection	DN	PCT(%)	95-99.9%	50	50	50	80	80	80	100	100	100
	DN	PPM	99.95% - 99.999%	50	50	50	50	50	50	50	50	50
Waste gas blow-off	mm			315	315	315	400	400	400	600	600	600

1. Flow is measured at Reference Conditions: 1 bara and 20°C at operating pressure of 7 barg, inlet temperature 20°C & Air Inlet Quality of ISO 8573-1:2010 class 1-4-1

PMNG 1-3 - Nitrogen generator with membrane technology

Features & Benefits

- ▶ High Quality membrane separator
 - Superior membrane constructed from high quality Aluminum with technically advance fiber.
 - N₂ Generation is achieved without any moving part
 - Outstanding performance for 90-99,5% Nitrogen separation
- ▶ Simple, reliable and user friendly
 - All-in-one plug & play solution
 - All filters integrated in enclosed canopy design
 - Instant supply of nitrogen
 - No specialist installation or commissioning
- ▶ 3-stage pre-filtration integrated in the canopy
- ▶ No power supply required thanks to Pneumatic controlled valves & battery-powered nitrogen analyzer
- ▶ Guaranteed purity
 - Nitrogen analyzer (battery powered) with auto-calibration button (optional)
 - Purity controller to ensure constant N₂ purity at all times
- ▶ Compressed Air savings when desired purity is reached
 - Economizer (pneumatic) automatically stops air consumption when target pressure is reached

General Specifications

- ▶ Membrane Nitrogen Generators
- ▶ Nitrogen purity achievable: 90%-99.5%
- ▶ Inlet pressure range: 4-13 bar/60-189 PSI
- ▶ Inlet temperature range: 5-50°C/41-122°C
- ▶ Required inlet air quality: 1-4-1 according to ISO 8573-1:2010



Options



Economizer



Nitrogen analyser
(battery powered)



Mobile
version

Pneumatech's new smaller range of PMNG nitrogen generators utilizes proprietary membrane separation technology. Membrane generators are an excellent choice in low (90%) to medium (99,5%) purity applications such as tire inflation, fire prevention, tank blanketing and pipeline drying. Nitrogen pressures can go up to 12 bar (g) without the need for an additional booster.

Engineered for simplicity, durability and ease of use make the PMNG what we believe to be the most user friendly unit in the market. All pre-filters and controls are included inside the canopy. Only a supply of dry compressed air is needed to get nitrogen at the outlet of the generator. Also the start-up procedure of the PMNG is made so straightforward that it does not require any specialist.

Pneumatech offers a purity controller that delivers true consistent purity downstream in ANY flow situation. Our simple design allows adjustments to be made easily, with a single screw. The purity is reliably monitored thanks to the optional battery operated Nitrogen Analyser. The optional Economiser system is designed to save the utility costs of operating the compressor and reduces the wear and tear on Air and Nitrogen Systems.

This cost effective solution from Pneumatech significantly reduces Nitrogen costs over traditional sources of Nitrogen supply.

Technical specifications for PMNG 1-3					
Specifications	Units	Product → Purity ↓	PMNG 1	PMNG 2	PMNG 3
Nominal air consumption	Nm³/hr	90%	15.48	30.96	46.44
		95%	9.72	19.44	29.16
		96%	9	18	27
		97%	7.56	15.12	22.68
		98%	6.84	13.68	16.92
		99%	6.12	12.24	18.36
		99.5%	5.76	11.52	17.28
Nominal free nitrogen delivery	Nm³/hr	90%	10.08	20.16	30.24
		95%	4.68	9.36	14.04
		96%	3.96	7.92	11.88
		97%	3.24	6.48	9.72
		98%	2.52	5.04	7.56
		99%	1.8	3.6	5.4
		99.5%	1.44	2.88	4.32
Air factor	-	90%	1.5	1.5	1.5
		95%	2.1	2.1	2.1
		96%	2.3	2.3	2.3
		97%	2.3	2.3	2.3
		98%	2.7	2.7	2.7
		99%	3.4	3.4	3.4
		99.5%	4.0	4.0	4.0
Pressure dewpoint outlet	°C /°F		-40	-40	-40
Length	mm		560.0	560.0	560.0
	inch		22.0	22.0	22.0
Width	mm		285.0	285.0	285.0
	inch		11.0	11.0	11.0
Height	mm		1150.0	1150.0	1150.0
	inch		45.0	45.0	45.0
Mass	kg		60.0	62.0	65.0
	lbs		132.3	136.7	143.3
Inlet connections	G		G1/2"	G1/2"	G1/2"
Outlet connections	G		G1/2"	G1/2"	G1/2"

1. Flow is measured at reference conditions: 1 Bar(a) and 20°C at operating pressure of 8 bar (g), inlet temperature 20°C & Air Inlet Quality of ISO 8573-1:2010 class 1-4-1.

PMNG 5 - 75 S - Nitrogen generator with membrane technology

Features & Benefits


- ▶ Energy-saving control
- ▶ Proprietary membrane technology ensuring lasting performance
 - No aging
 - No heater
- ▶ Guaranteed purity
 - Reliable purity measurement
 - Easy to set up the device for purity levels between 95% and 99.5%
- ▶ All-in-one plug & play solution
 - All filters integrated in enclosed canopy design
 - No buffer vessels required
 - Instant supply of nitrogen
 - No specialist installation or commissioning
- ▶ Optimal control and monitoring thanks to Purelogic™ Controller

General Specifications


- ▶ Membrane Nitrogen Generators
- ▶ Nitrogen purity achievable: 95%-99.5%
- ▶ Inlet pressure range:
4-13 barg/60-189 psig
- ▶ Inlet temperature range:
5-50°C/41-122°F
- ▶ Required inlet air quality:
1-4-1 according to ISO 8573-1:2010
- ▶ Power supply: 115-230VAC/50-60Hz



Options




Oil indicator




Flow sensor



PDP sensor kit



High ambient
temperature
software



Permeate vent kit

Pneumatech's PMNG nitrogen generators utilize proprietary membrane separation technology. Membrane generators are an excellent choice in low (95%) to medium (99,5%) purity applications such as tire inflation, fire prevention, tank blanketing and pipeline drying. Nitrogen pressures can go up to 12 barg without the need for an additional booster.

With the PMNG, on-site nitrogen supply becomes exceptionally convenient. All pre-filters and controls are included inside the canopy. Only a supply of dry compressed air and electricity is needed to get nitrogen at the outlet of the generator. An outlet buffer vessel is not required, which results in significant space

savings and easy installation. Also the start-up procedure of the PMNG is made so straightforward that it does not require any specialist.

Thanks to the Purelogic™ controller, the PMNG offers impressive control and monitoring capabilities. Various pressure and temperature sensors ensure that the membranes are used in the right working conditions. The nitrogen purity can easily be set with the purity regulator and is reliably monitored. The optional pressure dew point (PDP) sensor and oil indicator sensor safeguard air purity of class 1:4:1 according to ISO8573-1:2010 at the inlet of the membranes.

Technical specifications for PMNG 5 - 75 S

Specification	Unit	Product→ Purity↓	PMNG5 S	PMNG10 S	PMNG15 S	PMNG30 S	PMNG45 S	PMNG60 S	PMNG75 S
Nominal free nitrogen delivery ⁽¹⁾	m³/hr	95%	11.9	24.1	42.1	83.9	126.0	168.1	209.9
		96%	9.7	19.4	34.6	69.5	104.0	138.6	173.2
		97%	7.6	15.1	27.4	54.7	82.1	109.1	136.4
		98%	5.4	10.8	19.8	40.0	59.8	79.9	99.7
		99%	3.6	6.8	11.5	23.0	34.6	46.1	57.6
		99.5%	2.5	5.0	7.2	14.8	22.0	29.5	36.7
Nominal air consumption ⁽¹⁾	m³/hr	95%	31.0	62.3	109.1	218.5	327.6	436.7	546.1
		96%	29.2	58.0	104.0	208.1	311.8	415.8	519.8
		97%	26.6	52.9	95.4	191.2	286.6	382.3	477.7
		98%	23.4	47.2	85.7	171.7	257.4	343.1	428.8
		99%	22.0	43.6	72.7	145.4	218.2	291.2	364.0
		99.5%	21.6	42.8	62.6	124.9	187.6	249.8	312.5
Air factor		95%	2.6	2.6	2.6	2.6	2.6	2.6	2.6
		96%	3	3	3	3	3	3	3
		97%	3.5	3.5	3.5	3.5	3.5	3.5	3.5
		98%	4.3	4.3	4.3	4.3	4.3	4.3	4.3
		99%	6.3	6.3	6.3	6.3	6.3	6.3	6.3
		99.5%	8.5	8.5	8.5	8.5	8.5	8.5	8.5
Pressure dewpoint outlet	°C /°F		-40	-40	-40	-40	-40	-40	-40
Length	mm		820	820	820	820	820	820	820
	inch		32.3	32.3	32.3	32.3	32.3	32.3	32.3
Width	mm		772	772	772	1470	1470	1470	1470
	inch		30.4	30.4	30.4	57.9	57.9	57.9	57.9
Height	mm		2090	2090	2090	2090	2090	2090	2090
	inch		82.3	82.3	82.3	82.3	82.3	82.3	82.3
Mass	kg		259	268	285	445	497	535	571
	lbs		571	590	628	981	1096	1179	1259
Inlet connections	G/NPT		1/2"	1/2"	1/2"	1 1/2"	1 1/2"	1 1/2" - 1"	1 1/2" - 1"
Outlet connections	G/NPT		1/2"	1/2"	1/2"	1"	1"	1"	1"

1. Flow is measured at Reference Conditions: 1 bara and 20°C at operating pressure of 8 barg, inlet temperature 20°C & Air Inlet Quality of ISO 8573-1:2010 class 1-4-1

PPOG 1 - 120 - Oxygen generator with pressure swing adsorption technology

Features & Benefits

- ▶ Energy saving control
- ▶ High-quality, high-efficient zeolite, selected for the right application
- ▶ Guaranteed purity
 - Zirconia sensors for reliable purity measurement
- ▶ Designed & tested for cyclic load
- ▶ Optimal control and monitoring thanks to Purelogic™ Controller
- ▶ Available with IEC and CSA/UL approvals

General Specifications

- ▶ Pressure Swing Adsorption (PSA) Oxygen Generators - welded vessels
- ▶ Oxygen purity achievable: 90%-95%
- ▶ Inlet pressure range: 4-7.5 barg /58-109 psig
- ▶ Inlet temperature range: 5-45°C/41-113 psig
- ▶ Required inlet air quality: 1-4-1 according to ISO 8573-1:2010
- ▶ Power supply: 115-230VAC/50-60Hz



Options



Seaworthy packaging



PDP sensor kit



Oxygen buffer vessels



Pneumatech gives oxygen to your business. With the PPOG range, Pneumatech offers an attractive replacement for traditional oxygen supply with very interesting returns on investment. The PPOG1-120 series uses Pressure Swing Adsorption technology to extract oxygen from compressed air, resulting in oxygen purity levels up to 95%.

The PPOG1-120 range is a welded vessel design, designed and tested for cyclic load. The Purelogic™ is the central brain of the generator. It optimizes operating costs thanks to the availability of the energy saving control; ensures maximum reliability by

monitoring the most important parameters of the generator; and offers impressive control and monitoring capabilities.

The calibrated flow meters are part of the standard scope of supply, in order to facilitate the start-up process and to provide transparency of the actual oxygen consumption. The optional oxygen buffer vessel is equipped with a pressure regulator, manometer and dust filter. Each of these components is approved for high-purity oxygen use. The optional inlet pressure dew point sensor provides additional security in case the upstream dryer would fail.

Technical specifications for PPOG 1-120																						
Specifications	Units	Product → Purity ↓	PPOG 1	PPOG 1.5	PPOG 2	PPOG 3	PPOG 4	PPOG 5	PPOG 6	PPOG 8	PPOG 11	PPOG 12	PPOG 14	PPOG 17	PPOG 20	PPOG 26	PPOG 33	PPOG 39	PPOG 50	PPOG 63	PPOG 93	PPOG 120
Nominal free oxygen delivery ⁽¹⁾	m³/hr	90%	2.0	3.1	3.8	4.6	6.6	7.9	9.7	14.2	18.5	20.3	23.4	29.3	35.1	45.3	56.0	66.1	85.5	106.8	157.7	203.5
		93%	1.6	2.5	3.5	4.3	5.6	7.3	9.0	13.4	18.3	19.3	21.4	27.6	33.0	42.7	51.9	64.1	79.4	101.7	154.6	188.2
		95%	1.5	2.3	3.4	4.0	5.4	6.9	8.3	12.2	15.4	18.3	20.3	26.3	31.6	39.2	48.8	57.0	74.3	93.6	143.4	175.0
Nominal air consumption	m³/hr	90%	22.6	30.5	36.6	54.9	73.3	103.8	103.8	157.5	192.3	219.8	256.4	329.6	366.3	518.9	634.8	799.6	982.8	1245.3	1867.9	2246.3
		93%	22.0	29.9	36.0	53.7	67.1	100.7	102.6	146.5	189.2	213.6	244.2	319.9	355.3	512.8	604.3	781.3	964.5	1220.8	1953.3	2228.0
		95%	21.4	28.7	35.4	51.9	65.9	97.7	102.6	140.4	170.9	207.5	238.1	313.1	347.9	500.5	586.0	763.0	915.6	1159.8	1892.3	2197.5
Average air/oxygen ratio		90%	11.1	10.0	9.7	12.0	11.1	13.1	10.7	11.1	10.4	10.8	11.0	11.3	10.4	11.5	11.3	12.1	11.5	11.7	11.8	11.0
		93%	13.5	11.8	10.4	12.6	12.0	13.8	11.5	10.9	10.3	11.1	11.4	11.6	10.8	12.0	11.6	12.2	12.2	12.0	12.6	11.8
		95%	14.0	12.3	10.5	13.1	12.2	14.1	12.3	11.5	11.1	11.3	11.7	11.9	11.0	12.8	12.0	13.4	12.3	12.4	13.2	12.6
Pressure dewpoint outlet (°C)	°C/°F		-40	-40	-40	-40	-40	-40	-40	-40	-40	-40	-40	-40	-40	-40	-40	-40	-40	-40	-40	-40
Oxygen outlet quality			ISO8573-1:2010 Class 1-2-1																			
Length	mm		600.0	600.0	750.0	750.0	850.0	850.0	1120.0	1120.0	1190.0	1230.0	1230.0	1640.0	1765.0	1960.0	1960.0	1960.0	2470.0	2920.0	2470.0	2920.0
	inch		23.6	23.6	29.5	29.5	33.5	33.5	44.1	44.1	46.9	48.4	48.4	64.6	69.5	77.2	77.2	77.2	97.2	115.0	97.2	115.0
Width	mm		757.0	757.0	770.0	770.0	848.0	848.0	875.0	875.0	924.0	943.0	947.0	1108.0	1135.0	1175.0	1175.0	1175.0	1305.0	1440.0	2610.0	2880.0
	inch		29.8	29.8	30.3	30.3	33.4	33.4	34.4	34.4	36.4	37.1	37.3	43.6	44.7	46.3	46.3	46.3	51.4	56.7	102.8	113.4
Height	mm		1467.0	1489.0	1801.0	1801.0	1630.0	1630.0	1962.0	1962.0	2252.0	2278.0	2678.0	2450.0	2492.0	3094.0	3094.0	3592.0	3097.0	3280.0	3097.0	3280.0
	inch		57.8	58.6	70.9	70.9	64.2	64.2	77.2	77.2	88.7	89.7	105.4	96.5	98.1	121.8	121.8	141.4	121.9	129.1	121.9	129.1
Mass	kg		193.8	226.8	324.8	330.6	412.6	412.6	723.0	735.0	1009.3	1192.3	1321.2	2359.3	2632.7	3150.0	3150.0	3681.0	4908.0	6489.0	9746.0	12470.0
	lbs		427.3	500.0	716.1	728.9	909.6	909.6	1593.9	1620.3	2225.1	2628.5	2912.7	5201.4	5804.1	6944.6	6944.6	8115.2	10820.3	14305.8	21486.2	27491.6
Inlet connections	G/ NPT		G1/2"	G1/2"	G1/2"	G1/2"	G1/2"	G1/2"	G 3/4"	G 3/4"	G1"	G1"	G1"	G1 1/2"	G1 1/2"	DN50	DN50	DN50	DN50	DN50	2xDN50	2xDN50
Outlet connections	G/ NPT		G3/8"	G3/8"	G3/8"	G3/8"	G3/8"	G3/8"	G1/2"	G1/2"	G1/2"	G1/2"	G1/2"	G 3/4"	G 3/4"	G 3/4"	G 3/4"	G 3/4"	G 3/4"	G 3/4"	2xG3/4"	2xG3/4"

1. Flow is measured at Reference Conditions: 1 bara and 20°C at operating pressure of compressed air of 6 barg and oxygen pressure at the outlet 4.5 barg, inlet temperature 20°C & Air Inlet Quality of ISO 8573-1:2010 class 1-4-1

Oxygen solutions

Pneumatech offers packaged solutions for on-site oxygen generation, which guarantee peace-of-mind and quick returns compared to traditional oxygen supply.

A typical lineup consists of a compressor, a refrigerant dryer, filters, buffer vessels and a PPOG oxygen generator; and can be completed with a high-pressure oxygen booster and a bottle filling station. These can be containerized or skid-mounted, depending on the application and the needs.



**DO YOU
KNOW THAT?**

Our boosters are available in 3 kW to 15 kW models and can safely and reliably boost oxygen, nitrogen, helium or argon up to 200 barg / 2900 psig. By boosting a gas to these high pressures, you can bottle the gas you generate. This is particularly interesting to cover peak demand or as emergency back-up.



Pneumatech's on-site oxygen systems generate oxygen from 90% up to 95% purity, and are thus compliant with European pharmacopeia and United States Pharmacopeia (USP). Our production locations are moreover certified according to ISO 13485, the international quality management system for medical devices.

Clean air to protect your workers

Many of us would directly relate breathing air to the air that we breathe from the atmosphere. Compressed air for breathing shall not contain contaminants at a concentration which can cause toxic or harmful effect. There are so many industrial applications that need breathing air which are often not considered.

The air protects the workers engaged in tasks like

- Asbestos removal
- Tank cleaning
- Sand blasting
- Laboratory work
- Spray painting
- Pharmaceutical manufacturing



Breathing Air Solutions

Pneumatech's industrial breathing air purifiers offers guaranteed protection against contaminants-complying with International breathing air standards with a small foot print for flexible installations.

BA 25 - 300 - HE Breathing Air Purifiers

Features & Benefits

- ▶ The Pneumatech solution for Industrial Breathing Air applications, build to exceed standards
- ▶ Compliance with stringent international standards
- ▶ Special 7-stage filtration process offered unparalleled compressed air purity
 - Water Separator - For liquid water
 - Fine Filter - For Oil and Water aerosols
 - Super Fine Filter - For Oil and Water aerosols
 - Adsorption Dryer - For Water vapour and CO₂
 - Activated Carbon - For Gaseous impurities
 - Catalyst - For CO oxidation to CO₂
 - Bacteria Filter - For Bacteria & dust particles
- ▶ Advanced energy management for lowest operating costs
 - Compressor synchronization
 - Purge nozzle optimization
 - PDP control - Dew Point switching
- ▶ Advanced gas sensors
 - Direct reading from the controller screen
 - Voltage free contacts for easy integration
 - Adjustable level of warnings
- ▶ Best in class performance thanks to unique and patented purge nozzle design:
 - Purging rate adjusted as per the customer requirements instead of having multiple sets of the nozzles
- ▶ Low noise levels
- ▶ High quality filters
 - Guaranteed air purity thanks to High-efficient glass fibre media.
 - Significant energy savings with lower pressure drops
- ▶ More compact and easy to use -
 - Smaller footprint than previous designs - 35% smaller
 - Pre-assembled and ready for use eliminating complex installation needs

General Specifications

- ▶ Breathing Air Purifiers for Industrial applications.
- ▶ Dew points achievable: -40°C/-40°F
- ▶ Inlet pressure range: 4-13 barg/58-189 psig
- ▶ Ambient temperature range: 5-40°C/41-104°F
- ▶ Inlet temperature range: 5-50°C/41-122°F
- ▶ Power supply: 230 VAC 50 Hz/115 VAC 50Hz
- ▶ Maximum concentration of O₂ - 21,4%
- ▶ Reduced concentration of CO₂ below 500 PPM
- ▶ Reduced concentration of SO₂ / NO_x below 2 PPM



Options



Electronic drains



VT saturation indicator (Oil indicator)



O₂, CO & CO₂ sensors



NPT connections



Optimised purge nozzle



The compressed air quality is of vital importance in many applications even more so in breathing air applications. The applications, such as short-blasting, tank cleaning, tunneling, spray painting and many more require breathing air that is free from contaminants that may be present in the compressed air fed breathing air systems. These contaminants are present in the feed air in the form of fumes, oil, vapors, gases, solid particles and microorganisms.

Pneumatech's breathing air purifiers offers guaranteed protection against such contaminants complying with International breathing Air standards. The BA HE range assures safe working environment in a wide range of applications. Built to exceed standards, BA HE purifiers provide certified breathing air, even in situations with polluted intake air to ensure personnel safety at all times. The seven-filtration stages of the BA HE have been

carefully designed to make sure the air quality at the outlet complies with stringent international standards.

New and unique design for the adsorption dryer offers significant advantage. The purge valve design (patent awaited) offers optimum purge performance. The renovated design drastically lowers the purge air consumption saving value for the customer from the compressed air lost. The gas sensors are available as an option to optimize the system further. The possibility to connect the signals to the PureLogic Controller offers optimal control and monitoring.

With approximately 35% reduction in size, new BA HE version offers significant space saving advantage allowing for more flexible installations

Technical Specifications BA 25 - 300 HE

Specifications ↓	Units	BA25 HE	BA35 HE	BA45 HE	BA75 HE	BA90 HE	BA110 HE	BA150 HE	BA220 HE	BA300 HE
Flow ⁽¹⁾	l/s	12	17	21	35	42	52	71	104	142
	m³/hr	43.2	61.2	75.6	126	151.2	187.2	255.6	374.4	511.2
	cfm	25.4	36.0	44.5	74.2	89.0	110.2	150.4	220.4	300.9
Installed power	(kW)	0.24	0.24	0.24	0.24	0.24	0.24	0.24	0.24	0.24
	hp	0.32	0.32	0.32	0.32	0.32	0.32	0.32	0.32	0.32
Pressure drop over dryer	bar	0.9	1.4	1.1	1	0.9	0.9	0.9	1	1.4
	psi	13.1	20.3	16.0	14.5	13.1	13.1	13.1	14.5	20.3
Purge flow	(%)	18	18	18	18	18	18	18	18	18
Height	mm	1580	1598	1681	1678	1678	1678	1735	1776	1778
	inch	62.2	62.9	66.2	66.1	66.1	66.1	68.3	69.9	70.0
Width	mm	800	800	800	800	800	800	800	800	800
	inch	31.5	31.5	31.5	31.5	31.5	31.5	31.5	31.5	31.5
Length	mm	700	700	700	700	700	700	700	900	900
	inch	27.6	27.6	27.6	27.6	27.6	27.6	27.6	35.4	35.4
Connection inlet/outlet	inch	1/2"	1/2"	1/2"	1"	1"	1 1/2"	1 1/2"	1 1/2"	1 1/2"
Net mass	kg	106	116	131	137	159	213	213	290	338
	lbs	234	256	289	302	351	470	470	639	745

1. Flow is measured at reference conditions: 1 bara and 20°C at operating pressure of 7 barg, inlet temperature 35°C & std PDP of -40°C at the outlet.

BA 25-300 - S Breathing air purifiers

Features & Benefits

- ▶ The Pneumatech solution for Industrial Breathing Air applications, build to exceed standards.
- ▶ Compliance with stringent international standards
- ▶ Special 7-stage filtration process offered unparalleled compressed air purity
 - Water separator - For liquid water
 - Fine filter - For oil and water aerosols
 - Super fine filter - For oil and water aerosols
 - Adsorption dryer - For water vapour and CO₂
 - Activated carbon - For gaseous impurities
 - Catalyst - For CO oxidation to CO₂
 - Bacteria filter - For bacteria & dust particles
- ▶ Best-in-class performance thanks to unique purge valve design (patent pending)
 - Lowest pressure drop during drying
 - Lowest purge loss by ensuring maximum purge air expansion during regeneration
- ▶ Low noise levels
- ▶ High quality filters
 - Guaranteed air purity thanks to High-efficient glass fiber media
 - Significant energy savings with lower pressure drops
- ▶ Compact and easy to connect design

General Specifications

- ▶ Breathing air purifiers for industrial applications.
- ▶ Dew points achievable: -40°C/-40°F
- ▶ Inlet pressure range: 4-13 barg/58-189 psig
- ▶ Ambient temperature range: 5-40°C/41-104°F
- ▶ Inlet temperature range: 5-50°C/41-122°F
- ▶ Power supply: 230 VAC 50 Hz/115 VAC 50Hz
- ▶ Maximum concentration of O₂ - 21,4%
- ▶ Reduced concentration of CO₂ below 500 PPM
- ▶ Reduced concentration of SO₂ /NO_x below 2 PPM



Options



Electronic drains



VT saturation indicator (Oil indicator)



Gas sensors (As sales options)



NPT connections

The compressed air quality is of vital importance in many applications even more so in breathing air applications. The applications such as short-blasting, tank cleaning, tunneling, spray painting and many more require breathing air that is free from contaminants that may be present in the compressed air fed breathing air systems. These contaminants are present in the feed air in the form of fumes, oil, vapors, gases, solid particles and microorganisms.

Pneumatech's breathing air purifiers offers guaranteed protection against such contaminants complying with International breathing Air standards. The BA HE range assures safe working environment in a wide range of applications. Built to exceed standards, BA HE purifiers provide certified breathing air, even in situations with polluted intake air to ensure personnel safety at all times. The seven-filtration stages of the BA HE have been

carefully designed to make sure the air quality at the outlet complies with stringent international standards.

New and unique design for the adsorption dryer offers significant advantage. The purge valve design (patent awaited) offers optimum purge performance. The renovated design drastically lowers the purge air consumption saving value for the customer from the compressed air lost. The gas sensors are available as an option to optimize the system further. The possibility to connect the signals to the PureLogic Controller offers optimal control and monitoring.

With approximately 35% reduction in size, new BA S version offers significant space saving advantage allowing for more flexible installations

Technical Specifications for BA 25 S up to BA 300 S

Specifications ↓	Units	BA25 S	BA35 S	BA45 S	BA75 S	BA90 S	BA110 S	BA150 S	BA220 S	BA300 S
Flow ⁽¹⁾	l/s	12	17	21	35	42	52	71	104	142
	m³/hr	43.2	61.2	75.6	126	151.2	187.2	255.6	374.4	511.2
	cfm	25.4	36.0	44.5	74.2	89.0	110.2	150.4	220.4	300.9
Installed power	(kW)	0.24	0.24	0.24	0.24	0.24	0.24	0.24	0.24	0.24
	hp	0.32	0.32	0.32	0.32	0.32	0.32	0.32	0.32	0.32
Pressure drop over dryer	bar	0.65	0.93	0.72	0.71	0.64	0.74	0.75	0.91	1.48
	psi	9.4	13.4	10.5	10.3	9.3	10.7	10.9	13.3	21.4
Purge flow	%	18	18	18	18	18	18	18	18	18
Height	mm	1247	1642	1212	1467	1592	1522	1715	1824	1848
	inch	49.1	64.6	47.7	57.8	62.7	59.9	67.5	71.8	72.8
Width	mm	550	550	800	800	800	800	800	800	800
	inch	21.7	21.7	31.5	31.5	31.5	31.5	31.5	31.5	31.5
Length	mm	450	450	700	700	700	700	700	900	900
	inch	17.7	17.7	27.6	27.6	27.6	27.6	27.6	35.4	35.4
Inlet and Outlet Connections	inch	1/2"	1/2"	1/2"	1"	1"	1 1/2"	1 1/2"	1 1/2"	1 1/2"
Net mass	kg	77	87	102	108	130	184	184	261	309
	lbs	170	192	225	238	287	406	406	575	681

1. Flow is measured at reference conditions: 1 bara and 20°C at operating pressure of 7 barg, inlet temperature 35°C & std PDP of -40°C at the outlet.

Certified performance

Pneumatech filters have been fully tested and qualified according to the latest ISO standards. Tests have been conducted in-house as well as in external labs, and are independently validated by TÜV. The following table shows some of our available ISO certificates.

The ISO 8573 standards deal with the measurement of compressed air purity, while the ISO 12500 series validate the test methods for compressed air equipment.

ISO standard	Test method for	Available for
ISO 8573-2:2018	Oil aerosol content	G/C
ISO 12500-1:2007	Oil aerosol filters	
ISO 8573-5:2001	Oil vapor content	VT
ISO 12500-2:2007	Oil vapor filters	
ISO 8573-4:2019	Solid particle content	S/D G/C
ISO 12500-3:2009	Solid particle filters	



Filter Solutions

Pneumatech offers you a comprehensive line-up of innovative filter solutions to meet your specific needs. Our filtration solutions are engineered cost-effectively to provide the best air quality and meet today's increasing quality demands.

For general applications we provide oil coalescing, particulate and oil vapor filters in a wide range of flows and pressures. Pneumatech is also your partner for breathing air, silicone-free, sterile & process filtration.

Ultimate water separators

Features & Benefits

- ▶ Energy saving
 - Reducing both energy consumption and operating costs
- ▶ Flexible Installation
 - Modular design and accessible fixings enable simple close coupling assembly
- ▶ Cost effective
 - No replacement components required
- ▶ Product safety in mind
 - Guaranteed safe housing closure with rotational safety stop
- ▶ Corrosion protection
 - Internal and external electrophoretic painting followed by a tough polyester powder coating

General Specifications

- ▶ 13 sizes from 10-2550 m³/h
- ▶ Proven centrifugal technology
- ▶ Unique module with unique vanes to eliminate points of low efficiency
- ▶ Eliminates 99% bulk water, even at low velocities
- ▶ Minimal operating pressure loss (50-60 mbar)
- ▶ No replacement components necessary
- ▶ External accessible drain valve
- ▶ Same installation accessories as the filter series
- ▶ Electronic drain available as an option



Options



Electronic drain





Wall brackets

Integrating into Pneumatech's compressed air filtration range, the new Ultimate Water Separator combines proven centrifugal technology with a new forward thinking housing design to deliver market leading water removal efficiencies – eliminating 99% bulk water with continuously low differential pressure.

The custom engineered centrifugal module features unique vanes to eliminate points of low efficiency, and a vortex arrestor to stop re-entrainment – ensuring minimal operating pressure loss and maintaining excellent liquid removal, even at low velocity. Remove 99% of bulk water when tested in accordance with ISO 12500-4

Tested performance



With exceptional performance at any flow rate, the new Ultimate water separator is perfect for use with variable speed compressors.

Filter Model	Pipe Size	Flow Rate		Dimension (mm)				Weight (kg) Approx.	Element Model
	G/NPT	Nm³/h	SCFM	A	B	C	D		
PMH WS 10	1/8"	10	6	50	17	157	60	0.25	-
PMH WS 25	1/4"	25	15	50	17	157	60	0.25	-
PMH WS 42	1/4"	42	25	70	24	231	70	0.6	-
PMH WS 59	3/8"	59	35	70	24	231	70	0.6	-
PMH WS 85	1/2"	85	50	70	24	231	70	0.6	-
PMH WS 119	1/2"	119	70	127	32	285	80	1.7	-
PMH WS 212	3/4"	212	125	127	32	285	80	1.7	-
PMH WS 297	1"	297	175	127	32	285	80	1.7	-
PMH WS 476	1 1/4"	476	280	140	40	475	80	3	-
PMH WS 545	1 1/2"	545	321	140	40	475	80	3	-
PMH WS 1189	2"	1189	700	170	53	508	100	4.9	-
PMH WS 1444	2 1/2"	1444	850	220	70	413	100	8	-
PMH WS 2550	3"	2550	1500	220	70	413	100	8	-

Ultimate filters - Threaded filters

Features & Benefits

- ▶ Flow-optimised design
- ▶ Improved air flow characteristics
- ▶ Reduced energy consumption
- ▶ Reduced costs of owner ship
- ▶ 6 filtration grades
- ▶ Increased performance
 - Significantly reduced differential pressure <125 mbar
 - Exceptional oil aerosol and particulate removal
- ▶ New filtration technology
 - NEW deep pleated media
 - NEW housing design for flexible installation and simplified serviceability
 - NEW externally accessible drain
- ▶ Tested and validated in accordance with ISO 12500-1 & ISO 8573-1:2010
- ▶ Dead stop head to bowl connection with lock indication for safety closure
- ▶ Corrosion protected housings: internal and external electrophoretic paint finish followed by a tough polyester powder coating
- ▶ Unique, specially designed adapter for removal of the automatic and manual drains from the bowl without a need to open the filter (for sizes 119-2550 m³/h)
- ▶ Multiple options
 - Differential pressure gauge with/without potential free contact
 - Manual drain
 - Automatic drain
 - Electronic drain
 - Wall brackets
 - Connection kits
- ▶ Two ranges available:
 - HE version with differential pressure gauge
 - S version without differential pressure gauge

General Specifications

- ▶ Significantly reduced differential pressure <125 mbar
- ▶ Maximum working pressure: 16 bar(g)/232 psi(g)
- ▶ With manual drain: up to 20.7 bar(g)/300 psi(g)
- ▶ Available from 1/8" to 3"
- ▶ Flow rates from 10-2550 Nm³/h (6-1500 scfm)



HE filter



S filter

Options



Connection kits



Automatic drain



Wall brackets



Manual drain
with adapter



Electronic drain



Differential pressure
gauge including
potential free contact



With energy efficiency and low total cost of ownership the Pneumatech Ultimate Filter surpasses conventional filters in the market place, providing to be the most advanced filter yet.

with the new element design, significantly improves air flow and performance, making the Ultimate filter one of the most energy efficient filter housings available.

The expertly engineered Ultimate Series not only achieves the highest air purity standards in line with ISO 8573-1:2010, it also incorporates the latest in filtration technology. The new filter housing reduces differential pressure loss which, when combined

With a range that incorporates coalescence filters, dust filters, activated carbon filters and water separators, available in a wide range of port sizes suitable for installation worldwide.

Filter Model	Pipe Size	Flow Rate		Dimension (mm)				Weight (kg) Approx.	Element Model
	G/ NPT	Nm ³ /h	SCFM	A	B	C	D		
PMH (grade) 10	1/8"	10	6	50	17	157	60	0.25	F(grade)-1
PMH (grade) 25	1/4"	25	15	50	17	157	60	0.25	F(grade)-2
PMH (grade) 42	1/4"	42	25	70	24	231	70	0.6	F(grade)-3
PMH (grade) 54	3/8"	54	32	70	24	231	70	0.6	F(grade)-4
PMH (grade) 85	1/2"	85	50	70	24	231	70	0.6	F(grade)-5
PMH (grade) 119	1/2"	119	70	127	32	285	80	1.7	F(grade)-6
PMH (grade) 144	3/4"	144	85	127	32	285	80	1.7	F(grade)-7
PMH (grade) 178	1"	178	105	127	32	285	80	1.7	F(grade)-8
PMH (grade) 212	3/4"	212	125	127	32	371	80	2	F(grade)-9
PMH (grade) 297	1"	297	175	127	32	371	80	2	F(grade)-10
PMH (grade) 476	1 1/4"	476	280	140	40	475	80	3	F(grade)-11
PMH (grade) 545	1 1/2"	545	321	140	40	475	80	3	F(grade)-12
PMH (grade) 765	2"	765	450	170	53	508	100	4.9	F(grade)-13
PMH (grade) 1189	2"	1189	700	170	53	708	100	5.5	F(grade)-14
PMH (grade) 1444	2 1/2"	1444	850	220	70	736	100	10.5	F(grade)-15
PMH (grade) 1529	3"	1529	900	220	70	736	100	10.5	F(grade)-16
PMH (grade) 2125	3"	2125	1250	220	70	857	100	11.5	F(grade)-17
PMH (grade) 2550	3"	2550	1500	220	70	1005	100	12.5	F(grade)-18



Grade	P	G	S	C	D	V
Particle removal (micron) ■	5	-	1	-	0.01	-
Outlet oil aerosol concentration (mg/m ³) ■	1	0.3	-	0.01	-	0.003
Total mass efficiency (%)	>90	>99.25	-	>99.9	-	-
Quality class of air at outlet (particles / oil) ▲	4 / 3	- / 3	3 / -	- / 2	1 / -	- / 1
Initial pressure drop over filter in dry applications (bar)	0.05	0.055	0.055	0.085	0.085	0.115
Initial pressure drop over filter in wet applications (bar) ★	0.08	0.125	-	0.125	-	-

Pressure correction factors										
For maximum flow rate, multiply model flow rate by the correction factor corresponding to the minimum operating pressure										
Operating pressure barg (psig)	4 (58)	5 (72)	6 (87)	7 (100)	8 (115)	10 (145)	12 (174)	14 (203)	16 (232)	20 (290)
7 barg – correction factor	0.76	0.84	0.92	1.00	1.07	1.19	1.31	1.41	1.51	1.6

Ultimate filters - Elements

Features & Benefits

- ▶ Push fit Pneumatech filtration
- ▶ High quality stainless steel cylinders
- ▶ Custom engineered
- ▶ Custom outer drainage layer
- ▶ Unique element end cap
- ▶ Piracy protection (from size 3)
- ▶ Color coding system for optimum identification

General Specifications

- ▶ 6 filtration grades: coalescence, dust & oil vapor filtration



Market-leading filtration performance

To ensure optimal performance and low cost, filter elements should be replaced with original parts every 12 months/8000 hours (whichever comes first). Activated carbon filter elements should be replaced every 6 months/1000 hours (whichever comes first).

Pneumatech utilizes deep pleated media to deliver market leading filtration performance. The new forward thinking design delivers exceptional results in both oil aerosol removal and particulate retention; significantly reducing differential pressure and energy consumption for low operational lifetime costs. Engineered to

deliver a step change in performance, the new ultimate element optimizes filtration efficiencies and produces compressed air in line with the highest standards of air purity, meeting the quality classes specified in ISO 8573-1: 2010.

Performance assured

Filter housing design

The ISO 8573 group of international standards is used for the classification of compressed air

- ▶ 1000 hour neutral salt spray test for corrosion to ISO 9227:2006
- ▶ Burst pressure tested in excess of 100 barg for a 5:1 safety factor
- ▶ Housings are pressure decay tested before despatch. Fine filters are 100% aerosol integrity tested

Element technology

The new series is available in a complete range of contamination removal grades designed to meet the compressed air purity requirements throughout industry


- ▶ ISO 8573-1:2010 compressed air purity standard
- ▶ ISO 12500 series international standard for compressed air filter testing

Independent validation

Housing are approved to international standards including:

- ▶ Pressure equipment directive 2014/68/EU - Lloyd's register EMEA - notified body no. 0038
- ▶ ISO 9001 quality systems - LRQ0930553 - Lloyd's register EMEA - notified body no. 0038
- ▶ CRN approved - CRNOE19418 - for use within Canada

Typical installation



A. General purpose protection
air purity to ISO 8573-1:2010
G filter [3 : - : 3]
P filter [4 : - : 3]

B. General purpose protection
and reduced oil concentration
air purity to ISO 8573-1:2010
[1 : - : 2]

C. High quality air
with reduced dew point
air purity to ISO 8573-1:2010
[1 : 4 : 2]

D. High quality air with reduced
dew point and oil concentration
air purity to ISO 8573-1:2010
[1 : 4 : 1]

E. High quality air with extremely
low dew point
air purity to ISO 8573-1:2010
[2 : 2 : 1]

F. High quality air with extremely
low dew point
air purity to ISO 8573-1:2010
[1 : 2 : 1]

Ultimate filters - Industries

In any compressed air system, impurities are inevitable. Dust, dirt, water and oil contaminants can reduce air quality and significantly affect system efficiency. However, inadequate or incorrect filtration can negatively impact performance and end user equipment, and cause potential costly system downtime. With over 30 years of experience, Pneumatech has the know-how to support the individual demands of our customers.

Laser cutting



Packaging and bottling



Optical industry



Automotive



Energy



Electronic component manufacturing



Glass/crystal



Gas generation



Nuclear plants



FF 1 - 12 - Flanged filters

Features & Benefits

- ▶ Guaranteed air purity
 - High-efficient glass fiber and foam media
- ▶ No risks of:
 - Cracked filter media
 - Cylinder implosion
 - Top cap leakages
 - Oil re-entrainment
- ▶ Significant energy savings
 - Optimal filter media selection allows low pressure losses
 - Zero-loss electronic drain included as standard
- ▶ Highest quality standards
 - In-house research, development & production
 - Each filter subjected to rigorous quality control
 - Fully tested and qualified according to ISO standards
- ▶ Robust design
 - Stainless steel cores guarantee ultimate strength
 - Protection paper to avoid damaging of glass fiber media
 - Special coating ensures high corrosion protection, and therefore a housing lifetime of at least 20 years
- ▶ Easy service and installation
 - Bottom cover with special rotating system
 - Different grade, different colour
 - Differential pressure gauge, with voltage free contact


General Specifications

- ▶ Compressed air inlet pressure:
1-16 barg/15-232 psig
- ▶ Max. ambient air temperature:
66°C/151 °F (35°C/95 °F for V grade)
- ▶ Available grades:
 - P: pre-filter
 - G: fine filter
 - C: super fine filter
 - V: activated carbon filter for oil vapor
 - S: dust filter
 - D: dust filter- high efficient



Zooming in

Special rotating system of bottom cover



Pneumatech's flanged filter range contains the same type of robust, high-efficient filter cartridges as the threaded range. The cartridges are contained in a welded steel housing which is pressure-rated up to 16 barg / 232 psig and provided with flanged connections at the compressed air inlet and outlet. The filter housings are completely cleaned, zinc phosphate and KTL

coated at the inside and outside and externally painted afterwards. This guarantees a housing lifetime of at least 20 years.

All flanged filters are standard equipped with a zero-loss electronic drain and differential pressure gauge with voltage-free contact connections. The special rotating system of the bottom cover makes filter cartridge replacement very straightforward.

Technical specifications for flanged filters FF 1-12

Pneumatech Variant Specifications	Units	FF 1	FF 2	FF 3	FF 4	FF 5	FF 6	FF 7	FF 8	FF 9	FF 10	FF 11	FF12
Nominal (max.) Flow Rate ⁽¹⁾	l/s	"550 (630)"	"850 (970)"	1100 (1260)	1400 (1600)	1800 (2200)	2200 (2400)	3000 (3600)	4000	5000	6000	7000	8000
	m³/hr	1980 (2268)	3060 (3492)	3960 (4536)	5040 (5760)	6480 (7920)	7920 (8640)	10800 (12960)	14400	18000	21600	25200	28800
	cfm	1165 (1335)	1801 (2055)	2331 (2670)	2966 (3390)	3814 (4662)	4662 (5085)	6357 (7628)	8476	10594	12713	14832	16951
Max Pressure	barg	16	16	16	16	16	16	16	16	16	16	16	16
	psig	232	232	232	232	232	232	232	232	232	232	232	232
Connection	DN	DN80	DN100	DN100	DN150	DN150	DN150	DN200	DN200	DN250	DN250	DN300	DN300
Dimensions (A)	mm	370	510	510	620	640	640	820	820	820	920	920	1040
	inch	14.6	20.1	20.1	24.4	25.2	25.2	32.3	32.3	32.3	36.2	36.2	40.9
Dimensions (B)	mm	190	230	230	290	285	285	400	400	400	550	550	525
	inch	7.5	9.1	9.1	11.4	11.2	11.2	15.7	15.7	15.7	21.7	21.7	20.7
Dimensions (C)	mm	1295	1360	1360	1480	1555	1555	1745	1745	1745	2085	2085	2070
	inch	51.0	53.5	53.5	58.3	61.2	61.2	68.7	68.7	68.7	82.1	82.1	81.5
Weight	kg	76	141	143	210	176	178	420	428	432	594	597	1140
	lbs	167.6	310.9	415.3	463	388	392.4	925.9	943.6	952.4	1034	1479.3	1984.2
Number of filter elements		1	3	4	5	6	7	10	14	16	20	24	28
Filter element size		1F (grade)	2F (grade)	2F (grade)	2F (grade)	2F (grade)	2F (grade)	2F (grade)	2F (grade)	2F (grade)	2F (grade)	2F (grade)	2F (grade)
Order example:		FF 1 C HE (superfine filter with differential pressure gauge)											

1. Flow is measured at reference conditions: 1 bara and 20°C at operating pressure of 7 barg, inlet temperature 10°C & std PDP of 3°C at the inlet.

Filter elements performance

	P	G	C	V	S	D
Grades → Performance ↓	Pre-filter	Fine filter - Oil aerosols/ solid particles	Super fine filter - Oil aerosols/ solid particles	Activated Carbon - Oil vapor	Dust filter	High efficiency dust filter
Particle removal efficiency at nominal flow (% at MPPS)	92.03%	99.92%	99.98%	n/a	99.92%	99.98%
Oil carry-over at nominal flow (mg/m³)	<1*	<0,07*	<0,008*	<0,003	n/a	n/a

* Oil aerosol content

Correction factors

Inlet pressure (barg)	1	2	3	4	5	6	7	8	10	12	14	16
Inlet pressure (psig)	15	29	44	58	72.5	87	102	116	145	174	203	232
Correction factor	0.38	0.53	0.65	0.75	0.83	0.92	1	1.06	1.2	1.31	1.41	1.5



VT - Activated carbon towers + vessels

Features & Benefits

- ▶ Guaranteed air purity with residual oil content below 0,003 mg/m³
 - Superb 2-layer activated carbon material
 - Designed with sufficient safety margin
 - Performance certified by external body
- ▶ Significant energy savings & limited system operating costs
 - Optimal internal flow path
 - Average pressure drop of 125 mbar only
- ▶ Certified class 1 performance, according to ISO 8573-1:2010
 - If combined with Pneumatech oil coalescing filters (G & C)
- ▶ Compact and reliable product design
 - Wall-mounting kit, optional for VT1 - 7
 - Easy to lift, install and service
- ▶ The VT is capable of removing hydrocarbons, odors and oil vapors from compressed air

General Specifications

- ▶ Compressed air inlet pressure:
 - VT 1-9: 1-16 barg/15-232 psig (extruded Versions)
 - VT with optional oil indicator: 1-8,8 barg/15-127 psig
 - VT 11-15: 1-14,5 barg/15-210 psig (Welded Versions)
 - VT11-15: life time 12000 hours
- ▶ Ambient air temperature: (Extruded Versions)
 - -10 - 50°C/14 - 122°F
- ▶ Ambient air temperature: (Welded Versions)
 - -10 - 80°C/14 - 176°F
- ▶ Compressed air inlet temperature:
 - 1 - 66°C/34 - 151°F



VT 1-9



VT 11-15

Options




Wall mounting kit



Oil indicator



Oil indicator welded version



Dust filter



ISO 8573-1:2010 Class 1 validation certificate

Pneumatech's VT activated carbon towers and vessels are high-efficiency filtration products designed to meet the most demanding industry applications. Examples are pharmaceutical, medical, food & beverage, electronics and chemical industries.

The VT is capable of removing hydrocarbons, odors and oil vapors from compressed air. The activated carbon layers will, by the use Activated carbon vessels for higher flows available on request. Please consult Pneumatech for further support.

1. Flow is measured at reference conditions: 1 bara and 20°C at operating pressure of 7 barg, inlet temperature 20°C & inlet PDP of 3°C at the outlet. of adsorption, reduce the residual oil content to less than 0,003 mg/m3. In combination with Pneumatech G and C filters, the VT meets the requirements of air purity class 1 for total oil, according to ISO 8573-1:2010 in a typical compressed air installation, as was certified by an external body.


Technical specifications for VT 1-9

Pneumatech Variant→ Specifications ↓	Units	VT 1	VT 2	VT 3	VT 4	VT 5	VT 6	VT 7	VT 8	VT 9
Capacity ⁽¹⁾	l/s	20	45	60	95	125	150	185	245	310
	m³/hr	72	162	216	342	450	540	666	882	1116
	cfm	42	95	127	201	265	318	392	519	657
Initial pressure drop over filter when dry	barg	0,015	0,065	0,11	0,085	0,135	0,1	0,145	0,185	0,27
Connection	G/NPT	1/2"	1"	1"	1"	1 1/2"	1 1/2"	1 1/2"	1 1/2"	1 1/2"
Dimensions (A)	mm	490	715	840	715	840	715	840	840	840
	inch	19.29	28.15	33.07	28.15	33.07	28.15	33.07	33.07	33.07
Dimensions (B)	mm	223	223	223	387	387	551	551	715	879
	inch	8.78	8.78	8.78	15.24	15.24	21.69	21.69	28.15	34.61
Dimensions (C)	mm	190	190	190	190	190	190	190	190	190
	inch	7.48	7.48	7.48	7.48	7.48	7.48	7.48	7.48	7.48
Weight	kg	10	15	18	29	34	42	50	67	84
	lbs	22.0	33.1	39.7	63.9	75.0	92.6	110.2	147.7	185.2

1. Flow is measured at reference conditions: 1 bara and 20°C at operating pressure of 7 barg, inlet temperature 20°C & inlet PDP of 3°C at the outlet.

Technical specifications vessel version VT 11-15

Pneumatech Variant→ Specifications ↓	Units	VT 11	VT 12	VT 13	VT 14	VT 15
Capacity	l/s	425	550	850	1100	1800
	m³/hr	1530	1980	3060	3960	6480
	cfm	901	1165	1801	2331	3814
Initial pressure drop over filter when dry	bar	0.070	0.080	0.095	0.095	0,120
Connection	DIN	80	80	100	100	150
Dimensions (A)	mm	2435	2435	2449	2449	2535
	inch	95.9	95.9	96.4	96.4	99.8
Dimensions (B)	mm	1048	1048	1175	1175	1810
	inch	41.3	41.3	46.3	46.3	71.3
Dimensions (C)	mm	1125	1125	1118	1118	1213
	inch	44.3	44.3	44.0	44.0	47.8
Weight	kg	264	302	391	602	882
	lbs	582	666	862	1327	1944



Correction factors

For other compressed air inlet temperatures, please multiply the filter capacity by the following correction factor (Kt):

Inlet temperature	°C	20	25	30	35	40	45	50	55	60
	°F	68	77	86	95	104	113	122	131	140
Correction factor	Kt	1.67	1.43	1.25	1	0.71	0.56	0.37	0.25	0.19

For other compressed air inlet pressures, please multiply the filter capacity by the following correction factor (Kp):

Inlet pressure	barg	3	4	5	6	7	8	9	10	11	12	13
	psig	44	58	73	87	102	116	131	145	160	174	189
Correction factor	Kp	0.57	0.77	0.83	1	1	1	1	1.05	1.05	1.11	1.18

Correction factors for VT 11-15 (for other compressed air inlet temperatures)

Inlet pressure	°C	20	25	30	35	40	45	50	55	60	65
	Kt	1	1	1	1	0,83	0,67	0,59	0,48	0,42	0,33

* for oil free compressors correction factor is always 1



HP - High Pressure Filters

Features & Benefits

- ▶ High reliability
 - High-performance aluminum or stainless steel housings to withstand ultimately high operational pressures
 - Double O-rings, epoxy sealed caps and anti-corrosive coated filter housing
- ▶ Maximum contaminant removal
 - Removal of dry and wet dust, particulates, oil aerosol and water droplets
 - High-efficiency glass fiber and fleece media
- ▶ Significant energy savings & limited system operating costs
 - Optimal design and filter media allow for low pressure drops
- ▶ Easy to service
 - Cartridge color based on type of filtration grade, makes it easy to service

General Specifications

- ▶ Operating pressures: 50-100-350 barg / 725-1450-5075 psig
- ▶ Operating temperature range:
 - 0-120°C/32-248°F (for grades S, D, G & C)
 - 0-35°C/32-95°F (for grade V)
- ▶ Available grades:
 - G: general oil coalescing filtration (max oil carry-over: 0,08 mg/m³)
 - C: fine oil coalescing filtration (max oil carry-over: 0,007 mg/m³)
 - S: general dust filtration (99,92% at MPPS)
 - D: fine dust filtration (99,98% at MPPS)
 - V: oil vapor filtration (max oil carry-over: 0,003 mg/m³)
- ▶ Inlet and outlet connections: threaded
- ▶ Housing material: Aluminum (50 barg/725 psig only) or stainless steel (complete range)



Applications




Laser cutting



PET bottling



Pressure testing of components



High-pressure die casting



Autoclave

Pneumatech's high pressure filters are engineered to cost effectively provide the best air purity and meet today's increasing quality demands up to working pressures of 350 barg/5075 psig. All high pressure filter housings are hydraulically tested to ensure safe and reliable operation at all times. The hydrostatic test certificate is supplied with every filter.

The high pressure filters are available in 3 pressure ranges. The 50 barg (725 psig) range is available in both aluminum and stainless steel housings. As the performance of both filters is the same, the choice between the 2 can be made based on the customer's preference. The 100 barg (1450 psig) and 350 barg (5075 psig) filters are available in stainless steel housings.

Technical specifications for HP 1-9 50 barg Aluminium Filters										
Pneumatech Variant→ Specifications ↓	Units	1	2	3	4	5	6	7	8	9
Capacity ⁽¹⁾	l/s	44	69	125	153	232	347	479	535	889
	m³/hr	160	250	450	550	835	1250	1725	1925	3200
	cfm	94	147	265	324	491	736	1015	1133	1883
Connection	BSP	1/4"	3/8"	1/2"	3/4"	1"	1 1/2"	1 1/2"	2"	2"
Dimensions (A)	mm	63	63	114	114	114	146	146	146	146
	inch	2.48	2.48	4.49	4.49	4.49	5.75	5.75	5.75	5.75
Dimensions (B)	mm	150	190	305	305	395	435	435	435	635
	inch	5.91	7.48	12.01	12.01	15.55	17.13	17.13	17.13	25.00
Weight	kg	0.3	0.3	2.6	2.6	3.3	7.5	7.5	7.5	10
	lbs	0.7	0.7	5.7	5.7	7.3	16.5	16.5	16.5	22.0

Technical specifications for HP 1-7 100 barg Stainless Steel									
Pneumatech Variant→ Specifications ↓	Units	1	2	3	4	5	6	7	
Capacity ⁽¹⁾	l/s	28	88	128	189	333	472	944	
	m³/hr	100	315	460	680	1200	1700	3400	
	cfm	59	185	271	400	706	1001	2001	
Connection	BSP	1/4"	1/2"	3/4"	1"	1"	1 1/2"	2"	
Dimensions (A)	mm	65	65	88	135	135	150	150	
	inch	2.56	2.56	3.46	5.31	5.31	5.91	5.91	
Dimensions (B)	mm	135	250	275	265	480	525	815	
	inch	5.31	9.84	10.83	10.43	18.90	20.67	32.09	
Weight	kg	3.2	5.6	6.1	10.5	14.7	22	28	
	lbs	7.1	12.3	13.4	23.1	32.4	48.5	61.7	

Technical specifications for HP 1-8 50 barg Stainless Steel									
Pneumatech Variant→ Specifications ↓	Units	1	2	3	4	5	6	7	8
Capacity ⁽¹⁾	l/s	28	56	94	139	278	472	567	944
	m³/hr	100	200	340	500	1000	1700	2040	3400
	cfm	59	118	200	294	589	1001	1201	2001
Connection	BSP	1/4"	3/8"	1/2"	3/4"	1"	1 1/2"	2"	2"
Dimensions (A)	mm	85	85	85	110	110	150	150	150
	inch	3.35	3.35	3.35	4.33	4.33	5.91	5.91	5.91
Dimensions (B)	mm	202	227	257	270	422	517	517	817
	inch	7.95	8.94	10.12	10.63	16.61	20.35	20.35	32.17
Weight	kg	1.7	2	2.2	4	5	15	15	21
	lbs	3.7	4.4	4.9	8.8	11.0	33.1	33.1	46.3

Technical specifications for HP 1-6 350 barg Stainless Steel							
Pneumatech Variant→ Specifications ↓	Units	1	2	3	4	5	6
Capacity ⁽¹⁾	l/s	13	31	71	142	208	369
	m³/hr	48	111	255	510	750	1330
	cfm	28	65	150	300	441	783
Connection	BSP	1/4"	1/4"	1/2"	3/4"	1"	1"
Dimensions (A)	mm	41	65	88.5	88.5	150	150
	inch	1.61	2.56	3.48	3.48	5.91	5.91
Dimensions (B)	mm	103	135	210	280	330	480
	inch	4.06	5.31	8.27	11.02	12.99	18.90
Weight	kg	1.6	3.2	5.6	6.1	14.5	17.4
	lbs	3.5	7.1	12.3	13.4	32.0	38.4

Correction factors: 50 barg Aluminum & Stainless Steel										
Operating pressure	barg	4	6	8	10	15	20	30	40	50
	psig	58	87	116	145	218	290	435	581	726
Correction factor	Kp	0.14	0.22	0.28	0.34	0.47	0.56	0.7	0.85	1

Correction factors: 100 barg Stainless Steel										
Operating pressure	barg	20	30	40	50	60	70	80	90	100
	psig	290	435	581	726	871	1016	1161	1306	1451
Correction factor	Kp	0.45	0.57	0.68	0.8	0.84	0.88	0.92	0.96	1

Correction factors: 350 barg Stainless Steel										
Operating pressure	barg	-	-	50	100	150	200	250	300	350
	psig	-	-	726	1451	2177	2903	3628	4354	5080
Correction factor	Kp	-	-	0.73	0.78	0.82	0.87	0.91	0.96	1

1. Flow is referred to an absolute pressure of 1 barg and temperature of 20°C



SLF - Silicone free filters

Features & Benefits

- ▶ Guaranteed silicone-free
 - Plasma-cleaned O-rings, diaphragms & gaskets
 - Metallic cylinders, housing components and fasteners washed at 80°C/176°F
 - Certificates delivered with SLF filters
- ▶ Maximum contaminant removal
 - Removal of dry and wet dust, particulates, oil aerosol and water droplets
 - High-efficiency glass fiber and fleece media
- ▶ Significant energy savings & limited system operating costs
 - Optimal design and filter media allow for low pressure drops
 - High reliability
 - High-performance stainless steel cores, double O-rings, epoxy sealed caps and anti-corrosive coated filter housing


General Specifications

- ▶ Operating pressure range:
2-16 barg / 29-232 psig
- ▶ Operating temperature range:
 - 0-66°C/32-151°F (for grades S, D, G & C)
 - 0-35°C/32-95°F (for grade V)
- ▶ Available grades:
 - G: general oil coalescing filtration (max oil carry-over: 0,1 mg/m³)
 - C: fine oil coalescing filtration (max oil carry-over: 0,01 mg/m³)
 - S: general dust filtration (99,81 % at MPPS)
 - D: fine dust filtration (99,97 % at MPPS)
 - V: oil vapor filtration (max oil carry-over: 0,003 mg/m³)
- ▶ Inlet and outlet connections: threaded



Zooming in


Avoid paint defects



Avoid blisters



Avoid poor adhesion



Avoid craters

The SLF filters are free from substances that could cause defects in the paint. The filters are manufactured in a controlled environment that ensures silicone is not present on the components used or introduced in the production process. All filters are subject to dimensional inspection, pressure &

performance testing and a paint compatibility test.

SLF filters are available in 5 grades, which efficiently prevent dry and wet dust, oil aerosol, oil vapor and water drops from entering your compressed air system.

Technical specifications for SLF Silicone-free filters												
Pneumatech Variant → Specifications ↓	Units	SLF 1	SLF 2	SLF 3	SLF 4	SLF 5	SLF 6	SLF 7	SLF 8	SLF 9	SLF 10	SLF 11
Nominal flow ⁽¹⁾	l/s	9	17	32	44	60	120	150	175	280	390	520
	m ³ /hr	32.4	61.2	115.2	158.4	216	432	540	630	1008	1404	1872
	cfm	19	36	68	93	127	254	318	371	594	827	1102
Connection	G/NPT	3/8"	1/2"	1/2"	3/4" & 1"	1"	1-1/2"	1-1/2"	1-1/2"	2" & 2-1/2"	3"	3"
Dimensions (A)	mm	90	90	90	110	110	140	140	140	179	210	210
	inch	3.54	3.54	3.54	4.33	4.33	5.51	5.51	5.51	7.05	8.27	8.27
Dimensions (B)	mm	61	61	61	98.5	98.5	105	105	105	121	128	128
	inch	2.40	2.40	2.40	3.88	3.88	4.13	4.13	4.13	4.76	5.04	5.04
Dimensions (C)	mm	268	268	323	374	414	520	603	603	689	791	961
	inch	10.55	10.55	12.72	14.72	16.30	20.47	23.74	23.74	27.13	31.14	37.83
Weight	kg	1	1.1	1.3	1.9	2.1	4.2	4.5	4.6	6.9	11	12.6
	lbs	2.2	2.4	2.9	4.2	4.6	9.3	9.9	10.1	15.2	24.3	27.8

1. Flow measured at reference conditions of Nominal pressure: 7 barg(e)/102 psig; temperature: 20°C, 68°F.

Correction Factors										
Inlet pressure	barg	2	4	6	7	8	10	12	14	16
Inlet pressure	psig	29	58	87	102	116	145	174	203	232
Correction factor		0.53	0.75	0.92	1	1.06	1.2	1.31	1.41	1.5



FP & FP HP - Process filters (incl. high pressure)

Features & Benefits

- ▶ Enhanced stainless steel (1,4301) filter housing
 - Designed for applications with high risk of corrosion
 - High hygiene standards
- ▶ Advanced filter cartridge design
 - High filtration efficiency
 - Guaranteed performance over the entire lifetime
 - Low pressure drop
- ▶ Ultimate strength
- ▶ 100% integrity tested (DOP test)
- ▶ All components meet the FDA requirements for contact with food in accordance with the Code of Federal Regulations (CFR), title 21.
- ▶ Wide range of cartridges to suit application needs

General Specifications: FP 1-18

- ▶ Stainless steel process filters
- ▶ Operating pressure: 10-16 barg / 145-232 psig
- ▶ Operating temperature range¹: 0-150°C / 41-302°F
- ▶ Body connections: DIN 11851 (Milk pipe connections)
- ▶ Surface finish: Ra 1.6, electro-polished
- ▶ Inlet and outlet connections: Threaded and flanged.

¹Operating temperature range can vary as per the filter element used.



In process industries where the risk of corrosion of the compressed air system components is high, Pneumatech's FP 1-18 process filter range provides the right solution. The filter housing is made out of stainless steel grade 1,4301. The surface has been smoothened with advanced mechanical and electro-polishing techniques to a level of Ra 1,6. To avoid

micro-organism contamination between the filter head and bowl, these are connected by a milk pipe connection as per DIN 11851.

The filter cartridges are available in 4 different filtration grades for a wide variety of applications. All cartridges have been extensively tested to guarantee the best filtration efficiency over the entire cartridge lifetime.

Technical Specifications FP 1-18


Pneumatech Variant→ Specifications ↓	Units	FP 1	FP 2	FP 3	FP 4	FP 5	FP 6	FP 7	FP 8	FP 9	FP 10	FP 11	FP 12	FP 13	FP 14	FP 15	FP 16	FP 17	FP 18
Flow ⁽¹⁾	m³/hr	75	105	150	225	315	420	600	900	1260	1680	2400	3600	5040	6720	9600	13440	17280	21120
	cfm	44	62	88	132	185	247	353	530	742	989	1413	2119	2966	3955	5650	7910	10171	12431
Operating Pressure	barg/psig	16/232	16/232	16/232	16/232	16/232	16/232	16/232	16/232	16/232	16/232	12/174	12/174	10/145	10/145	10/145	10/145	10/145	10/145
Connections	inch	1/4"	3/8"	1/2"	3/4"	1"	1 1/4"	1 1/2"	2"	2"	2 1/2"	3"	3"	DN100	DN100	DN150	DN150	DN200	DN200
Dimensions	A (mm)	202	232	230	254	275	337	386	457	583	740	1004	1029	986	1240	1311	1351	1496	1496
	A (inch)	8.0	9.1	9.1	10.0	10.8	13.3	15.2	18.0	23.0	29.1	39.5	40.5	38.8	48.8	51.6	53.2	58.9	58.9
	B (mm)	116	120	125	125	136	155	180	180	180	224	224	252	410	410	480	540	660	660
	B (inch)	4.6	4.7	4.9	4.9	5.4	6.1	7.1	7.1	7.1	8.8	8.8	9.9	16.1	16.1	18.9	21.3	26.0	26.0
	C (mm)	76.1	76.1	76.1	76.1	88.9	88.9	114.3	114.3	114.3	139.7	139.7	168.3	219.1	219.1	273	323.9	406.4	406.4
	C (inch)	3.0	3.0	3.0	3.0	3.5	3.5	4.5	4.5	4.5	5.5	5.5	6.6	8.6	8.6	10.7	12.8	16.0	16.0
	D	1/4"	1/4"	1/4"	1/4"	1/4"	1/4"	1/4"	1/4"	1/4"	1/4"	1/4"	1/4"	1"	1"	1"	1"	1"	1"
Mass	kg	1.7	1.9	1.9	2	2.6	3	4.3	4.8	5.3	9	10.8	16.2	45	46	70	80	135	135
	lbs	3.7	4.2	4.2	4.4	5.7	6.6	9.5	10.6	11.7	19.8	23.8	35.7	99.2	101.4	154.3	176.4	297.6	297.6

1. Flow is measured at Reference Conditions: 1 bara and 20°C

Technical specifications for FP HP 1-8

Pneumatech Variant→ Specifications ↓	Units	FP HP 1	FP HP 2	FP HP 3	FP HP 4	FP HP 5	FP HP 6	FP HP 7	FP HP 8
Flow ⁽¹⁾	m³/hr	150	225	315	420	600	900	1260	2400
	cfm	88	132	185	247	353	530	742	1413
Operating Pressure	barg/psig	50/725	50/725	50/725	50/725	50/725	50/725	50/725	50/725
Connections	Inch	1/2"	3/4"	1"	1 1/4"	1 1/2"	2"	2"	3"
Dimensions	A (mm)	231	253	274	336	387	453	580	1005
	A (inch)	9.1	10.0	10.8	13.2	15.2	17.8	22.8	39.6
	B (mm)	125	125	136	155	180	180	180	224
	B (inch)	4.9	4.9	5.4	6.1	7.1	7.1	7.1	8.8
	C (mm)	76.1	76.1	88.9	88.9	114.3	114.3	114.3	139.7
	C (inch)	3.0	3.0	3.5	3.5	4.5	4.5	4.5	5.5
	D	1/4"	1/4"	1/4"	1/4"	1/4"	1/4"	1/4"	1/4"
Mass	kg	2.5	2.6	3.4	3.9	5.6	6.2	6.9	14.1
	lbs	5.5	5.7	7.5	8.6	12.3	13.7	15.2	31.1

1. Flow is measured at Reference Conditions: 1 bara and 20°C



Correction factors

Operating pressure	barg	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	20	30	40	50
	psig	29	44	58	72	87	100	115	130	145	160	174	189	203	218	232	100	290	435	725
Correction factor	Kp	0,38	0,5	0,63	0,75	0,88	1	1,13	1,25	1,38	1,50	1,63	1,75	1,88	2,00	2,13	2,63	3,88	5,13	6,38

FS - Sterile filters

Features & Benefits

- ▶ Enhanced high-grade stainless steel filter housing
 - Designed for applications with high risk of corrosion
 - High hygiene standards thanks to sanitary couplings
- ▶ Advanced filter cartridge design
 - High microbiological filtration efficiency
 - Designed to withstand a large number of sterilization cycles thanks to silicon bonded joint and additional NOMEX layer
- ▶ Stainless steel cylinders and end-caps
- ▶ Low pressure drop
- ▶ 100% integrity tested (DOP test)
- ▶ All components meet the FDA requirements for contact with food in accordance with the Code of Federal Regulations (CFR), title 21.

General Specifications

- ▶ Operating pressure: -16 (12) barg/29-232 (174) psig
- ▶ Operating temperature range¹: -20°C to 150°C/-4°F to 302°F
- ▶ Body connections: DIN 11851 (Milk pipe connections)
- ▶ Surface finish: Ra 0.8, electro-polished
- ▶ Inlet and outlet connections: threaded



Pneumatech's FSI filters are designed for compressed air and gas applications that need to be free from microbiological contamination, and can thus be sterilized regularly.


Pneumatech's FSI filter housings are made out of stainless steel grade 1.4404, with a surface that has been smoothened to a level of Ra 0,8. There is no void inside the entire filter housing; and thus no risk of micro-organism contamination.

The filter elements are manufactured with silicon as bonded joint to ensure robustness at high operating and sterilization

temperatures. For the same reason, an additional NOMEX layer is used at the inside and outside of the filter element. The filter cylinders and end-caps are made out of stainless steel. This all results in a highly efficient and exceptionally strong filter, which keeps its performance after a large number of sterilization cycles.

Filter Model	Pipe Size	Flow Rate		Dimension (mm)				Weight (kg) Approx.	Element Model
	G/NPT	Nm³/h	SCFM	A	B	C	D		
FSI 1	1/4"	75	44	225	116	76.1	1/8	1.7	-
FSI 2	3/8"	105	62	251	120	76.1	1/8	1.9	-
FSI 3	1/2"	150	88	253	125	76.1	1/8	1.9	-
FSI 4	3/4"	225	132	281	125	76.1	1/8	2.0	-
FSI 5	1"	315	185	290	136	88.9	1/8	2.6	-
FSI 6	1 1/4"	420	247	357	155	88.9	1/8	3.0	-
FSI 7	1 1/2"	600	353	408	179	114.3	1/4	4.3	-
FSI 8	2"	900	530	476	179	114.3	1/4	4.8	-
FSI 9	2"	1260	742	602	180	114.3	1/4	5.3	-
FSI 10	2 1/2"	1680	989	762	224	139.7	1/4	9.0	-
FSI 11	3"	2400	1413	1030	224	139.7	1/4	10.8	-
FSI 12	3"	3600	2119	1035	238	154	1/4	16.2	-

Correction factors																
Operating pressure	barg	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
	psig	29	44	58	72	87	100	115	130	145	160	174	189	203	218	232
Correction factor	Kp	0,38	0,50	0,63	0,75	0,88	1	1,13	1,25	1,38	1,50	1,63	1,75	1,88	2,00	2,13



TF DC - Filters with desiccant cartridges

General Specifications

- ▶ Pressure dew point: -40°C
- ▶ Max working pressure: 16 barg/232 psig
- ▶ Operating temperature range:
1,5 – 45 °C/35 - 113 °F

The TF DC consists of a desiccant-filled cartridge, fit inside the standard Pneumatech filter housing. The desiccant dries the compressed air down to -40°C / -40°F but only has a limited lifetime, as it is not regenerated. The DC is therefore meant to dry small amounts of temporarily required compressed air; or as a safety filter downstream the main dryer.

The integrated dust filter collects any dust particles from the desiccant, making downstream dust filtration unnecessary. As with adsorption dryers, upstream oil coalescing filters are recommended to avoid that oily contaminants would stick to the desiccant.

Technical specifications for Desiccant Cartridges

Filter Cartridge Size element → Specifications ↓	Unit	TF 2 DC	TF 4 DC	TF 5 DC	TF 6 DC
Nominal flow ⁽¹⁾	m ³ /hr	0,2	0,7	1	3,7
	cfm	0,12	0,41	0,59	2,18
Total Capacity ⁽²⁾	m ³	5	18	26	82
	ft ³	185,9	647,8	907,4	2898,5
Connections	inch	1/2"	3/4"	1"	1 1/2"
Molecular Sieves Mass	kg	0,056	0,196	0,278	0,878
	lbs	0,12	0,43	0,61	1,94

1. Refers to 10s contact time at 7 barg operating pressure and 20°C.

2. Refers to 20°C inlet temperature, 100% relative humidity and 20% wt desiccant load capacity.



Correction factor

Operating pressure	barg	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
	psig	29	44	58	73	87	102	116	131	145	160	174	189	203	218	232
Pressure correction factor	Kp	0.38	0.5	0.63	0.75	0.88	1	1.13	1.25	1.38	1.5	1.63	1.75	1.88	2	2.13

Correction factor

Operating Temperature	°C	20	25	30	35	40	45
	°F	68	77	86	95	104	113
	Kt	1	0.98	0.97	0.95	0.94	0.92

TF CC & TF HC - Filters with activated carbon & hopcalite cartridges

The cartridge-concept of the Desiccant Cartridges is also applied to activated carbon and hopcalite materials.

The activated carbon cartridge can be considered an intermediate solution between the carbon impregnated cartridge (V) and the activated carbon towers (VT). It provides thus a compact oil vapor filtration solution, albeit with a longer service life than the V filter.

Hopcalite is a catalyst which converts carbon monoxide into carbon dioxide. It is often used in breathing air applications to bring the carbon monoxide concentration below the prescribed thresholds of 15 ppm according to EN 12021 and 5 ppm according to the European Pharmacopeia.

Both solutions include an integrated dust filter. The correct filter sizing is usually based on the requested pressure drop over the filter.

General Specifications

- ▶ Max working pressure: 16 barg / 232 psig
- ▶ Operating temperature range:
1,5 – 45 °C / 35 - 113 °F
- ▶ Service life: Dependent on inlet concentration – please consult Pneumatech for further support.



Technical specifications for Activated Carbon Cartridges

Filter grade→ Specifications↓	Unit	TF 2 CC	TF 4 CC	TF 5 CC	TF 6 CC
Flow Capacity ⁽¹⁾	m³/hr	72	144	216	396
	cfm	42	85	127	233
Connections	inch	1/2"	3/4"	1"	1 1/2"
Pressure Drop at Nominal Flow	mBar	80	110	120	420
	psig	1,16	1,60	1,74	6,09
Activated Carbon Mass	kg	0,04	0,14	0,199	0,627
	lbs	0,1	0,3	0,4	1,4

1. Flow refers to 1 barg and 20°C at 7 barg operating pressure.

Technical specifications for Hopcalite Cartridges

Filter grade→ Specifications↓	Unit	TF 2 HC	TF 4 HC	TF 5 HC	TF 6 HC
Flow Capacity ⁽¹⁾	m³/hr	78	120	198	335
	cfm	46	71	117	197
Connections	inch	1/2"	3/4"	1"	1 1/2"
Pressure Drop at Nominal Flow	mBar	80	110	120	420
	psig	1,16	1,60	1,74	6,09
Hopcalite mass	kg	0,073	0,252	0,358	1,129
	lbs	0,2	0,6	0,8	2,5

1. Flow refers to 1 barg and 20°C at 7 barg operating pressure.

Correction factor

Operating pressure	barg	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
	psig	29	44	58	73	87	102	116	131	145	160	174	189	203	218	232
Pressure correction factor	Kp	0.38	0.5	0.63	0.75	0.88	1	1.13	1.25	1.38	1.5	1.63	1.75	1.88	2	2.13

Competitor spare parts - Alternative line filter cartridges

Features & Benefits

- ▶ Guaranteed performance
 - Filter media selected to offer low differential pressure, high oil removal efficiencies and proven continuous performance
 - Performance equal to or superior than the original
- ▶ Robust design
 - Perforated support cylinders made from corrosion resistant stainless steel, which is twice as strong as galvanized steel
 - Protection layers to protect the glass fiber media from being damaged by the metal cores
- ▶ Guaranteed interchangeability
 - Designed to fit into the original housing
 - Tested in more than 10.000 filters in the field
- ▶ Quality control
 - Full traceability by ink jet marking specific codes on every filter element complying with our IOS 9001 manufacturing procedures





Brands

Domnick Hunter	Dollinger (SPX)
Zander	Finite
Donaldson Ultrafilter	Kaeser
Hydrovane	CompAir
Hiross	Ingersoll Rand
Hankison (SPX)	Parker Balston
Deltech (SPX)	Sullair
CTA	FST
Bea Filtri	And many more

Pneumatech offers superior quality alternative line filters for all major brands including Domnick Hunter, Zander, Donaldson and many more. We can supply filtration solutions for any grade or class of air quality to suit all air compressor needs.

Pneumatech's high quality filter elements use the latest filter media technology and fit seamlessly into OEM machines

and housings. There is no need for modification kits or adapters. The elements offer unrivaled reliability and operate with minimal pressure drop, delivering optimum energy efficiency. All our brand alternatives are tested in accordance with ISO 12500 to guarantee exceptional performance. The filters are extensively tested in the field without any performance issues.



Grade	G		C		S		D		V	
Filter type	General oil coalescing		Fine oil coalescing		General dry dust		Fine dry dust		Oil vapor	
Maximum oil carryover (68°F / 20°C)	0.5 mg/m³		0.01 mg/m³		-		-		0.003 mg/m³	
Pressure loss clean and dry	1 psig	<70 mbar	2 psig	< 140 mbar	1 psig	< 70 mbar	2 psig	< 140 mbar	-	
Wet pressure drop	2 psig	< 140 mbar	3 psig	< 200 mbar	-	-	-	-	-	
Maximum temperature	248°F	120°C	248°F	120°C	248°F	120°C	248°F	120°C	122°F	50°C

Competitor spare parts - Alternative desiccants

Features & Benefits

- ▶ All types of desiccants, matched to the OEM performance
 - Activated alumina
 - Silicagel
 - Molecular sieves
 - Activated carbon
- ▶ High-quality supply at the lowest cost
 - Lowest total cost of ownership
 - Highest crushing resistance
 - Limited anti-aging effect

Why choose Pneumatech for alternative spare parts?

- ▶ Excellent customer service
- ▶ Over 250.000 parts available
- ▶ Same day shipping
- ▶ World class logistics
- ▶ Full track and trace of all shipments
- ▶ Competitive pricing & flexible discounts
- ▶ Customized labelling

Adsorption dryers can only be energy efficient if they contain premium desiccant material. The desiccant used in Pneumatech adsorption dryers is carefully selected from a wide range of European and North-American suppliers; and is suitable for all OEM machines including Domnick Hunter, Donaldson, Boge, Ingersoll Rand, Compair, Kaeser, Almig and many more.



Brands

Domnick Hunter	CompAir
Zander	Ingersoll Rand
Donaldson Ultrafilter	Boge
Hankison (SPX)	Almig
Deltech (SPX)	FST
CTA	KSI
Dollinger (SPX)	Parker Balston
Kaeser	And many more

Protect the environment – treat your condensate

As efficient as the process may be, a compressor inevitably produces more than compressed air alone. One of its by-products is a large volume of condensate, generally an emulsified combination of oil and water that poses a serious environmental risk. Only by treating this condensate in the right way, we can make sure it brings no harm to the environment.

Depending on the location, severe penalties can be charged for dumping oily condensate in the sewage system. The legal threshold of the maximum oil concentration in water varies strongly depending on continent, country and even local region. However, the maximum allowable oil content in drainage to the sewage generally varies between 15 and 20 mg/l



Condensate Management

Pneumatech's condensate management portfolio includes solutions for separating, draining, detecting and treating oily condensate.

Water separators can be used downstream of the compressor instead of - or together with - the air receiver. We offer three types of condensate drains depending on your needs: a timer drain, a mechanical zero loss float drain and an electronic zero loss drain. Also for condensate treatment we give you the choice, i.e. between the cost-competitive ECOBOX solution and our premium, patented OWS technology.

WD - Water detector

Features & Benefits

- ▶ 24/7 peace-of-mind at a reasonable cost
 - Water level as low as 3 cl detected
 - Can be installed at every critical application in the compressed air network
- ▶ Transparency of operation
 - Alarm message on control panel
 - Potential-free contact to trigger alarm in control room
 - Test button for manual drainage
- ▶ Easy mechanical and electrical installation

General Specifications

- ▶ Water detector
- ▶ Operating pressure range:
0,2-16 barg/2,9-232 psig
- ▶ Operating temperature range:
1-60°C/34-140°F
- ▶ Power supply: 230VAC 50/60Hz



Options



Power supply
cable (2m)




Voltage-free contact
cable (5m)

Despite all efforts to make dryers, water separators and drains reliable, a failure can never be ruled out. The consequence of condensate water in your pipe network and operations can be dramatic: from corrosion and ice formation to bad product quality and process malfunctioning.

The installation of a Pressure Dew Point (PDP) sensor downstream brings a solution, but is often a too large investment.

Pneumatech's Water Detector (WD) provides peace-of-mind at an affordable cost. The WD gives an alarm as soon as a 3cl water level is detected. This alarm message is visible, audible and can be routed to a control room thanks to the potential-free contact. The ball valve at the outlet is meant to release water after an alarm situation and is closed during normal operation.

Technical Specifications for WD	
General characteristics	WD
First alarm level (cl)	3
Second alarm level (cl)	6,7
Max. power consumption (W)	10
Electrical connection	Solenoid plug type B - 2+PE
Potential free contact connection	M12 connector A-coding 4-pole Both Normally Open (NO) and Normally Closed (NC) possible
IP Protection	IP65
Physical characteristics	WD
Length (mm / inch)	160 / 6,3
Width (mm / inch)	69 / 2,71
Height (mm / inch)	116 / 4,5
Weight (kg / Lbs)	0,6 / 1,32
Connections	WD
Inlet	G1/2", horizontal + vertical
Outlet	Ball valve for condensate removal
Features	WD
Test button	Yes
Indicative LEDs	Yes
Potential free alarm	Yes



LD 100 - 204 - Zero loss drains

Features & Benefits

- ▶ No loss of compressed air
 - Automatic controlled drainage of condensate without any compressed air leak
- ▶ Maximum reliability
 - Integrated filter to prevent dirt from entering the valve diaphragm
 - Auto-repair algorithm: forced opening/closing cycles of the valve in case of malfunction
- ▶ Transparency of operation
 - Alarm message on control panel when drain is blocked
 - Potential-free contact to trigger alarm in control room
 - Test button for manual drainage
- ▶ Easy installation and maintenance
 - Straightforward mechanical and electrical connections
 - Wear kits available

General Specifications

- ▶ Zero-loss drain
- ▶ Operating pressure range:
0,2-16 barg/2,9-232 psig
- ▶ Operating temperature range:
1-60°C/34-140°F
- ▶ Compressor capacity:
from 180 up to 9500 m³/hr
- ▶ Power supply:
230VAC 50/60Hz
24VAC 50/60Hz
115VAC 50/60Hz



Options



Mounting kits



Wear kits



Power supply cable (2m)



Voltage-free contact cable (5m)

The series of LD zero-loss drains permit a controlled drainage of condensate without any compressed air leaks. All LD drains are equipped with an integrated storage tank, inside which a level sensor has been mounted. The sensor is controlled by an intelligent electronic circuit based on an 8-bit microprocessor logic. All drain functions are displayed on the control panel*. A test push button is available on the control panel for manual drainage. A built-in filter prevents the solenoid valve from clogging.

In case of trouble, the control circuit unlocks the drain pipes by carrying out a series of forced opening/closing cycles of the

solenoid valve. If this is not enough, the malfunction is reported outside by an alarm with potential-free contact to draw the attention of maintenance staff*.

The LD drains are produced in 10 different models with different flow rates. All versions are suitable for working with any type of condensate water.

*not applicable for the smallest model LD100

Technical specifications for LD 100 - 204										
Pneumatech Variant → Specifications ↓	LD100	LD101	LD 101 Compact	LD 101 L	LD200	LD200 L	LD202	LD202 L	LD203	LD204
General characteristics										
Drain capacity (l/h)	1.6	4.03	3.3	5	8.07	10	16.14	20	85	200
Compressor capacity (m³/hr) ⁽¹⁾	180	450	378	450	900	900	1800	1800	9500	18000
Compressor capacity (cfm) ⁽¹⁾	106	265	222	265	530	530	1059	1059	5591	10594
Max. power consumption (W)	10									
Electrical connection	Solenoid plug type B – 2+PE									
Potential free contact connection	M12 connector A-coding 4-pole									
IP Protection	IP65	IP65	IP65	IP65	IP 65	IP 65	IP 65	IP 65	IP 65	IP 65
Physical characteristics										
Length (mm)	136	163	160	163	163	163	163	163	188	247
Length (inch)	5.4	6.4	6.3	6.4	6.4	6.4	6.4	6.4	7.4	9.7
Width (mm)	60	69	69	69	69	69	69	69	130	130
Width (inch)	2.4	2.7	2.7	2.7	2.7	2.7	2.7	2.7	5.1	5.1
Height (mm)	120	140	120	140	155	155	214	214	230	230
Height (inch)	4.7	5.5	4.7	5.5	6.1	6.1	8.4	8.4	9.1	9.1
Weight (kg)	0.42	0.6	0.5	0.6	0.7	0.7	1.2	1.2	2.8	3.45
Weight (lbs)	0.9	1.3	1.1	1.3	1.5	1.5	2.6	2.6	6.2	7.6
Connections										
Inlet	G1/2"	G1/2"	G1/2" (F)	G1/2" (F)	G1/2" (F)	2 x G1/2" (F)	G1/2" (F)	2 x G1/2" (F)	2 x G1/2" (F)	2 x G1/2" (F) + 1x G3/4" (F)
Outlet	1 x Ø12	1 x Ø12	1 x Ø12	1 x Ø12	1 x Ø12	1 x Ø12	1 x Ø12	1 x Ø12	1 x Ø12	1 x Ø12
Features										
Test button	Yes									
Indicative LEDs	No	Yes								
Potential free alarm	No	Yes (NC/NO)								

1. The calculation of compressor capacity is based on the maximum condensate drainage of a compressor aftercooler in moderate climate conditions.

TD - Timer drain

Features & Benefits

- ▶ Guaranteed reliability
 - Robust solenoid, made in Europe
 - Integrated Y-filter to prevent dirt from entering the valve
 - Large cross-section openings
- ▶ Endless flexibility
 - No limitations in air flow
 - Cycle and valve opening intervals can be set independently of each other
- ▶ IP65 enclosed
- ▶ Transparency of operation
 - Test button and operation indicator

Pneumatech's TD condensate drains discharge the condensate automatically, based on pre-set time intervals. The opening and closing times can be set with high flexibility, which make the drains suitable for almost all capacities. TD drains are selected in heavy-duty operations, where the large cross-sections opening and the simplicity of the drain are highly valued.

High-pressure TD drains are available on request.



Technical specifications

Pressure range	0-16 barg/ 0-232 psig
Supply voltage	24VAC 50/60Hz & 230VAC 50/60Hz (CE)
Electrical connection	DIN43650A
Inlet/outlet connections	G 1/2" (CE) NPT 1/2" (UL)
Environmental protection	IP65
Max. compressor capacity	No limit
Min/Max operating temperature	1-50°C/ 34-122°F
Timer cycle	On: 0,5 – 10 s; Off: 0,5 – 45 min. including test feature
Valve type	2/2 direct acting
Valve orifice	4.5 mm- 0,177"
Valve seal	FKM

MD - Mechanical zero-loss float drain

Pneumatech's MD drain discharges the condensate automatically and without compressed air losses up to 16 barg. A floating body rises and falls with the condensate level in a collecting chamber; and opens/closes a mechanical drain valve. The condensate collecting chamber is closed off from the compressed air flow when the drain is depressurized.

The drain is equipped with an integrated venting function, which prevents the risks of possible air slots. The MD has a well-proven, rugged metal design with threaded connections at inlet and outlet.



Features & Benefits

- ▶ No loss of compressed air
 - Automatic controlled drainage of condensate without any compressed air leak
- ▶ Plug-and-play solution
 - No power supply needed
 - No programming or calibration
- ▶ Guaranteed reliability
 - Large cross-section openings
 - Well-proven, rugged aluminum design
 - Integrated venting function to prevent air slots
- ▶ Transparency of operation
 - Manual drain valve for system discharge and operational check

Technical specifications

Pressure range	0-16 barg / 0-232 psig
Inlet/outlet connections	G ½" (CE)
Max. water discharge capacity	250 l/h @ 7 barg / 0,147 cfm @ 101 psig 360 l/h @ 16 barg / 0,212 cfm @ 232 psig
Max compressor capacity (without dryer)	5.400 m³/hr / 3178 cfm
Length	156 mm / 6,14"
Width	108 mm / 4,25"
Height	111 mm / 4,37"
Weight	0,9 kg / 2 lbs

ECOBX 2 - 4 - Oil water separators

Features & Benefits

- ▶ Excellent performance
 - 2-stage filtration with advanced adsorption media
 - After separation, water contains oil levels below 15 ppm⁽¹⁾
 - Emulsion treatment possible (on request)
- ▶ Eliminating potential health issues
 - No standing or stagnant water
- ▶ Plug-and-play installation and service
 - Connection points at inlet
 - Compact footprint
 - No pre-soaking required
- ▶ Time-based service indicator and sampling kit (standard) to verify outlet concentration on a regular base.



Options



Extra 4 port kit

Pneumatech extends its cost-competitive ECOBOX condensate cleaning solution with 3 more models, up to 1400 m³/hr. The models are designed according to the same success factors: reliable double adsorption with recycled glass media, compact footprint, and easy installation and service.

Additionally the ECOBOX 2 - 4 has 4 connections points at the inlet; and a sample test point at the outlet.

Technical specifications for ECOBOX 2-4				
		ECOBX 2	ECOBX 3	ECOBX 4
Maximum rated flow - normal climate ⁽²⁾	l/s	53	158	389
	m ³ /hr	190	570	1400
	cfm	112	335	824
Connections	Inlet	4 x 12mm	4 x 12mm	4 x 12mm
		4 x 1/2"	4 x 1/2"	4 x 1/2"
	Outlet	12mm	20mm	20mm
		1/2"	3/4"	3/4"
Weight	kg	2,7	3,6	14,8
	lbs	6,0	7,9	32,6
Dimensions	Length (mm)	215	345	432
	Length (inch)	8,46	13,58	17,01
	Width (mm)	257	282	495
	Width (inch)	10,12	11,10	19,49
	Height (mm)	500	654	989
	Height (inch)	19,69	25,75	38,94
Service life for filter ⁽³⁾		4,000 Operating Hrs	4,000 Operating Hrs	4,000 Operating Hrs

- 15ppm is generally well below the acceptance level for disposal in the sewage, but due to strongly varying international and local regulations, it is the user's responsibility to consult local waste water discharge regulations and ensure compliance.
- In tropical climates (high ambient temperatures and humidity levels), the air generally contains more water vapor. The extra condensate, generated during the compression and cooling process of the air, shortens the contact time in the device, leaving less time for the media to absorb the oil. Climatic conditions used in the table above are defines as follows:
 - a. Cold climate conditions: average ambient temperature of 20°C/ 68°F- relative humidity of 50 %
 - b. Normal climate conditions: average ambient temperature of 25°C/ 75°F - relative humidity of 50%
 - c. Hot climate conditions: average ambient temperature of 35°/ 95°F - relative humidity of 70 %
- Pneumatech assumes as well maintained compressor plant and reasonable operating conditions. Performance on mineral or mineral-based lubricants should be as above, irrespective of compressor type, condensate drain technology or climate, provided the condensate produced is not a stable emulsion.

OWS 25 - 5300 - Oil water separators

Features & Benefits


- ▶ Stable and reliable performance for weak as well as stable emulsions thanks to patented dual stage filtration technology
 - Filtering all types of condensate
 - No risk of spillage thanks to large capacity chamber design
- ▶ Eliminating all potential health issues
 - No standing or stagnant water
 - Optional anti-bacteria kit
- ▶ Accurate and quick indication of filter replacement thanks to saturation indicator
- ▶ Overflow indicator signalizes if the emulsion is flowing too quickly through the media
- ▶ DIBT certified
- ▶ Hassle-free maintenance with genuine service kits
- ▶ Optimized serviceability
 - Easy to remove first stage filtration bags
 - 2nd stage filter cartridge adapted from outside for easy exchange
 - Built-in wheels for larger cartridge for easy transport

General Specifications


- ▶ Service interval 4000 hours
- ▶ Oil water separator
- ▶ Clean wastewater with oil content at the outlet at just 10ppm, and the possibility of going to as low as 5ppm depending on the set-up
- ▶ Flow range at mild ambient conditions: 43-8998 m³/hr/25-5296 cfm
- ▶ Standard version with activated carbon for unstable emulsions such as those containing mineral oil
- ▶ Organoclay version for stable emulsions with synthetic oil as well as for polypropylen based lubricants




Options



Multiple inlet manifold



Wall mount brackets



Spill container



Photoelectric sensor



Pneumatech offers with the new OWS generation a patented way to turn oily condensate from mineral oil, synthetic oil as well as polypropylene based lubricants into harmless water that can be drained away, while capturing the oil to be easily disposed of in an environmentally friendly manner. The multi-stage separation process, using both buoyant oleophilic filters and activated carbon/organoclay ensures exceptional performance, lower disposal costs and trouble free operation.

The OWS range eliminates oil through multi-stage filtration rather than the conventional gravity systems which have limitations on the type of condensate that can be treated. As a result, the OWS separator capacity is not linked to the type of emulsion collected since. The OWS range also eliminates stable emulsions by using organoclay cartridge in the second filtration stage.

Technical specifications for OWS 75 – OWS 5000

Installation Type	Pneumatech Variant→ Specifications ↓	Units	OWS 25	OWS 53	OWS 106	OWS 180	OWS 360	OWS 636	OWS 1325	OWS 2650	OWS 5300
Complete installation ⁽¹⁾ with Dryer ⁽²⁾	Cold Climate ³	m ³ /hr ⁽⁶⁾	58	119	241	407	817	1440	2999	5998	11995
		cfm ⁽⁶⁾	34	71	141	240	480	848	1766	3532	7065
	Mild Climate ⁴	m ³ /hr ⁽⁶⁾	43	90	180	306	612	1080	2250	4500	9000
		cfm ⁶	25	53	106	180	360	636	1325	2650	5300
	Hot Climate ⁵	m ³ /hr ⁽⁶⁾	22	43	86	148	299	526	1094	2189	4378
		cfm ⁽⁶⁾	13	26	52	88	175	309	645	1289	2578
Complete installation ⁽¹⁾ without Dryer ⁽²⁾	Cold Climate ³	m ³ /hr ⁽⁶⁾	72	151	299	511	1019	1800	3751	7499	15001
		cfm ⁽⁶⁾	42	88	133	300	601	1060	2208	4417	8833
	Mild Climate ⁴	m ³ /hr ⁽⁶⁾	54	112	227	382	767	1350	2812	5627	11250
		cfm ⁽⁶⁾	32	66	133	225	451	795	1656	3313	6625
	Hot Climate ⁵	m ³ /hr ⁽⁶⁾	32	61	122	205	410	724	1512	3020	6041
		cfm ⁽⁶⁾	18	36	71	121	242	427	890	1779	3558
Connections		inlet (BSP/NPT)	1x1/2"	2x1/2"	2x1/2"	2x3/4"	2x1/2"	2x3/4"	2x3/4"	2x3/4"	-
		outlet (BSP/NPT)	1x1/2"	1x1/2"	1x1/2"	1x3/4"	1x1/2"	1x3/4"	1x3/4"	1x1"	-
Dimensions	Length	mm	470	680	680	750	750	945	945	945	-
		inch	18,5	27	27	30	30	37	37	37	-
	Width	mm	165	255	255	546	546	650	695	1185	-
		inch	6,5	10	10	21,5	21,5	26	27	47	-
	Height	mm	610	762	762	889	1041	1092	1092	1092	-
		inch	24	30	30	35	41	43	43	43	-
	Weight	kgs	4	13	15	25	26	28	30	60	-
		lbs	9	29	33	55	57	62	66	132	-

Reference conditions

Relative air humidity: 60%

Air inlet temperature: 25°C (77°F) Running hours per day: 12 hrs

Effective working pressure: 7 bar (102 psi)

Note: Capacity is based on the compressor running at 7 barg / 100 psig for 12 hours per day, with all condensate from the compressor, the air receiver, the filters and fridge dryer being piped into the unit.

Correction factors

Relative humidity	%	0.5	0.6	0.7	0.8	0.9	-
	Correction factor	1.10	1.00	0.85	0.74	0.66	-
Ambient temperature	°C	15	20	25	30	35	40
	Correction factor	1.33	1.17	1.00	0.76	0.50	0.30
Running hours per day	hrs	12	18	24	-	-	-
	Correction factor	1	0.88	0.75	-	-	-

CA - Air cooled aftercoolers

Features & Benefits

- ▶ Highly efficient axial fans
- ▶ Cooling down to 10°C/18°F above ambient
- ▶ Negligible pressure drop
- ▶ Robust construction and compact design
- ▶ Easy to dismantle for cleaning

General Specifications

- ▶ Air cooled aftercooler
- ▶ Max. operating pressure: 15 barg/218 psig
- ▶ Operating temperature: 170°C/338°F
- ▶ Approach above ambient temperature: 10°C/18°F
- ▶ Flow Rate: 66 to 4500 Nm³/hr (39 to 2649 cfm)



Compressed air will always be 100% saturated with water when it leaves a compressor. But also the outlet temperature has an important influence on the water load downstream the compressor. In order to minimize the load – and thus size – of the downstream refrigeration or adsorption dryer, it is therefore recommended to install a highly efficient aftercooler between the compressor and the dryer.


Pneumatech's air cooled aftercoolers CA 1-14 consist of a reliable axial fan with supreme efficiency. The fan forces ambient air over the copper tubes and aluminum fins of the heat exchanger. Hence the compressed air is cooled down to only 10°C/18°F above ambient temperature.

In this way, the CA is a simple product, but with a major impact on the investment and lifecycle cost of your downstream equipment!

Technical specifications for air cooled aftercoolers CA 1-14

Pneumatech Variant → Specifications ↓	Units	CA 1	CA 2	CA 3	CA 4	CA 5	CA 6	CA 7	CA 8	CA 9	CA 10	CA 11	CA 12	CA 13	CA 14
Flow ⁽¹⁾	m³/hr	66	126	222	294	390	522	774	990	1260	1560	1890	2520	3090	4500
	scfm	39	74	131	173	230	307	456	583	742	918	1112	1483	1819	2649
PipeSize	inch	G1"	G1"	G1 1/2"	G1 1/2"	G2"	G2"	G2"	G2 1/2"	DN100	DN100	DN100	DN100	DN125	DN125
Power Supply	Ph/Volt/Fr	1/230/50	1/230/50	3/400/50	3/400/50	3/400/50	3/400/50	3/400/50	3/400/50	3/400/50	3/400/50	3/400/50	3/400/50	3/400/50	3/400/50
Fan	Ø mm -W	Ø250-45W	Ø250-45W	Ø350-110W	Ø400-130W	Ø500-540W	Ø500-540W	Ø630-370W	Ø630-370W	Ø800-1470W	Ø800-1470W	Ø800-1470W	Ø800-1470W	2xØ800-1470W	2xØ800-1470W
Dimensions	A (mm)	957	957	1024	1024	1136	1136	1450	1450	1634	1634	1800	2000	2090	2300
	A (inch)	37.7	37.7	40.3	40.3	44.7	44.7	57.1	57.1	64.3	64.3	70.9	78.7	82.3	90.6
	B (mm)	320	320	368	368	355	355	465.5	465.5	564.1	564.1	790	795	830	850
	B (inch)	12.6	12.6	14.5	14.5	14.0	14.0	18.3	18.3	22.2	22.2	31.1	31.3	32.7	33.5
	C (mm)	400	400	490	490	764	764	775	775	1616	1616	1560	1740	1850	2010
	C (inch)	15.7	15.7	19.3	19.3	30.1	30.1	30.5	30.5	63.6	63.6	61.4	68.5	72.8	79.1
Weight	kg	19	20	27	29	44	48	61	66	127	143	148	166	212	315
	lbs	41.9	44.1	59.5	63.9	97.0	105.8	134.5	145.5	280.0	315.3	326.3	366.0	467.4	694.5

1. Flow refers to 1 barg and 20°C at 7 barg operating pressure.



Note : In- and outlet connections can be chosen freely in the 4 corners of the heat exchanger

CW 1 - 17 - Water cooled aftercoolers

Features & Benefits

- ▶ Close temperature approach thanks to counter-current heat exchange
- ▶ Robust shell-and-tube design: stainless steel tubes within coated shell
- ▶ Negligible pressure drop
- ▶ Compact design
- ▶ Detailed calculations available on request

General Specifications

- ▶ Water cooled aftercooler
- ▶ Operating pressure of compressed air: 0-16 barg/0-232 psig
- ▶ Operating temperature of compressed air: 2-200°C/35-392°F
- ▶ Flow Rate: 132 to 45570 Nm³/hr/
78 to 26821 cfm




Compressed air will always be 100% saturated with water when it leaves a compressor. But also the outlet temperature has an important influence on the water load downstream the compressor. In order to minimize the load – and thus size – of the downstream refrigeration or adsorption dryer, it is therefore recommended to install a highly efficient aftercooler between the compressor and the dryer.

Pneumatech's water cooled aftercoolers CW 1-17 are robust shell-and-tube heat exchangers with excellent efficiency. Hot compressed air or gas passes through the stainless steel tubes while cooling water flows in counter-current around the tubes. This results in a minimal temperature difference between the outgoing compressed air and the incoming cooling water. Detailed design calculations are available on request.

Technical specifications for CW 1-17																		
Pneumatech Variant→ Specifications ↓	Units	CW 1	CW 2	CW 3	CW 4	CW 5	CW 6	CW 7	CW 8	CW 9	CW 10	CW 11	CW 12	CW 13	CW 14	CW 15	CW 16	CW 17
Flow ⁽¹⁾	m ³ /hr	132	235	367	661	955	1323	2205	3087	3969	7056	8967	11025	16170	22050	26460	33810	45570
	cfm	78	138	216	389	562	779	1298	1817	2336	4153	5278	6489	9517	12978	15574	19900	26821
Connections Air side	inch	DN 50	DN 50	DN 50	DN 50	DN 50	DN 80	DN 80	DN 125	DN 125	DN 200	DN 200	DN 250	DN 300	DN 400	DN 400	DN 450	DN 500
Connections Water side	inch	DN 20	DN 20	DN 20	DN 20	DN 20	DN 20	DN 20	DN 32	DN 32	DN 50	DN 65	DN 80	DN 80	DN 100	DN 150	DN 200	DN 200
Operating Pressure	barg	0-16	0-16	0-16	0-16	0-16	0-16	0-16	0-16	0-16	0-16	0-16	0-10	0-10	0-10	0-10	0-10	0-10
	psig	0-232	0-232	0-232	0-232	0-232	0-232	0-232	0-232	0-232	0-232	0-232	0-232	0-232	0-232	0-232	0-232	0-232
Dimensions	A (mm)	806	816	816	870	870	1500	1510	1300	1300	1300	1300	1300	1300	1300	1300	1300	1300
	A (inch)	31.7	32.1	32.1	34.3	34.3	59.1	59.4	51.2	51.2	51.2	51.2	51.2	51.2	51.2	51.2	51.2	51.2
	B (mm)	60.3	60.3	60.3	60.3	60.3	88.9	88.9	139.7	139.7	219	219	273	323.9	406	406	457	508
	B (inch)	2.4	2.4	2.4	2.4	2.4	3.5	3.5	5.5	5.5	8.6	8.6	10.7	12.8	16.0	16.0	18.0	20.0

1. Refers to 1 barg and 20°C at 7 barg operating pressure and inlet temperature of 120°C.

Please consult Pneumatech team for accurate sizing based on the operating conditions. Given table is only valid at the reference conditions hence the sizing has to be validated to confirm the performance of the selected version.



Keeps the pressure up

Did you know that a pressure drop of 1 bar results in a 7% increase of your energy consumption? To avoid such losses you need to ensure that your piping system is properly sized, leak-free and retains the pressure. AIRnet is an engineered piping system that can be sized and planned to deliver the desired pressure for a variety of high performing applications.



Piping systems

The optimal piping network is sized, planned and installed to support sustainable operational excellence in the production process. Material and product design, installation and maintenance costs, flexibility and safety. They all influence your total cost of ownership and the level of efficiency in your production. If you are looking for a high performing and effortless system that can be customized to fit any production site, AIRnet will turn out to be the best investment choice you can make.


AIRnet - Aluminium range

Features and Benefits

- ▶ Time and tooling
 - Quick connections with no need to crimp, thread, solder or glue the pipe
 - No heavy tooling or machinery required
 - PF series and black series can be connected to any existing network via simple use of adaptor unions and nipple sockets
 - PF series is assembled by hand, a push of the pipe into the fitting is all it takes
- ▶ Modularity
 - Easy to handle and easy to work with lightweight materials
 - Modular design supports extensions and modifications to meet new demands
 - Components are interchangeable and reusable after disassembly
 - Quickdrops are easily mounted, both horizontally and vertically
- ▶ Sustainability
 - Optimized inner body design minimizes flow resistance and pressure drop in the fittings
 - Low friction factor and seamless connections minimize pressure drops in the pipe network
 - Superior sealing technology ensures a leak free system and maintains performance over time
 - Durable and corrosion resistant materials offers a maintenance free system
- ▶ Safety
 - Safety factor of 4 for all diameters (burst pressure)
 - Camera control and automatic assembly guarantee zero defect manufacturing
 - Plastic components and pipe clips comply to UL 94 HB and UL 94 V-2 for flammability
 - Torque indicators ensure sufficient torquing



Options




Fittings



Fittings



White torque indicators



Aluminium
RAL 5012



Aluminium
RAL 6018

Pipes 20 (¾") - 25 (1") - 40 (1 ½") - 50 (2") - 63 (2 ½") - 80 (3") - 100 (4") - 158 (6") mm

Applications	Compressed Air and Vacuum	EN standard
Additional gases	Nitrogen, Helium, Argon, Neon, Xenon and Krypton	-
Material	Extruded aluminum alloy EN AW-6060 T6 (similar to alloy 6063T5)	EN 755-2 (ASTM B241)
Safety factor	4 for all diameters (burst pressure)	(Calculated according to ASME B31.1)
Working pressure	Max 16 bar(g) (Max 232 psig)	-
Working temperature	-20°C to 80°C (-4°F to 176°F)	-
Vacuum level	13 mbar(a) (0.189 psia)	-
Dewpoint	Lowest allowable pressure dewpoint is -70°C (-94°F)	-
Outside treatment	Polyester powder paint (QUALICOAT certified)	-
Inside treatment	Chrome free conversion treatment	-
Colors	Blue RAL 5012 and Green RAL 6018 : only 20-25mm (¾"-1")	-

Fittings 20 (¾") - 25 (1") - 40 (1 ½") - 50 (2") mm (pf series)

Connection	Push to fit technology	EN standard
Materials	Engineered polymer PA6 - GF30 fiberglass reinforcement Aluminum high pressure die casting EN AC-46100 (Similar to A03830) Wrought aluminum alloy EN AW-6026 (Similar to alloy 6082)	EN 1706 (ASTM B85) EN 755-2 (ASTM B221)
Seal fittings	NBR 70 Sh A (PTFE coating on pipe seal)	-

Fittings 63 (2 ½") - 80 (3") mm (black series)

Connection	Torque to grip technology	EN standard
Materials	Aluminum high pressure die casting EN AC-46100 (Similar to A03830) Aluminum permanent mold casting EN AC-43100 (Similar to A13600) Wrought aluminum alloy EN AW-6026 (Similar to alloy 6082)	EN 1706 (ASTM B85) EN 1706 (ASTM B85) EN 755-2 (ASTM B221)
Seal fittings	NBR 70 Sh A	-

Fittings 100 (4") - 158 (6") mm

Connection	Bolt clamp technology	EN standard
Materials	Aluminum permanent mold casting EN AC-43100 (Similar to A13600) Stainless Steel EN 1.4301 (Similar to alloy 304)	EN 1706 (ESTM B85) EN 10088-2 (AISI 304)
Seal fittings	NBR 70 Sh A	-

AIRnet - Stainless steel range

AIRnet stainless steel is a piping system designed to deliver a fast, easy, reliable and clean distribution network for compressed air, nitrogen, vacuum specifically for industries that demand the highest quality of air.

Features and Benefits

- No corrosion, leak resistant and 10 year guarantee
 - Press fit system ensures fast installation with minimal tools
 - No welding, no threading: just push & press
 - Silicone free system
 - FKM Seal (approved by all international regulating bodies for Pharma, F&B)
 - Can be used for clean room applications (316 L)
 - Considerable savings on the labor cost
- Advantage of press connection
- 20% enlargement of the sealing surface area with a security seal ring minimizes the risk of accidents
 - Eliminates the risk of sealing ring being pressed out or damaged
 - The fit between the sealing ring and the groove makes the pipes insertion easier.



Airnet product information

Product range	Pipes SS304L: D15 (½"), D28 (1"), D35 (1 ¼"), D42 (1 ½"), D54 (2"), D76 (2 ¾"), D89 (3 ½"), D108 (4") Pipes SS316L: D15 (½"), D28 (1"), D42 (1 ½")	-
Applications	Compressed Air, Nitrogen, Vacuum...	-
Material	Stainless Steel AISI 304L 1.4301 Stainless Steel AISI 316L 1.4404	EN10088 ASTM A666
Safety factor	4, Burst pressure > 64 Bar (> 928 PSI)	-
Working pressure	16 Bar (232 PSI)	-
Working temperature	-20°C to 120°C (- 4°F to 248° F)	-
Vacuum level	20 mbar (0.29 PSI) abs	-
Dewpoint	Lowest allowable pressure dewpoint is -70°C (-94°F)	-
Treatment	Annealing	-
Fittings	D15 (½"), D28 (1"), D35 (1 ¼"), D42 (1 ½"), D54 (2"), D76 (2 ¾"), D89 (3 ½"), D108 (4")	-
Connection	Press fit system	-
Materials	Stainless steel AISI 316L 1.4404	EN10088 ASTM A666
Seal fittings	FKM (fluoroelastomer)	-





Pneumatech reserves the right to change or revise specifications and product design in connection with any features of our products. Such changes do not entitle the buyer to corresponding changes, improvements, additions or replacements for equipment previously sold or shipped.

© 2021 Pneumatech. All rights reserved.

