


Suitable sensors for Check Box M6, Check Box M1-M5, Check Box 500 mobile, PDP C

Consumption meters insertion-version	Order no.
Flow Check Universal flow meter, Max version (185 m/s), probe length 220 mm, incl. 5 m connection cable to mobile devices	2255332524
Flow Check Universal flow meter, High-Speed version (224 m/s), probe length 220 mm, incl. 5 m connection cable to mobile devices	2255332525



Flow Check
Universal

Flow meters inline version	Order no.
Flow Check 1 with integrated measuring section, (R 1/4" DN 8)	2255330393
Flow Check 2 with integrated measuring section, (R 1/2" DN 15)	2255330394
Flow Check 3 with integrated measuring section, (R 3/4" DN 20)	2255330395
Flow Check 4 with integrated measuring section, (R 1" DN 25)	2255330396
Flow Check 5 with integrated measuring section, (R 1 1/4" DN 32)	2255330397
Flow Check 6 with integrated measuring section, (R 1 1/2" DN 40)	2255330398
Flow Check 7 with integrated measuring section, (R 2" DN 50)	2255330399




Flow Check

Dew point sensors	Order no.
PDP Sens 2 set dew point sensor, -80 - + 20 ° Ctd incl. measuring chamber mobile and 5 m connection cable to mobile devices	2255332526
PDP Sens 1 set dew point sensor, -20 - + 50 ° Ctd incl. measuring chamber mobile and 5 m connection cable to mobile devices	2255332527




PDP Sens

Connection cable for flow check universal/ flow check and pdp sens 1/2 sensors	Order no.
Connection cable for Flow/ PDP sensors to mobile devices, ODU/M12, 5 m	2255332516
Extention cable for mobile für mobile equipment, 10 m	2255332517



ODU/M12



Extention cable

Pressure probes	± 1% Accuracy	± 0,5% Accuracy
Standard pressure probe PMH 16, 0-16 bar	2255330414	2255332478
Standard pressure probe PMH 40, 0...40 bar	2255330415	2255332479
Standard pressure probe PMH 1.6, 0. 1.6 bar abs.	-	2255332480
Standard pressure probe PMH 10, 0-10 bar	2255332477	2255332481
Standard pressure probe PMH 100, 0...100 bar	-	2255332482
Standard pressure probe PMH 250, 0...250 bar	-	2255332483
Standard pressure probe PMH 400, 0...400 bar	-	2255332484
Precision pressure probe PMH -1+15 bar, ± 0.5% accuracy of. f.s.	-	2255332485
Differential pressure probe 1.6 bar diff.	-	2255332486
Calibration certificate pressure, 5 calibration points for the whole measuring range	2255332487	-



Temperature sensors	Order no.
Bendable temperature probe PT 100 (2-wire) class A, length: 300 mm, d=3 mm, -70°C to +500°C, connect cable PFA, 2 m with ODU-plug (8 pole) to mobile instruments	2255332526
Screw-in temperature sensor PT 100 class A, length 300 mm, d = 6 mm, with transmitter 4-20 mA = -50 °C-+ 500 °C (2-wire)	2255332488
Cross-band surface temperature probe, thermocouple Type K, with integrated transducer 4...20 mA = 0°C...+180°C, 2 m connect cable (PVC) with ODU-plug (8-pole) to mobile instruments	2255332527
Cable temperature sensor PT 100 class A (4-wire), length: 300 mm, d = 6 mm, -70 - + 260 °C, 5 m connect cable PFA with open ends	2255332491
Cable temperature sensor PT 100 class A (4-wire), length: 100 mm, d = 6 mm, -70 - + 260 °C, 5 m connection cable PFA with open ends	2255332492
Cable temperature sensor PT 100 class A (4-wire), length: 200 mm, d = 6 mm, -70 - + 260 °C, 5 m connect cable PFA with open ends	2255332493
Magnetic surface temperature sensor, magnet 39x26x25 mm, PT 100 class B (2-wire), -30-+ 180 °C, 5m connection cable PFA with open ends	2255332494
Compression fittings: 6mm; G 1/2" teflon clamping ring pressure-tight up to 10 bar. Material: stainless steel, application area: max. + 260 °C	2255332495
Compression fittings: 6mm; G 1/2" teflon clamping ring pressure-tight up to 16 bar. Material: stainless steel, application area: max. + 260 °C	2255332496
Calibration certificate temperature, 2 calibration points	2255332497



2255332488



2255332527




2255332526




2255332491

Connection cables for pressure sensors / temperature sensors	Order no.
Connection cable for pressure, temperature and external sensors to mobile devices, ODU/open ends, 5 m	2255332514
Connection cable for pressure, temperature and external sensors to mobile devices, ODU/open ends, 10 m	2255332515
Extension cable for mobile instruments, ODU / ODU, 10 m	2255332517
ODU plug for connection to mobile devices	2255332528



Extension cable



Connection cable/ODU



ODU connector

Clamp on ammeter	Order no.
Clamp-on ammeter 0 - 1000 A TRMS incl. 3 m connection cable	2255332529
Clamp-on ammeter 0 - 400 A TRMS incl. 3 m connection cable	2255332530



Clamp-on ammeter